

VG2030m

20" DIGITAL MEDIA GRAPHIC SERIES LCD

WITH SWIVEL AND HEIGHT ADJUST

Expand your view.

The ViewSonic® 20" VG2030m expands your desktop visual experience with its spacious screen space. The stylish, slim design blends high-end features such as FAST 8MS VIDEO RESPONSE, OPTISYNC® ANALOG AND DIGITAL INPUTS and integrated speakers and amplifier. The VG2030m is a great choice for business applications that include mixed data, audio, graphics and video content. Graphics professionals and gamers will love the BLUR-FREE, FULL MOTION VIDEO AND CRYSTAL-CLEAR GRAPHICS RENDERING. Enjoy flexible connectivity with VGA and digital DVI sources. Reduce desktop clutter and accent your office décor by mounting the VG2030m on the wall. KENSINGTON® SECURITY PORT OFFERS THEFT DETERRENCE and the OSD/Power lock ensures your optimal screen settings remain in place.



ENHANCE PRODUCTIVITY WITH THIS ERGONOMIC BIG SCREEN DISPLAY

- > **ClearMotiv® 8ms video response time**
Fast 8ms video response delivers broadcast-quality video.
- > **Dynamic Structure™ technology**
Innovative liquid crystal composition and pixel matrix accelerate video response for seamless video and intense graphics.
- > **OptiSync® digital/analog inputs expand your connectivity**
Multi-mode input technology supports both digital (DVI) and analog (VGA) signals for ultimate compatibility and configuration flexibility.
- > **Ergonomic base adds ease and comfort**
Ultimate ergonomic flexibility comes built-in with the convenient 3.2" height adjustment and 360° swivel.
- > **Multimedia enhanced**
Save workspace and enjoy rich, stereo sound from the integrated stereo speakers and amplifier.
- > **Stylish slim-bezel design**
The full 20" viewable screen in an ultra-thin bezel lets you see more without taking up valuable desktop real estate.
- > **High 300 nit brightness (typ) and 500:1 contrast ratio (typ)**
- > **VESA® 100mm wall mount interface and Kensington® security port**
- > **Windows Vista approved**
- > **PC and Mac® compatible**
- > **TCO'03 and ENERGY STAR® qualified**



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

ViewSonic®
See the difference® 

VG2030m

20" DIGITAL MEDIA GRAPHIC SERIES LCD WITH SWIVEL AND HEIGHT ADJUST



360° SWIVEL



HEIGHT ADJUST



TILT



ISO 9001:2000
FM 40187



ISO 14001:1996
FM 40968

ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789

Customer Service and Technical Support: (800) 688-6688 • Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

*Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Windows Vista and the Windows logo are trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2007 ViewSonic Corporation. All rights reserved. [13350-01B-03/07] VG2030m-1

LCD	Type	20" color TFT active matrix SXGA+ LCD
	Display Area	16.1" horizontal x 12.1" vertical; 20.1" diagonal
	Optimum Resolution	1400x1050
	Contrast Ratio	500:1 (typ)
	Viewing Angles	170° horizontal, 155° vertical @ contrast ratio > 5:1
	Response Time	8ms (typ)
	Light Source	Long life, 50,000 hrs. (typ)
	Brightness	300 cd/m2 (typ)
VIDEO INPUT	Panel Surface	Anti-glare
	Analog/Digital	RGB analog (75 ohms, 0.7 Vp-p)/DVI-D
	Frequency	F _H : 30~82kHz, F _V : 56~76Hz
COMPATIBILITY	Sync	H/V separated (TTL)
	PC	VGA up to 1400x1050 non-interlaced
CONNECTOR	Mac**	Power Mac™ G3/G4/G5 up to 1400x1050
	Analog/Digital	15-pin mini D-sub/DVI-D
POWER	Audio In	Stereo mini audio line in
	Power	3-pin AC plug
	Voltage	AC 100~240V (universal), 50~60Hz (auto switch)
AUDIO	Consumption	45W (typ)
	Speakers	2x2.5-watt
CONTROLS	Amplifier	2-watt
	Basic	Power, 1, down, up, 2
ERGONOMICS	OnView®	Auto image adjust, brightness, contrast, input selection, ViewMatch® color adjust (sRGB, 9300K, 6800K, 6500K), information (mode, model number, serial number), audio (volume, mute), manual image adjust (H. position, V. position, fine tune, sharpness), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), memory recall
		Height adjustment range 3.2", tilt, swivel range 360°
OPERATING CONDITIONS	Temperature	41~95°F (5~35°C)
DIMENSIONS (W x H x D)	Humidity	20~80% (non-condensing)
WEIGHT	Physical with stand	18.1" x 19.1" x 9.1" (459mm x 485mm x 230mm)
	Physical without stand	18.1" x 15.9" x 2.4" (459mm x 404mm x 61mm)
REGULATIONS	Net with stand	14.1 lb. (6.4kg)
	Net without stand	11.7 lb. (5.3 kg)
	Gross with stand	18.3 lb. (8.3 kg)
RECYCLE/DISPOAL		UL, cUL, FCC-B, CB, CE, ENERGY STAR®, NOM, TUV/GS, TUV-S, TUV/ERGO (covers ISO13406-2 & MPR II), TCO'03, GOST-R + 20 original copies hygienic, SASO, PCBC, VCCI, BSMI, CCC, PSB, C-TICK, RoHS
POWER MANAGEMENT		The lamp in this product contains mercury. Please dispose of in accordance with local, state and federal laws.
PACKAGE CONTENTS		Meets TCO'03 and ENERGY STAR® standards
WARRANTY		LCD display, VGA cable, DVI cable, power cable, audio cable, Quick Start Guide, ViewSonic Wizard CD
		Three-year limited warranty

ViewSonic®
See the difference® 

For more product information, visit us on the web at ViewSonic.com