

NMP-700

NETWORK MEDIA PLAYER

X-86 Based Network Media Player

ViewSonic's NMP-700 X86-based Network Media Player features an Intel Mobile Core 2 Duo processor, 2GB of memory, and an Intel X4500MHD graphics card for power digital signage messaging. Connect to any display having VGA and HDMI inputs. This cost-effective solution integrates into your existing network and supports a wide variety of digital display components and applications. With a 160GB hard drive and hardware video decode, local playback of high-definition video files are not an issue. It is powerful enough to deliver smooth playback of graphics and video content up to 1080p Full HD, yet small enough to install anywhere.



- > Intel Core 2 Duo T6400 Processor and Intel X4500MHD Graphics Card
- > X86 design based on the latest Intel technology
- > Versatile output formats: Dual VGA and HDMI
- > Embedded Microsoft Windows XP OS
- > Industrial grade media player
- > Reliable watchdog timer

NMP-700 NETWORK MEDIA PLAYER



ViewSonic® recommends our commercial displays, open frame display or any ViewSonic large screen LCD or LCD TV and digital signage software for use with the NMP-700 to give you the best possible digital signage results.

PRODUCT TYPE	X86-based network media player	
CPU	Intel Core 2 Duo Mobile T6400 2.0GHz 2MB L2 Cache 800MHz FSB	
CORE LOGIC	Intel GM45 Express Chipset	
GRAPHICS	Intel X4500MHD	
OPERATING SYSTEM	Windows embedded standard	
MEMORY (RAM)	2GB DDR-2 SO-DIMM format	
BIOS	AMI	
STORAGE	160GB	
NETWORK	Gigabit (10/100/1000 Mbits/sec) LAN	
REAR PANEL INPUT/OUTPUT	USB port (x2), DC jack (20VDC), VGA port (x2), HDMI port, RJ45 LAN, RS-232 port, audio out, mic in, Kensington® lock	
FRONT PANEL INPUT/OUTPUT	Power button, HDD LED, power indicator, USB port (x2)	
EXPANSION	Mini card slot	
PRE-INSTALLED SOFTWARE APPLICATIONS	Optional	
WATCH DOG TIMER	1~255 sec	
SUPPORTING PROTOCOLS	TCP/IP, HTTP	
DISPLAY	VGA (x2), HDMI	
AUDIO	RCA stereo analog	
DECODING	Video	MPEG-1, 2, 4, Macromedia® Flash
	Audio	Realtek HD Audio Codec
OPERATING CONDITIONS	Temperature	32°-122°F (0°-50°C)
	Humidity	95% (non-condensing)
DIMENSIONS (W x H x D)	Physical	6.5" x 1.9" x 6.2" (166mm x 48mm x 157mm)
WEIGHT	Net	2.7 lb. (1.2 kg)
	Gross	5.2 lb. (2.4 kg)
REGULATIONS	UL/cUL, FCC-15B, CE, CB, RoHS	
PACKAGE CONTENTS	Network media player, AC adapter, mounting bracket, Quick Start Guide, Driver CD	
WARRANTY	One-year limited warranty on parts and labor.	



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by TUV NORD.

Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2009 ViewSonic Corporation. All rights reserved. [14428-00B-06/09] NMP-700-1

ViewSonic®
See the difference®

For more product information, visit us on the web at ViewSonic.com