

VA703m

**17" MULTIMEDIA LCD
WITH INTEGRATED SPEAKERS**

High quality, high performance.

The ViewSonic® 17" VA703m is the all-in-one price performance solution for all needs. No matter if your use is for entertainment or for intensive graphics, whether in the home or in the office, the VA703m fits the bill perfectly. Its 5ms response time delivers crisp images and fluid full-motion video for games, movies and scrolling text. Matched with 700:1 contrast ratio (typ) and 300 nits brightness (typ), the VA703m displays brilliant, vivid, true-to-life colors. Invisible built-in speakers deliver true multimedia performance. The slim styling and silver-black bezel add to the monitor's appeal. Prepare to be impressed by the performance, quality and style of the VA703m.



IMPRESSIVE PERFORMANCE WITHOUT THE HIGH PRICE TAG

- > **ClearMotiv® 5ms video response time**
Super fast 5ms video response delivers broadcast-quality full motion video.
- > **Multimedia enhanced**
Save workspace and enjoy rich sound with built-in invisible stereo speakers.
- > **High brightness and contrast**
300 nit brightness (typ) and 700:1 contrast ratio (typ) for clear, detailed images.
- > **Full 17" viewable screen with 1280x1024 resolution**
Displays a full, flat 17" viewable area with crisp details and fully saturated colors.
- > **Stylish slim-bezel design**
An ultra-thin bezel lets you see more without taking up valuable desktop real estate.
- > **OnView® controls for superior screen adjustability**
Screen adjustments are precisely made via an easy-to-use on-screen menu.
- > **OSD/Power lock secures your settings**
Prevents changes to monitor settings and maintains an optimized image.
- > **Integrated power supply**
- > **VESA® 100mm wall mount and Kensington® security port**
- > **PC and Mac® compatible**
- > **TCO'03 and ENERGY STAR® qualified**



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

ViewSonic®
See the difference® 

VA703m

17" MULTIMEDIA LCD WITH INTEGRATED SPEAKERS



LCD	Type	17" Color TFT Active Matrix XGA LCD
	Display Area	13.3" horizontal x 10.6" vertical; 17.0" diagonal
	Pixel Pitch	0.264mm
	Optimum Resolution	1280x1024
	Contrast Ratio	700:1 (typ)
	Viewing Angles	170° horizontal, 160° vertical
	Response Time	5ms (typ)
	Color Support	16.7M colors supported
	Light Source	Long life, 50,000 hrs. (typ)
	Brightness	300 cd/m ² (typ)
	Panel Surface	Anti-glare (3H)
VIDEO INPUT	Analog	RGB analog (75 ohms, 0.7 Vp-p)
	Frequency	F _H : 30~82kHz, F _V : 50~75Hz
	Sync	H/V separated (TTL)
COMPATIBILITY	PC	VGA up to 1280x1024 non-interlaced
	Mac®*	Power Mac™ up to 1280x1024 non-interlaced
CONNECTOR	Analog	15-pin mini D-sub (VGA)
	Audio	3.5mm stereo audio line-in
	Power	3-pin AC plug (CEE22)
POWER	Voltage	AC 100~240V, 50/60Hz (auto switch), internal power supply
	Consumption	36W (max), <1-watt in power save mode
AUDIO	Speakers	2x1-watt
CONTROLS	Basic	Power, menu [1], up, down, select [2]
	OSD	Auto image, adjust, contrast, brightness, audio adjust (volume, mute), ViewMatch® color adjust (sRGB, 9300K, 6500K, 5400K, user RGB), information (resolution, H/V frequency, pixel clock, model number, serial number, website), manual image adjust (H/V position, H size, fine tune, sharpness), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), OSD/power lock, memory recall
ERGONOMICS	Tilt	Down 5°, Up 20°
OPERATING CONDITIONS	Temperature	32~104°F (0~40°C)
	Humidity	10~90% (non-condensing)
DIMENSIONS	Physical (W x H x D)	14.9" x 15.7" x 8.3" (379mm x 400mm x 210mm)
WEIGHT	Net	7.9 lb. (3.6 kg)
	Gross	10.6 lb. (4.8 kg)
VESA® MOUNT		100mm x 100mm
REGULATIONS		TCO'03, CE, CB, GS ERGO, ISO13406-2 (pixel failure class II), UL/cUL, FCC-B, NOM, GOST-R, ENERGY STAR®, BSMI, CC, PSB, C-TICK, Green Mark, WEEE, RoHS
RECYCLE/DISPOSAL		The lamp in this product contains mercury. Please dispose of in accordance with local, state or federal laws.
POWER MANAGEMENT		Meets TCO'03 and ENERGY STAR® standards
PACKAGE CONTENTS		LCD display, power cable, audio cable, Quick Start Guide, ViewSonic Wizard CD (User Guide and drivers)
WARRANTY		Three-year limited warranty on parts, labor and backlight.



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

*Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2009 ViewSonic Corporation. All rights reserved. [14379-00B-04/09] VA703m-3

ViewSonic®
See the difference®

For more product information, visit us on the web at ViewSonic.com