

# VA1928wm

## 19" MULTIMEDIA LCD

WITH 10,000:1 DYNAMIC CONTRAST RATIO

### Big screen multimedia performance

ViewSonic's 19" VA1928wm widescreen LCD combines 10,000:1 dynamic contrast ratio that produces excellent front-of-screen performance with fast 5ms ClearMotiv® video response for blur-free fast action video. Complementing these high performance features are integrated speakers that offer a true multimedia experience. The VA1928wm enhances productivity allowing you to work in two documents or applications simultaneously and is ideal for home and small office or educational use. Lock in your brilliant colors and perfect screen adjustment with the OSD and power lock. Mount this stylish display on the wall to save valuable desktop space and add a touch of style to your workspace.



#### Enhance your work and play

- > **10,000:1 dynamic contrast ratio**  
Provides for darker black levels and better overall front-of-screen performance.
- > **Multimedia enhanced**  
Save desk and workspace and enjoy rich, stereo sound with built-in 2x2-watt stereo speakers.
- > **Full 19" viewable widescreen with 1440x900 resolution.**
- > **OptiSync digital/analog inputs expand your connectivity**  
Multi-mode input technology supports both digital (DVI) and analog (VGA) signals for ultimate compatibility and configuration flexibility.
- > **sRGB Color Management**  
Ensures color accuracy from screen to print when used with other sRGB-compliant peripherals.
- > **ClearMotiv 5ms video response**  
Video response as fast as 5ms enables digital HD broadcast-quality video.



**VIEWSONIC**  
PRODUCTS, PROGRAMS,  
AND SERVICES

**ViewSonic®**  
See the difference™ 

# VA1928wm

ViewSonic®  
See the difference™ 

19" MULTIMEDIA LCD WITH 10,000:1 DYNAMIC CONTRAST RATIO



<b>LCD</b>	Type	19" Wide Color a-Si TFT Active Matrix LCD
	Display Area	16.1x10.1 (in)
	Optimum Resolution	1440x900
	Brightness	300 cd/m2 (typ.)
	Contrast Ratio	1000:1 (typ.) ; 10,000:1 dynamic
	Viewing Angles	160° (H), 160° (V) (CR>10)
	Response Time	5ms
	Pixel Pitch	0.285mm(H) x 0.285mm(V)
	Panel Surface	Anti-glare, hard-coating (3H)
	light source	50,000 (typ.)
	color support	16.7 M (6-bits + Hi FRC)
<b>VIDEO INPUT</b>	Analog	RGB Analog (75 ohms, 0.7 / 1.0 Vp-p)
	Digital	DVI (TMDS, 100 ohms)
	Sync	Separate Sync
	Frequency	Fh:24-82kHz, Fv:50-75Hz
<b>COMPATIBILITY</b>	PC	VGA up to 1440x900 non-interlaced
	Mac	Power Mac up to 1440x900
<b>CONNECTOR</b>	Analog	15 pin mini D-sub x1
	Digital	DVI (support HDCP and DDC/CI)
	Audio-in	3.5 mm Audio line-in
	Power	3-Pin plug
<b>AUDIO</b>	Speaker	2 x 2-watt
<b>POWER</b>	Voltage	100-240VAC; 50/60 Hz (auto switch)
	Consumption	32W (typ.) / 36W (max.)
<b>ERGONOMICS</b>	Tilt	20 ~ -5 degrees
<b>CONTROLS</b>	Basic	[1], [2], Power, Down[▼], Up[▲]
	OnView	Auto image adjust, Contrast/Brightness, Input select, Color adjust (sRGB, 9300K, 6500K, 5400K, User color [R,G,B]), Information, Manual image adjust (Horizontal size, H/V Position, Fine tune, Sharpness), Setup menu (Language select, Resolution notice, OSD )
<b>OPERATING CONDITIONS</b>	Temperature	32°F -104°F (0°C -40°C)
	Humidity	10-90% (non-condensing)
<b>DIMENSIONS (WXHXD)</b>	Physical (w/stand)	17.3 x 15.1 x 7.6 (in) , 440.2 x 383.4 x 195 (mm)
	Physical (w/o stand)	17.3 x 12 x 2.4 (in) , 440 x 303 x 62 (mm)
<b>WEIGHT</b>	Net w/ stand	9.7 lbs (4.4 Kg)
<b>REGULATIONS</b>		UL/CUL, FCC-B (ICES-003B), CB, CE, TCO'03, GS, GS and ERGO Ergo (covers ISO13406-2 & MPRII), TUV-S, VCCI, NOM, GOST-R (4 copies), HYGIENIC, Energy Star, CCC, BSMI, PSB, C-TICK, KTL/MIC, SASO, WEEE, RoHS, Ukraine
<b>VESA Mount</b>		100mm x 100mm
<b>POWER MANAGEMENT</b>		TCO'03, ENERGY STAR
<b>RECYCLE/DISPOSAL</b>		The lamp in this product contains mercury. Please dispose of in accordance with local, state or federal laws.
<b>PACKAGE CONTENTS</b>		ViewSonic VX2260wm LCD, VGA cable, DVI cable, Audio cable, Power cable, Quick Start Guide, ViewSonic Wizard CD
<b>WARRANTY</b>		Three-year limited warranty on parts, labor and backlight.



ISO 9001:2000  
FM 40187

ISO 14001:1996  
FM 40968

ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

Sales: (888) 881-8781 · SalesInfo@ViewSonic.com · ViewSonic.com

\*Running eco-mode exclusively can extend lamp life. See ViewSonic.com for full Express Exchange details. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2009 ViewSonic Corporation. All rights reserved [14322-02B-03/09] VA1928wm

For more product information, visit us on the web at ViewSonic.com