

NMP-200

NETWORK MEDIA PLAYER

Standard Definition (480p) Network Media Player

ViewSonic's NMP-200 Network Media Player features a reliable ESS-based processor for 24x7 digital signage applications. Connect to any display having a VGA/S-Video/RCA composite input, this cost-effective solution integrates into your existing network and supports MPEG1/2/4 videos. The built-in CF Slot allows you to install high capacity memory cards for content storage. The included Signage Manager Express Software makes it quick and easy to setup and manage all your digital signage content.



- > Solid-state device for extreme reliability
- > 720x480p video performance
- > Reliable 24/7/365 operation
- > WAN and LAN connectivity
- > MPEG 1/2/4 decoding
- > SCALA Content Manager Release 5 compatible

NMP-200 NETWORK MEDIA PLAYER






Upload and automatically play content via the USB port.



ViewSonic® recommends our commercial displays, open frame display or any ViewSonic large screen LCD or LCD TV and the included Signage Manager Express software for use with the NMP-200 to give you the best possible digital signage results.

PRODUCT TYPE	Network Media Player
PROCESSOR	IAdec™ IAN411 Multimedia Networking Processor ESS Digital Media Processor 2 (DMP2) Dual Processor
NETWORKING	IEEE 802.3 Ethernet 10/100 Base-T with Auto-MDIX
PLAYBACK CONTROL	Signage Manager Express Software (LAN) Adfotain Central Management Server (WAN)
SUPPORTED MEDIA FORMATS	MPEG 1/2 MP@ML (480p) MPEG 4 ASP@L2 AVI
CONTENT CAPACITY	Typically 3 Mbps data rate, equivalent to 25 minutes per 512MB memory card and 1 hour per 1.2GB memory card
STORAGE MEDIUM	CompactFlash Type I/II memory card
VIDEO PERFORMANCE	up to 720x480 resolution, 30 frames per second
VIDEO OUTPUT	VGA, S-video, composite RCA video
AUDIO OUTPUT	Stereo line-out
DIMENSIONS (W x H x D)	Physical 5.3" x 4.4" x 1.0" (133.5mm x 113.5mm x 25mm)
WEIGHT	Net 1.8 lb. (0.8 kg)
MOUNTING HOLES	4 VESA® compliant (10-cm/4-inch)
POWER CONSUMPTION	4-watt (typ)
OPERATING CONDITIONS	Temperature 0–40° C Humidity 5–85% @ 40° C
REGULATIONS	UL approved AC adapter
PACKAGE CONTENTS	Media Player, AC power adapter, User Guide, Signage Manager Express software
WARRANTY	One-year limited warranty on parts and labor

	ViewSonic Digital Signage Software Partners	Recommended Network Media Player
1:1		NMP-610 NMP-700
1:50 (LAN)		NMP-530
100+ (WAN)	Signage Manager Express	NMP-200 NMP-550
Offsite Hosted		NMP-600 NMP-610 NMP-700



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by TUV NORD.

Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2009 ViewSonic Corporation. All rights reserved. [14427-00B-0609] NMP-200-1

ViewSonic®
See the difference® 

For more product information, visit us on the web at ViewSonic.com