

With a 25-year heritage as an award-winning display technology leader, ViewSonic is poised to provide the best in complete digital signage solutions. Offering a broad range of product lines and breakthrough technologies, ViewSonic is elevating commercial displays to new levels. Whether you need digital signage for education, business or a commercial installation, ViewSonic has the perfect solution that will change the way you advertise, promote, and broadcast to your target audience. All ViewSonic digital signage solutions come standard with essential features, while individual product lines offer unique options to meet your specific needs.



## Commercial-Grade TVs

| Product                 | Screen Size  | Resolution           | Contrast | Brightness                     | Video Response | VESA® Mount (mm) | Connectivity   | Net Weight                                      | Dimensions W x H x D (in.)   | Special Features   |
|-------------------------|--------------|----------------------|----------|--------------------------------|----------------|------------------|--|---|--|--|
| <b>VT1602-L</b><br>HDTV | 15.6"<br>LED | 1366x768             | 650:1    | 220 cd/m <sup>2</sup><br>(typ) | 11ms<br>(typ)  | 75x75            | RF, HDMI, VGA, 3.5mm mini stereo, YPbPr, SPDIF                   | 2.9 lb<br>(w/ stand)<br>2.5 lb<br>(w/o stand)   | 14.7 x 10.7 x 5.5<br>(w/ stand)<br>14.7 x 9.0 x 1.66<br>(w/o stand)  | Hospitality Menu, USB cloning feature, Progressive Scan, 3D Comb filter, Digital Sound, HDTV built-in w/ QAM TV Tuner, HDMI CEC control                  |
| <b>VT2216-L</b><br>HDTV | 21.5"<br>LED | 1920x1080<br>Full HD | 1000:1   | 250 cd/m <sup>2</sup><br>(typ) | 5ms<br>(typ)   | 100x100          | RF, HDMI, VGA, 3.5mm mini stereo, YPbPr, SPDIF                   | 19.4 lb<br>(w/ stand)<br>17.6 lb<br>(w/o stand) | 17.1 x 12.0 x 6.3<br>(w/ stand)<br>17.1 x 10.6 x 1.1<br>(w/o stand)  | Hospitality Menu, USB cloning feature, Progressive Scan, 3D Comb filter, Digital Sound, HDTV built-in w/ QAM TV Tuner, IR pass through, HDMI CEC control |
| <b>VT2406-L</b><br>HDTV | 23.6"<br>LED | 1920x1080<br>Full HD | 1000:1   | 250 cd/m <sup>2</sup><br>(typ) | 5ms<br>(typ)   | 100x100          | RF, HDMI (x3), VGA, 3.5mm mini stereo, CVBS, YPbPr, RS232, SPDIF | 9.1 lb<br>(w/ stand)<br>4.1 lb<br>(w/o stand)   | 22.3 x 15.6 x 5.9<br>(w/ stand)<br>22.3 x 13.7 x 1.9<br>(w/o stand)  | Hospitality Menu, USB cloning feature, Progressive Scan, 3D Comb filter, Digital Sound, HDTV built-in w/ QAM TV Tuner, IR pass through, HDMI CEC control |
| <b>VT2756-L</b><br>HDTV | 27"<br>LED   | 1920x1080<br>Full HD | 1,200:1  | 300 cd/m <sup>2</sup><br>(typ) | 3.4ms<br>(typ) | 100x100          | RF, HDMI (x3), VGA, 3.5mm mini stereo, CVBS, YPbPr, RS232, SPDIF | 12.1 lb<br>(w/ stand)<br>11.2 lb<br>(w/o stand) | 26.0 x 18.2 x 7.1<br>(w/ stand)<br>26.0 x 16.1 x 1.95<br>(w/o stand) | Hospitality Menu, USB cloning feature, Progressive Scan, 3D Comb filter, Digital Sound, HDTV built-in w/ QAM TV Tuner, IR Pass through                   |
| <b>VT3200-L</b><br>HDTV | 32"<br>LED   | 1920x1080<br>Full HD | 3,000:1  | 300 cd/m <sup>2</sup><br>(typ) | 6.5ms<br>(typ) | 200x100          | RF, HDMI (x3), VGA, 3.5mm mini stereo, CVBS, YPbPr, RS232, SPDIF | 16.1 lb<br>(w/ stand)<br>14.3 lb<br>(w/o stand) | 29.5 x 19.2 x 7.1<br>(w/ stand)<br>29.5 x 17.8 x 2.5<br>(w/o stand)  | Hospitality Menu, USB cloning feature, Progressive Scan, 3D Comb filter, Digital Sound, HDTV built-in w/ QAM TV Tuner, IR pass through, HDMI CEC control |
| <b>VT4200-L</b><br>HDTV | 42"<br>LED   | 1920x1080<br>Full HD | 3,000:1  | 350 cd/m <sup>2</sup><br>(typ) | 6.5ms<br>(typ) | 200x200          | RF, HDMI (x3), VGA, 3.5mm mini stereo, CVBS, YPbPr, RS232, SPDIF | 29.3 lb<br>(w/ stand)<br>26.2 lb<br>(w/o stand) | 38.4 x 24.7 x 8.3<br>(w/ stand)<br>38.4 x 22.8 x 2.5<br>(w/o stand)  | Hospitality Menu, USB cloning feature, Progressive Scan, 3D Comb filter, Digital Sound, HDTV built-in w/ QAM TV Tuner, IR pass through, HDMI CEC control |

Sales: (888) 881-8781 . [salesinfo@ViewSonic.com](mailto:salesinfo@ViewSonic.com) . [ViewSonic.com](http://ViewSonic.com)

For the most current product accessories and specifications, visit [ViewSonic.com](http://ViewSonic.com). Program, specifications and availability are subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2014 ViewSonic Corporation. All rights reserved. [17030-01B-04/14]

## Large Format Displays

| Product                                | Screen Size | Brightness            | Contrast | Video Response | Resolution             | Connectivity   | Integrated Speakers | VESA® Mount (mm)       | Net Weight                                      | Dimensions W x H x D (in.)   | Special Features  |
|--|-------------|-----------------------|----------|----------------|------------------------|--|---------------------|------------------------|---|--|---|
| <b>CDE3200-L</b><br>LED Display        | 32"         | 300 cd/m <sup>2</sup> | 3,000:1  | 6.5ms          | 1920 x 1080<br>Full HD | HDMI (x3), YPbPr, Component, VGA, S-Video, CVBS, SPDIF, USB, RS232 | 10W (x2)            | 200 x 100              | 16.1 lb<br>(w/ stand)<br>14.3 lb<br>(w/o stand) | 29.5 x 19.6 x 7.1<br>(w/ stand)<br>29.5 x 16.5 x 3.1<br>(w/o stand)  | Hospitality Menu, RS232, USB cloning feature, IR Pass Through   |
| <b>CDE4200-L</b><br>LED Display        | 42"         | 350 cd/m <sup>2</sup> | 3,000:1  | 6.5ms          | 1920 x 1080<br>Full HD | HDMI (x3), YPbPr, Component, VGA, S-Video, CVBS, SPDIF, USB, RS232 | 10W (x2)            | 200 x 200              | 27.8 lb<br>(w/ stand)<br>26.2 lb<br>(w/o stand) | 38.4 x 26.7 x 8.2<br>(w/ stand)<br>38.4 x 24.6 x 2.5<br>(w/o stand)  | Hospitality Menu, RS232, USB cloning feature, IR Pass Through   |
| <b>CDP4260-L</b><br>LED Display        | 42"         | 450 cd/m <sup>2</sup> | 1,300:1  | 12ms           | 1920 x 1080<br>Full HD | HDMI, YPbPr, DVI-D, VGA, DisplayPort, RCA Audio In, RS232, RJ45    | 10W (x2)            | 400 x 200<br>200 x 200 | 40.3 lb   | 38.0 x 22.0 x 2.7  | 15.8mm narrow bezel, 5 x 5 daisy chain support, RS232, IR Pass Through, SuperClear™ Technology, HDMI CEC control          |
| <b>CDP4262-L</b><br>LED Display        | 42"         | 700 cd/m <sup>2</sup> | 1,300:1  | 12ms           | 1920 x 1080<br>Full HD | HDMI, YPbPr, DVI-D, VGA, DisplayPort, RCA Audio In, RS232, RJ45    | 10W (x2)            | 400 x 200<br>200 x 200 | 40.3 lb   | 38.0 x 22.0 x 2.7  | 15.8mm narrow bezel, 5 x 5 daisy chain support, RS232, IR Pass Through, SuperClear™ Technology, HDMI CEC control          |
| <b>CDE4600-L</b><br>LED Display        | 46"         | 350 cd/m <sup>2</sup> | 4,000:1  | 8ms            | 1920 x 1080<br>Full HD | HDMI, DVI, USB Component, CVBS, VGA, RJ45, RS232                   | 7W (x2)             | 400 x 400              | 33.7 lb   | 42.0 x 24.5 x 1.5  | Hospitality Menu, RS232, USB cloning feature, Progressive Scan, IR Pass Through, SuperClear™ Technology, HDMI CEC control |
| <b>CDX4650-L</b><br>LED Display        | 46"         | 700 cd/m <sup>2</sup> | 4,000:1  | 6.5ms          | 1920 x 1080<br>Full HD | HDMI, DVI, Component, VGA, S-Video, CVBS (BNC)                     | 10W (x2)            | 400 x 400              | 58.3 lb<br>(w/ stand)<br>53.5 lb<br>(w/o stand) | 40.2 x 24.2 x 12.9<br>(w/ stand)<br>40.2x22.7 x 5.0<br>(w/o stand)   | Intel® OPS ready, Ultra thin 2.7mm bezel, Video wall up to 10 x 10,   |
| <b>CDX4652-L</b><br>LED Display        | 46"         | 500 cd/m <sup>2</sup> | 3,500:1  | 8ms            | 1920 x 1080<br>Full HD | HDMI, DVI, Component, VGA, S-Video, CVBS (BNC)                     | 10W (x2)            | 400 x 400              | 50.7 lb   | 40.3 x 22.8 x 4.9  | Ultra thin 2.8mm bezel, Video wall up to 10 x 10, External speaker out  |
| <b>CDP5560-L</b><br>LED Display        | 55"         | 450 cd/m <sup>2</sup> | 1,300:1  | 12ms           | 1920 x 1080<br>Full HD | HDMI, YPbPr, DVI-D, VGA, DisplayPort, RCA Audio In, RS232, RJ45    | –                   | 400 x 400              | 51.2 lb<br>(w/ stand)<br>48.1 lb<br>(w/o stand) | 50.5 x 32.5 x 11.7<br>(w/ stand)<br>50.5 x 29.6 x 1.5<br>(w/o stand) | 15.8mm narrow bezel, 5 x 5 daisy chain support, RS232, IR Pass Through, SuperClear™ Technology, HDMI CEC control          |
| <b>CDP5562-L</b><br>LED Display        | 55"         | 700 cd/m <sup>2</sup> | 1,300:1  | 12ms           | 1920 x 1080<br>Full HD | HDMI, YPbPr, DVI-D, VGA, DisplayPort, RCA Audio In, RS232, RJ45    | 10W (x2)            | 400 x 400              | 67.4 lb   | 49.1 x 28.3 x 2.8  | 15.8mm narrow bezel, 5 x 5 daisy chain support, RS232, IR Pass Through, SuperClear™ Technology, HDMI CEC control          |
| <b>CDX5550-L</b><br>LED Display        | 54.6"       | 700 cd/m <sup>2</sup> | 3,500:1  | 12ms           | 1920 x 1080<br>Full HD | HDMI, DVI, Component, VGA, S-video, CVBS (BNC)                     | 10W (x2)            | 400 x 400              | 84.2 lb<br>(w/ stand)<br>79.4 lb<br>(w/o stand) | 47.9 x 29.0 x 15.8<br>(w/ stand)<br>47.9 x 27.0 x 5.0<br>(w/o stand) | Intel® OPS ready, Ultra thin bezel, Video wall up to 10 x 10  |
| <b>CDE7051-TL</b><br>LED Touch Display | 69.5"       | 350 cd/m <sup>2</sup> | 4,000:1  | 6ms            | 1920 x 1080<br>Full HD | HDMI (x2), VGA (x2), Digital Audio Out, RS232, USB                 | 15W (x2)            | 600 x 600              | 165.3 lb  | 64.9 x 39.3 x 3.8  | Optional i5 Slot-in PC (NMP707) 6-point touch capable 7H scratch resistant coating  |

Sales: (888) 881-8781 . [salesinfo@ViewSonic.com](mailto:salesinfo@ViewSonic.com) . [ViewSonic.com](http://ViewSonic.com)

For the most current product accessories and specifications, visit [ViewSonic.com](http://ViewSonic.com). Program, specifications and availability are subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2014 ViewSonic Corporation. All rights reserved. [17030-01B-04/14]

## Free-standing ePoster Digital Kiosks

| Product  | Screen Size | Resolution          | Connectivity                             | Internal Memory | File Type Supported   | Integrated Speakers | Dimensions W x H x D (in.) | Special Features   |
|--|-------------|---------------------|--|-----------------|---|---------------------|----------------------------|--|
| <b>EP4220</b><br>Single Sided ePoster          | 42"         | 1920 x 1080 Full HD | HDMI, VGA, RS232, PC Audio               | 2GB storage     | Video: MPEG 1/2/3, H.264, Xvid 1.00-AVI, MP4, Photo: JPEG<br>Audio: WMA, MP3, M4A | 2.5W (x2)           | 27.0 x 72.2 x 17.7         | 1-year limited warranty with extended options available  |
| <b>EP4612-L</b><br>Single Sided LED ePoster    | 46"         | 1920 x 1080 Full HD | HDMI, VGA, USB (x2), RJ45                | 4GB storage     | Video: MPEG 1/2/3, H.264, Xvid 1.00-AVI, MP4, Photo: JPEG<br>Audio: WMA, MP3, M4A | 6W (x2)             | 27.8 x 72.8 x 17.7         | ePoster Manager Express content management software<br>1-year limited warranty                 |
| <b>EP4646</b><br>Dual Sided ePoster            | 46"         | 1920 x 1080 Full HD | HDMI, VGA, YPbPr, USB, A/V, RJ45 pigtail | 4GB storage     | Video: MPEG 1/2/3, H.264, Xvid 1.00-AVI, MP4, Photo: JPEG<br>Audio: WMA, MP3, M4A | 5W (x2)             | 27.8 x 76.8 x 19.7         | Dual sided display,<br>1-year limited warranty with extended options available                 |
| <b>EP5502T</b><br>Single Sided ePoster w/touch | 55"         | 1920 x 1080 Full HD | HDMI, VGA, YPbPr, USB, A/V, RJ45 pigtail | 4GB storage     | Video: MPEG 1/2/3, H.264, Xvid 1.00-AVI, MP4, Photo: JPEG<br>Audio: WMA, MP3, M4A | 5W (x2)             | 32.7 x 76.8 x 17.7         | Interactive touch screen,<br>1-year limited warranty with extended options available           |
| <b>EP5555</b><br>Dual Sided ePoster            | 55"         | 1920 x 1080 Full HD | HDMI, VGA, YPbPr, USB, A/V, RJ45 pigtail | 4GB storage     | Video: MPEG 1/2/3, H.264, Xvid 1.00-AVI, MP4, Photo: JPEG<br>Audio: WMA, MP3, M4A | 5W (x2)             | 32.7 x 76.8 x 18.3         | Dual sided display,<br>1-year limited warranty with extended options available                 |
| <b>EP5555T</b><br>Dual Sided ePoster w/touch   | 55"         | 1920 x 1080 Full HD | HDMI, VGA, YPbPr, USB, A/V, RJ45 pigtail | 4GB storage     | Video: MPEG 1/2/3, H.264, Xvid 1.00-AVI, MP4, Photo: JPEG<br>Audio: WMA, MP3, M4A | 5W (x2)             | 32.7 x 76.8 x 18.3         | Dual sided display, one side touch,<br>1-year limited warranty with extended options available |

## Media Players

| Product   | OS              | Graphics           | Output Resolution | RAM / Internal Memory   | File Support  | Network   | Connectivity   | Mounting (mm)               | Dimensions W x H x D (in.) |
|---|-----------------|--------------------|-------------------|-------------------------|---|---|--|-----------------------------|----------------------------|
| <b>NMP-570w</b><br>Wireless Media Player        | Linux           | -                  | up to 1920 x 1080 | -<br>4GB Flash          | Video: MPEG-1/2/4, H.264, VC-1/WMV9<br>Audio: MPEG-1, MP3<br>Image: JPEG, PNG | 10/100 LAN, WiFi<br>802.11 b/g/n                          | HDMI, VGA, A/V out, USB (x2), RJ45, CF card reader                         | MIS-D100 (VESA® compatible) | 5.9 x 4.3 x 1.1            |
| <b>NMP-707</b><br>Slot-in PC (CDE7051-TL)       | Windows® 8 Pro  | -                  | up to 1920 x 1080 | -<br>4GB Flash          | Video: MPEG-1/2/4, H.264, VC-1/WMV9<br>Audio: MPEG-1, MP3<br>Image: JPEG, PNG | 10/100 LAN, WiFi<br>802.11 b/g/n                          | HDMI, VGA, A/V out, USB (x2), RJ45, CF card reader                         | MIS-D100 (VESA® compatible) | 5.9 x 4.3 x 1.1            |
| <b>VOT133</b><br>Mini PC                        | Windows® 7 Home | AMD Radeon HD 6310 | up to 1920 x 1080 | 2GB DDR-3<br>320 GB HDD | Video: AVC, VC1, MPEG2<br>Audio: ALC662                                       | Gigabit (10/100/1000 Mbits/sec) LAN                       | HDMI, DVI-I, SPDIF In/Out, USB (x6), RJ45, card reader (SD/SDHC/MS/MS Pro) | VESA® 100 x 100             | 7.5 x 5.3 x 1.0            |
| <b>WPG-370</b><br>Wireless Presentation Gateway | -               | -                  | up to 1920 x 1080 | -<br>-                  | -   | 802.11 a/b/g/n, WiDi, Gigabit (10/100/1000 Mbits/sec) LAN | HDMI, VGA, Audio In/Out, RJ45, USB   | -                           | 7.5 x 1.3 x 4.0            |

Sales: (888) 881-8781 . salesinfo@ViewSonic.com . ViewSonic.com

For the most current product accessories and specifications, visit ViewSonic.com. Program, specifications and availability are subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2014 ViewSonic Corporation. All rights reserved. [17030-01B-04/14]

## Wall-mounted ePoster Digital Billboards

| Product  | Screen Size | Resolution          | Connectivity                  | Internal Memory | File Type Supported   | Integrated Speakers | Mounting (mm)   | Dimensions W x H x D (in.) | Special Features  |
|--|-------------|---------------------|-------------------------------|-----------------|---|---------------------|-----------------|----------------------------|---|
| <b>EP1031r</b><br>Single Sided ePoster           | 10.1"       | 800 x 480           | USB2.0, RJ45, Wi-Fi 801.b/g/n | 4.0GB           | HTML5, Android 4.0, W3C, SMIL, JPEG, MPEG 1,2, H.2264, PNG          | 2W (x2)             | 75 x 75         | 10.9 x 7.3 x 1.5           | Signage Manager Express software, POE (Power Over Ethernet), Motion Sensor w/ touch buttons (6)                           |
| <b>EP1032r-T</b><br>Single Sided ePoster w/touch | 10.1"       | 1280 x 800          | USB2.0, RJ45, Wi-Fi 801.b/g/n | 4.0GB           | HTML5, Android 4.0, W3C, SMIL, JPEG, MPEG 1,2, H.2264, PNG          | 2W (x2)             | 75 x 75         | 10.9 x 7.3 x 1.5           | Signage Manager Express software, POE (Power Over Ethernet), Touch buttons (6)  |
| <b>EP2203r</b><br>Single Sided ePoster           | 21.5"       | 1920 x 1080 Full HD | VGA, HDMI, USB                | 4.0GB           | Photo: JPEG, GIF, PNG, BMP<br>Video: MPEG 1/4, WMV, H.264, AVI, FLV | 2W (x2)             | VESA® 100 x 100 | 14.9 x 23.1 x 1.3          | Slim design, 1-year limited warranty with extended options available, ePoster Manager Express content management software |
| <b>EP3203r</b><br>Single Sided ePoster           | 31.5"       | 1366 x 768          | VGA, HDMI, USB                | 4.0GB           | Photo: JPEG, GIF, PNG, BMP<br>Video: MPEG 1/4, WMV, H.264, AVI, FLV | 5W (x2)             | VESA® 400 x 200 | 19.7 x 31.9 x 1.6          | Slim design, 1-year limited warranty with extended options available, ePoster Manager Express content management software |
| <b>EP4203r</b><br>Single Sided ePoster           | 42"         | 1920 x 1080 Full HD | VGA, HDMI, USB                | 4.0GB           | Photo: JPEG, GIF, PNG, BMP<br>Video: MPEG 1/4, WMV, H.264, AVI, FLV | 2W (x2)             | VESA® 400 x 400 | 25.0 x 41.0 x 1.6          | Slim design, 1-year limited warranty with extended options available, ePoster Manager Express content management software |

## Glossary



### LED

LED backlighting enhances display performance, delivers an outstanding color range, and adjusts contrast ratios for remarkably detailed images. The LED backlighting further conserves up to 25%\* more energy when compared to conventional displays.

### OPS (Open Pluggable Specification)

The Open Pluggable Specification (OPS) helps standardize the design and development of digital signage media player devices. ViewSonic OPS-ready digital signage displays provide the flexibility for customers to configure and integrate cable-free OPS-compatible media players with performance that meets the application requirements.



### Optical Touch

Optical touch utilizes two or more image sensors that are usually placed around the edges of a display. Unlike Projected Capacitive touch, however, optical touch does not require a conductive object for touch recognition, making it ideal for high-traffic environments where simple finger touch solutions are needed.



### Warranty

ViewSonic is committed to using the highest grade panels and offers the industry's leading pixel performance policy. Optional extended warranties are available for up to 5-years of coverage.

Sales: (888) 881-8781 . [salesinfo@ViewSonic.com](mailto:salesinfo@ViewSonic.com) . [ViewSonic.com](http://ViewSonic.com)

For the most current product accessories and specifications, visit ViewSonic.com. Program, specifications and availability are subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2014 ViewSonic Corporation. All rights reserved. [17030-01B-04/14]