

Pro8500

120HZ AND 3D-READY

Brilliant and 3D-ready.

The ViewSonic® Pro8500 is an advanced high brightness DLP® installation projector which includes BrilliantColor™ technology to produce more vibrant colors. The Pro8500 delivers 5000 lumens with a 1024x768 XGA native resolution, allowing it to shine in virtually any lighting situation. The Pro8500 provides maximum mounting flexibility with a wide 1.5X optical zoom adjustment and a multitude of connectivity options including Network Display, USB, and WiFi. The filter-less design and long lamp life provide for easy maintenance and low total cost of ownership.



Network control through RJ-45

Schedule, manage and monitor the projector remotely and receive e-mail alerts of projector lamp status.

Closed captioning

Integrated closed captioning decoder for the hearing impaired.

HDMI 1.3

Through HDMI 1.3 and a full array of other input interfaces provide all the connectivity needed.

Bright in virtually any setting with 5,000 lumens

Ultra-bright 5,000 lumen output makes this the perfect choice for large boardrooms, conference halls and auditoriums.

Give Greener presentations and save

Use the Eco mode to achieve lower power consumption, reduce overall noise and extend lamp life.

BrilliantColor™ technology

Latest BrilliantColor technology delivers stunning all-digital clarity with life-like color, sharp graphics and outstanding video. The sophisticated 5-segment color wheel enhances the yellow color performance that is key to accurate and vivid color reproduction.

Stay connected

Supports multiple video timing formats from SD (NTSC, PAL & SECAM) to HD 1080p.

ViewSonic®
See the difference™ 

Pro8500

NETWORKABLE HIGH BRIGHTNESS PROJECTOR - 120HZ AND 3D-READY



Optional Accessories

- Replacement Lamp RLC-059
- Universal Ceiling Mount Kit WMK-025

Projection Distance		4:3 Aspect			
		Wide		Tele	
M	Feet	M	Inches	M	Inches
7.6	30	0.8	33	0.06	2.70
10.2	40	1.1	45	0.09	3.60
12.7	50	1.4	57	0.11	4.50
15.2	60	1.7	69	0.13	5.40
20.3	80	2.3	92	0.18	7.20
25.4	100	2.9	116	0.23	9.10
30.5	120	2.9	139	0.27	10.90
38.1	150	4.4	175	0.34	13.60
50.8	200	5.9	234	0.46	18.10
55.9	220	6.5	257	0.50	19.90
63.5	250	7.4	292	0.57	22.60
76.2	300	8.9	351	0.69	27.20



ISO 9001:2000
FM 40187

ISO 14001:1996
FM 40968

ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

Model Name		Pro8500
Display	Type	0.7" Digital Micromirror Device (DLP™)
	Resolution	XGA 1024 x 768 (Native)
	Lens	1.5× Manual optical zoom / Manual optical focus
	Keystone	Vertical digital keystone correction: +/- 40 degrees
	Size	30" - 300" / 0.76m - 7.6m
	Throw Distance	1.2m - 10m / 3.9ft - 32.8ft
	Throw Ratio	1.45 - 2.18:1
	Lamp	280 watt
	Lamp Life (Normal/Eco-mode)	4000 / 5000* hours
	Brightness	5000 Lumens
	Contrast Ratio	4900:1
	Aspect Ratio	4:3 (native) and 16:9
	Color Gamut	90% NTSC 1931 CIE
	Input Signal	Computer And Video
Frequency		Fh: 31 - 100kHz, Fv: 48 - 120Hz
Compatibility	PC	VGA to UXGA
	Mac	Up to UXGA (scaled)
Connector	RGB Input	15-pin mini D-sub (x2)
	RGB Output	15-pin mini D-sub
	Digital Input	HDMI 1.3
	Component	RCA (x3)
	Composite Input	RCA jack
	S-video Input	4-pin mini - DIN
	Microphone	3.5mm mini mon jack
	Audio Input	3.5mm mini jack
	Audio Output	3.5mm mini jack
	Control	RS-232 (8 Pin Mini - Din)
Audio	Speaker	RJ - 45
	Power	10W (x2)
Power	Voltage	90-240VAC (Auto Switching), 50/60Hz (universal)
	Power Consumption	342W (typ) / <1W (stand-by mode)
Controls	Basic	Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, auto, mode/enter, source
	Osd	Picture: Brightness, Contrast, Color Setting, Keystone, Aspect Ratio, Image, White Intensity, Gamma, 3D Sync, 3D Sync invert
		Computer Image: Frequency, Tracking, H Position, V Position
		Video Image: Saturation, Sharpnes, Tint
		Setting: Manual Position, Projection, Signal Type, Lamp Hour, Lamp Hour Reset, Filter Mode, Filter Hours, Filter Hours Reset, Power Saving, Auto Source, Eco-mode, High Altitude, OSD Timeout
		Advance: Blank Screen, Password Word, Screen Capture, Start up Screen, Text Shof, Digital Zoom, DCR, Close Captions, Brilliant Color
	Operating Condition	Temperature Humidity Altitude
	Noise Level	Normal / Eco Mode 34dB / 29dB
	Dimensions (W X H X D)	Physical Packaging
	Weight	Net Gross
Regulations	CB, RoHS, SVHC, WEEE, UL/cUL, FCC-B, ICES-004, TUV-S (Argentina), NOM, PSB, C-tick, KC, CE, GOST-R, Hygienic, UKrSEPRO, CCC	
Packing Contents	ViewSonic projector, power cable, VGA cable, remote control/laser with batteries, lens cap, Quick Start Guide, ViewSonic Wizard DVD (with User Guide)	

For more product information, visit us at ap.viewsonic.com

ViewSonic®
See the difference™