



ID2456-4K - 24" 4K PODIUM TOUCH DISPLAY WITH ACTIVE STYLUS AND ADVANCED ERGONOMICS

Key Features


- Premium Touch Interactivity and Accurate Handwriting
- Cross-Platform Touch Support
- Advanced Ergonomics
- Easy Connections with HDMI Output
- Advanced Connectivity to Nearly Any Device



24"
DISPLAY



PANEL



1920x1080
RESOLUTION



Product Description

The ViewSonic® myPodium™ ID2456-4K interactive pen display transforms traditional podiums into modern digital teaching and presentation hubs. Designed for front-of-room use in classrooms, lecture halls, and corporate training spaces, this 24" (23.8" viewable) 4K display combines ultra-responsive PCAP touch with an MPP2.0 active stylus for smooth, accurate on-screen writing and annotation. Presenters can face their audience while interacting naturally with content, improving engagement and communication. Its sleek, bezel-less design looks professional in any environment, while USB-C offers simple, one-cable plug-and-play connectivity with laptops and Chromebooks. An HDMI output enables screen mirroring or extended desktops to large front-of-room displays. The battery-free stylus delivers 4096 levels of pressure sensitivity and $\pm 50^\circ$ tilt for precise writing and drawing, and stores and charges wirelessly in the included external holder. Whether used at the podium or on a desktop, the ID2456-4K enhances instruction, collaboration, and productivity across education and enterprise settings.

Specifications

	More Information
UPC	766907031362
Screen Size	24"
Viewable Area (in.)	23.8
Display Resolution	3840 x 2160
Display Resolution	4K (3840x2160)
Static Contrast Ratio	1,300:1
Light Source	LED
Brightness	250 cd/m2
Colors	1.07B
Color Space Support	10 bit (8 bit + FRC)
Aspect Ratio	16:9
Response Time (Typical GTG)	14ms
Viewing Angles	178º horizontal, 178º vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-glare, Hard coating 7H
Refresh Rate	60Hz
PC Resolution (max)	1920x1080
Mac® Resolution (max)	1920x1080
USB Type A	4
USB Type B	1
USB Type C	98W PD x 1
3.5mm Audio Out	1
HDMI 2.0 In	1
HDMI 2.0 Out	1
DisplayPort	1
Touch Technology	Projective Capacitive
Touch Points	10-Point Touch
Internal Speakers	2.5W (x2)
Consumption (typical)	33W
Consumption (max)	36W
Voltage	AC 100-240V (universal), 50-60Hz
Stand-by	0.5W
Power Supply	Internal

Cable Organization	No
On Screen Display	Input Select, Audio Adjust, View Mode, Color Adjust, Manual Image Adjust, Setup Menu
Temperature	32-104° F (0 - 40° C)
Humidity (non-condensing)	10-85%
VESA Compatible	75 x 75 mm
Tilt (Forward/Back)	15° +/-2 (forward), 70.0° +/-2 (backward)
Regulations	cTUVus, FCC, Energy Star 8.0, CEC, ICES003
Net (lbs)	9.7
Gross (lbs)	16.5
Net (kg)	4.4
Gross (kg)	7.5
Packaging (in.)	26.4 x 16.1 x 6.3
Physical (in.)	21.44 x 13.11 x 1.7
Packaging (mm)	670.0 x 410.0 x 160.0
Physical (mm)	544.6 x 333.1 x 43.3
Package Contents	ID2456-4K, Power cable (1.8m), Type-C cable (1.8m), HDMI cable (1.8m), USB A/B cable (1.8m), USB C cable (1.8m), MPP2.0 ACP Pen, Pen tether, Wireless pen charger, Quick Start Guide
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.

UPC: 766907031362



Contact Sales

[ViewSonic.com](https://www.viewsonic.com)

888.881.8781

email: salesinfo@viewsonic.com