

## VB-CAM-201-S - 4K WIDE-ANGLE CONFERENCE CAMERA WITH PAN/TILT/ZOOM, MICROPHONE ARRAY, AND BLUETOOTH

### Key Features

---



### Product Description

---


The ViewSonic® VB-CAM-201 is a 4K video conferencing camera perfect for medium to large-sized conference rooms and boardrooms. With 4K Ultra HD resolution and a 120° super wide-angle lens, the VB-CAM-201 captures everyone in a meeting room with stunning clarity. Voice-tracking technology, combined with 5x digital zoom, ensures that the speaker is always on camera. In addition, an 8W speaker and a four-microphone array with noise and echo cancellation technologies ensure that everyone on your call feels as if they are in the room with you. Plug-and-play connectivity with ViewSonic ViewBoard® interactive displays and commercial displays make setup quick and easy.

### Specifications

---

| More Information        |                                              |
|-------------------------|----------------------------------------------|
| UPC                     | 766907018318                                 |
| Sensor                  | 1/2.5 inch, CMOS, 8.51M pixel                |
| Lens                    | 5x digital zoom, pan/tilt ±15°               |
| Digital Noise Reduction | 2D, 3D digital noise reduction               |
| White Balance           | Auotmatic, Indoor, Outdoor, One Push, Manual |
| Field of View (FOV)     | 120°(DFOV), 110°(HFOV)                       |
| Display Resolution      | 3840 x 2160                                  |

|                                  |                                                                                                                                                                                                         |
|----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>PTZ</b>                       | MPT + EPTZ                                                                                                                                                                                              |
| <b>HDMI 2.0 Out</b>              | 1                                                                                                                                                                                                       |
| <b>USB 2.0 Type A</b>            | 1                                                                                                                                                                                                       |
| <b>USB 3.0 Type C</b>            | 1                                                                                                                                                                                                       |
| <b>Ethernet LAN (RJ45)</b>       | 1                                                                                                                                                                                                       |
| <b>Video Support</b>             | 4K@30fps, 1080P@60fps, 1080P@30fps, 720P@60fps, 720P@30fps, etc.                                                                                                                                        |
| <b>Compression</b>               | H.264 / MJPEG /YUY2 /NV12                                                                                                                                                                               |
| <b>Internal Speakers</b>         | 8W (x1)                                                                                                                                                                                                 |
| <b>Sensitivity</b>               | 96dB at 0.5m / 1.6 ft                                                                                                                                                                                   |
| <b>Audio features</b>            | 32K sampling rate, high-definition broadband audio, full-duplex voice / Auto Echo cancellation / Auto Noise suppression / Auto Gain control                                                             |
| <b>USB protocol</b>              | Support UAC 2.0                                                                                                                                                                                         |
| <b>Microphone</b>                | Beamforming microphone                                                                                                                                                                                  |
| <b>Microphone array</b>          | 4 microphones                                                                                                                                                                                           |
| <b>Distance</b>                  | 6m / 20 ft                                                                                                                                                                                              |
| <b>Minimum Hardware Specs</b>    | CPU (Recommended) 2.4GHz Intel® Core 2™ Duo processor or higher, RAM (Recommended) 2GB of Memory or higher, USB 2.0 Type-A required for 1080p video output, USB Type-C required for 4K UHD video output |
| <b>Voltage</b>                   | DC 12V/1.5A Adapter                                                                                                                                                                                     |
| <b>Consumption (typical)</b>     | 18W                                                                                                                                                                                                     |
| <b>Bluetooth</b>                 | Bluetooth 5.0                                                                                                                                                                                           |
| <b>Temperature</b>               | 32-104° F (0 - 40° C)                                                                                                                                                                                   |
| <b>Humidity (non-condensing)</b> | 20-90%                                                                                                                                                                                                  |
| <b>Wireless Connectivity</b>     | N/A                                                                                                                                                                                                     |
| <b>Packaging (in.)</b>           | 26.54 x 18.98 x 18.66                                                                                                                                                                                   |
| <b>Physical (in.)</b>            | 23.62 x 5.31 x 4.53                                                                                                                                                                                     |
| <b>Packaging (mm)</b>            | 674 x 482 x 474                                                                                                                                                                                         |
| <b>Physical (mm)</b>             | 600 x 135 x 115                                                                                                                                                                                         |
| <b>Net (lbs)</b>                 | 4.86                                                                                                                                                                                                    |
| <b>Gross (lbs)</b>               | 28.66                                                                                                                                                                                                   |
| <b>Gross (kg)</b>                | 4.86                                                                                                                                                                                                    |
| <b>Warranty</b>                  | *Refurbished. 30-day DOA policy for full refund, with a 90-day repair warranty on parts and labor.                                                                                                      |
| <b>Recycle/Disposal</b>          | Please dispose of in accordance with local, state or federal laws.                                                                                                                                      |
| <b>Regulations</b>               | FCC, FCC ID, CE, IC ID, LVD                                                                                                                                                                             |
| <b>Package Contents</b>          | VB-CAM-201, Documentation, Remote Control, Power Adapter, Bracket, USB Type-C Cable, Bracket Screw x 6, Wall Anchor x 6                                                                                 |
| UPC: 766907018318                |                                                                                                                                                                                                         |



**Contact Sales**  
[ViewSonic.com](https://www.viewsonic.com)  
888.881.8781 📞  
email:  
[salesinfo@viewsonic.com](mailto:salesinfo@viewsonic.com)