


## PA503S-2 - 4000 LUMENS SVGA HOME WITH HDMI AND VERTICAL KEYSTONE

### Key Features


---



30 - 300 in. / 0.76 - 7.62 m  
**DISPLAY**



**PANEL**



VGA (640 x 480) to WUXGA\_RB (1920 x 1200)  
**RESOLUTION**

3,600 Lumens and SVGA Resolution



### Product Description

---

The ViewSonic® PA503S price-performance projector features 4,000 lumens, native SVGA 800 x 600 resolution, and intuitive, user-friendly design. Exclusive SuperColor™ technology offers a wide color gamut for beautiful image production in nearly any environment. The PA503S also features extensive connectivity including HDMI, 2 x VGA, VGA out, Composite Video and audio in/out. An energy-saving SuperEco™ feature reduces power consumption and extends the lamp life by up to 15,000 hours. With advanced audio-visual features, flexible connectivity options, and an affordable price, the PA503S is ideal for use in education and small business environments.

\*Energy consumption and lamp life may vary based on actual usage and other factors.

### Specifications

---

|                                                    |                                           |
|----------------------------------------------------|-------------------------------------------|
| <b>UPC</b>                                         | 766907012521                              |
| <b>Light Source</b>                                | DLP Lamp                                  |
| <b>Display Resolution</b>                          | SVGA (800x600)                            |
| <b>Display Resolution</b>                          | 800 x 600                                 |
| <b>Brightness (Lumens)</b>                         | 4,000 ANSI                                |
| <b>Screen Size</b>                                 | 30 - 300 in. / 0.76 - 7.62 m              |
| <b>Throw Distance</b>                              | 3.9 - 43 ft / 1.19 - 13.11 m              |
| <b>Throw Ratio</b>                                 | 1.96 ~ 2.15                               |
| <b>Keystone</b>                                    | Vertical (+/- 40°)                        |
| <b>Lens</b>                                        | 1.1x optical zoom                         |
| <b>Light Source (watt)</b>                         | 190                                       |
| <b>Light Source Life, Normal (hours)</b>           | 5000                                      |
| <b>Light Source Life, Dynamic Eco-Mode (hours)</b> | 15000                                     |
| <b>Color Depth</b>                                 | 1.07B Color (R/G/B 10bit)                 |
| <b>Dynamic Contrast Ratio</b>                      | 22,000:1                                  |
| <b>Aspect Ratio</b>                                | 4:3                                       |
| <b>Input Lag</b>                                   | 37ms                                      |
| <b>Frequency Horizontal</b>                        | 15K~102KHz                                |
| <b>Frequency Vertical</b>                          | 23~120Hz                                  |
| <b>PC Resolution (max)</b>                         | VGA (640 x 480) to WUXGA_RB (1920 x 1200) |
| <b>Mac® Resolution (max)</b>                       | VGA (640 x 480) to WUXGA_RB (1920 x 1200) |
| <b>Mini USB Type B</b>                             | 1                                         |
| <b>3.5mm Audio Out</b>                             | 1                                         |
| <b>3.5mm Audio In</b>                              | 1                                         |
| <b>Control (RS232)</b>                             | 1                                         |
| <b>HDMI 1.4 In</b>                                 | 1                                         |
| <b>VGA In</b>                                      | 2                                         |
| <b>VGA Out</b>                                     | 1                                         |
| <b>Composite RCA Video In</b>                      | 1                                         |
| <b>Internal Speakers</b>                           | 2W (x1)                                   |
| <b>Voltage</b>                                     | AC 100-240V (universal), 50-60Hz          |
| <b>Consumption (typical)</b>                       | 260W                                      |
| <b>Stand-by</b>                                    | <0.5W                                     |
| <b>Temperature</b>                                 | 32-104° F (0 - 40° C)                     |
| <b>Net (lbs)</b>                                   | 4.9                                       |
| <b>Gross (lbs)</b>                                 | 7.1                                       |

|                         |                                                                                                    |
|-------------------------|----------------------------------------------------------------------------------------------------|
| <b>Net (kg)</b>         | 2.2                                                                                                |
| <b>Gross (kg)</b>       | 3.2                                                                                                |
| <b>Packaging (in.)</b>  | 14.4 x 7.4 x 11.8                                                                                  |
| <b>Physical (in.)</b>   | 11.6 x 4.3 x 8.6                                                                                   |
| <b>Packaging (mm)</b>   | 365 x 188 x 300                                                                                    |
| <b>Physical (mm)</b>    | 294 x 110 x 218                                                                                    |
| <b>Regulations</b>      | FCC (including ICES-003), cTUVus                                                                   |
| <b>Package Contents</b> | PA503S projector, power cable, VGA cable, remote control, Quick Start Guide                        |
| <b>Warranty</b>         | *Refurbished. 30-day DOA policy for full refund, with a 90-day repair warranty on parts and labor. |
| <b>Recycle/Disposal</b> | Please dispose of in accordance with local, state or federal laws.                                 |

UPC: 766907012521



**Contact Sales**  
[ViewSonic.com](http://ViewSonic.com)  
 888.881.8781  
 email:  
[salesinfo@viewsonic.com](mailto:salesinfo@viewsonic.com)