

VG2456 - 24" 1080P ERGONOMIC IPS DOCKING MONITOR WITH USB C AND RJ45 AND DAISY CHAIN

Key Features



24"
DISPLAY



IPS
PANEL



1920x1080
RESOLUTION



- x1 HDMI 1.4
- x1 DisplayPort (In)
- x1 DisplayPort (Out)
- x2 USB-A 3.2
- x1 USB-B 3.2
- x1 USB 3.2 Type-C
- x1 Ethernet LAN (RJ45)
- 2x 2-watt integrated speakers

FUTURE-PROOF INPUTS
For flexible connectivity

Product Description


Designed to boost productivity and maximize output, the ViewSonic® VG2456 is a 24" docking monitor that transforms your desktop into a streamlined and efficient workspace. Enjoy reliable and flexible network connectivity with the integrated gigabit Ethernet port, while the latest USB 3.2 Type-C connectivity makes dual-monitor setup a breeze. That's not all, the integrated USB hub also provides single-cable simplicity for connecting and charging your peripherals and accessories. A best-in-class ergonomic design features 40-degree tilt and bi-directional pivot so your screen and workspace are as comfortable as you need. In addition, the included vDisplay software gives you quick and easy OSD control, as well as customized screen templates for easy multi-tasking. This monitor is also shipped in eco-friendly biodegradable packaging, along with an easy-to-install quick release stand that makes for quick deployment and a lower total cost of ownership.

Specifications

	More Information
UPC	766907007602
Screen Size	24"
Viewable Area (in.)	23.8
Panel Type	IPS
Display Resolution	1920 x 1080
Display Resolution	Full HD (1920x1080)
Static Contrast Ratio	1,000:1
Dynamic Contrast Ratio	50,000,000:1
Light Source	WLED
Brightness	250 cd/m2
Colors	16.7M
Color Space Support	6 bits
Aspect Ratio	16:9
Response Time (Typical GTG)	15ms
Response Time (GTG w/OD)	5ms
Viewing Angles	178º horizontal, 178º vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-glare, Hard coating (3H)
PC Resolution (max)	1920x1080
Mac® Resolution (max)	1920x1080
USB Type A	2
USB Type B	1
USB Type C	60W x 1
Ethernet LAN (RJ45)	1
HDMI 1.4 In	1
DisplayPort	1
DisplayPort Out	1
Internal Speakers	2W (x2)
Eco Mode (Conserve)	10.0W
Eco Mode (optimized)	11.7W
Consumption (typical)	13.7W
Consumption (max)	17.4W
Voltage	AC 100-240V (universal), 50-60Hz

Stand-by	0.3W
Power Supply	Internal
Cable Organization	No
Kensington Lock Slot	1
Physical Controls	1,2,3,4,5,6 (Power)
On Screen Display	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)
Temperature	32-104º F (0 - 40º C)
Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Frequency Horizontal	15 ~ 82 KHz
Frequency Vertical	24 ~ 75 Hz
Digital Sync	TMDS for HDMI (v1.4), PCI-E for DisplayPort (v1.2), Micro-Packet for USB Type C
Height Adjust	130 mm / 5.1 in
Swivel	120º
Pivot (Right/Left)	90º / 90º
Tilt (Forward/Back)	40º / 5º
Regulations	cTUVus, FCC-B, ICES003, Energy Star Certified, EPEAT Certified, MX-CoC, Mexico Energy
Net (lbs)	14.1
Net Without Stand (lbs)	8.8
Gross (lbs)	20.7
Net (kg)	6.4
Net Without Stand (kg)	4.0
Gross (kg)	9.4
Packaging (in.)	23.4 x 8.3 x 15.6
Physical (in.)	21.2 x 16.0 x 8.0
Physical Without Stand (in.)	21.2 x 12.6 x 2.0
Packaging (mm)	595.0 x 210.0 x 396.0
Physical (mm)	539.0 x 406.2 x 202.0
Physical Without Stand (mm)	539.0 x 320.0 x 52.0
Package Contents	VG2456 Display, Power Cable, DP to DP Cable, USB Type C Cable, USB 3.2 Uplink Cable, Quick Start Guide
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Warranty	*Refurbished. 30-day DOA policy for full refund, with a 90-day repair warranty on parts and labor.

UPC: 766907007602



**FULL HD (1920 X 1080P)
RESOLUTION**

Contact Sales
[ViewSonic.com](https://www.viewsonic.com)
888.881.8781 📞
email:
salesinfo@viewsonic.com