




VG2456A - 24" 1080P ERGONOMIC IPS DOCKING MONITOR WITH 90W USB C, RJ45 AND DAISY CHAIN

Key Features



24"
DISPLAY



IPS
PANEL



1920 x 1080
RESOLUTION



Flexible Connectivity Options

- 100x100 mm VESA compatible
- x1 HDMI 1.4
- x2 DisplayPort (In/Out)
- x2 USB Type-A
- x1 USB Type-B
- x1 USB Type-C
- x1 Ethernet LAN (RJ45)
- x2 3-watt speakers

Product Description


Designed to boost productivity and maximize output, the ViewSonic® VG2456a is a 24" docking monitor that transforms your desktop into a streamlined and efficient workspace. Enjoy reliable and flexible network connectivity with the integrated gigabit Ethernet port, while the latest USB-C connectivity makes dual-monitor setup a breeze and provides up to 90W power delivery to your laptop. That's not all, the integrated USB hub also provides single-cable simplicity for connecting and charging your peripherals and accessories. A best-in-class ergonomic design features 40-degree tilt and bi-directional pivot so your screen and workspace are as comfortable as you need. In addition, the included vDisplay software gives you quick and easy OSD control, as well as customized screen templates for easy multi-tasking. This monitor is also shipped in eco-friendly biodegradable packaging, along with an easy-to-install quick release stand that makes for quick deployment and a lower total cost of ownership.

Specifications

	More Information
UPC	766907016109
Screen Size	24"
Viewable Area (in.)	23.8
Panel Type	IPS
Display Resolution	1920 x 1080
Display Resolution	Full HD (1920x1080)
Static Contrast Ratio	1,000:1
Dynamic Contrast Ratio	50,000,000:1
Light Source	LED
Brightness	250 cd/m2
Colors	16.7M
Color Space Support	6 bit + A-FRC
Aspect Ratio	16:9
Response Time (Typical GTG)	5ms
Viewing Angles	178º horizontal, 178º vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-Glare type, Hard-coating (3H), Haze 25%
PC Resolution (max)	1920 x 1080
Mac® Resolution (max)	1920 x 1080
USB Type A	2
USB Type B	1
USB Type C	90W x 1
Ethernet LAN (RJ45)	1
HDMI 1.4 In	1
DisplayPort	1
DisplayPort Out	1
Internal Speakers	2W (x2)
Eco Mode (Conserve)	18W
Eco Mode (optimized)	21W
Consumption (typical)	24W
Consumption (max)	46W
Voltage	AC 100-240V (universal), 50-60Hz
Stand-by	0.5W

Power Supply	Internal
Cable Organization	No
Physical Controls	Key 1 (eye), Key 2, Key 3, Key 4, Key 5, Key 6 (power)
On Screen Display	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu
Temperature	32-104º F (0 - 40º C)
Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Frequency Horizontal	15 ~ 82 KHz
Frequency Vertical	50 ~ 75 Hz
Height Adjust	130 mm / 5.1 in
Swivel	120º
Pivot (Right/Left)	90º / 90º
Tilt (Forward/Back)	5º / 40º
Regulations	cTUVus, FCC-B, ICES003, Energy Star 8.0, EPEAT Silver, CEC, MX-CoC, Mexico Energy
Net (lbs)	13.9
Net Without Stand (lbs)	8.6
Gross (lbs)	20.3
Net (kg)	6.3
Net Without Stand (kg)	3.9
Gross (kg)	9.2
Packaging (in.)	23.4 x 8.3 x 15.6
Physical (in.)	21.2 x 15.99~20.15 x 8.0
Physical Without Stand (in.)	21.2 x 12.6 x 2.0
Packaging (mm)	595.0 x 210.0 x 396.0
Physical (mm)	539.0 x 406.19~511.9 x 202.0
Physical Without Stand (mm)	539.0 x 320.0 x 52.0
Package Contents	VG2456a Display, Power Cable, DisplayPort Cable, USB Type C cable, USB A/B Cable, Quick Start Guide
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Warranty	*Refurbished. 30-day DOA policy for full refund, with a 90-day repair warranty on parts and labor.

UPC: 766907016109



Contact Sales
ViewSonic.com
 888.881.8781
 email: salesinfo@viewsonic.com