


VG2755-2K - 27" 1440P ERGONOMIC 40-DEGREE TILT IPS MONITOR WITH USB C


Key Features



27"
DISPLAY




IPS
PANEL



2560x1440
RESOLUTION

WQHD (2560x1440p) Resolution



Product Description

Designed for the modern day office, the ViewSonic® VG2755-2K monitor delivers an efficient end-to-end enterprise experience. USB Type-C connectivity provides charging power, data, video, and audio over a single connector for convenience and reduced cable clutter. SuperClear® IPS panel technology delivers wide-angle viewing and incredibly vivid colors, while 3-sided thin bezel design provides a seamless viewing experience for multi-monitor setups. For enhanced productivity, an advanced ergonomic design offers a wide range of customizable adjustments for maximum comfort including pivot, swivel, height adjustment, and tilt. With the ability to tilt an impressive 40-degrees, this 27" monitor is ideal for users who prefer to work while standing up, as well as for those who like to use their screen for group discussions. Along with USB Type-C, additional connectivity options include HDMI, DisplayPort, and USB. This monitor is also shipped in eco-friendly biodegradable packaging, along with an easy-to-install quick release stand that makes for simple out-of-the box setup. The quick release stand also includes an integrated client mount and cable management features.

Specifications

	More Information
UPC	766907002393
Screen Size	27"
Viewable Area (in.)	27
Panel Type	IPS
Display Resolution	2560 x 1440
Display Resolution	QHD (2560x1440)
Static Contrast Ratio	1,000:1
Dynamic Contrast Ratio	80,000,000:1
Light Source	WLED
Brightness	350 cd/m2
Colors	16.7M
Color Space Support	True 8 bit
Aspect Ratio	16:9
Response Time (Typical GTG)	15ms
Response Time (GTG w/OD)	5ms
Viewing Angles	178° horizontal, 178° vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-glare, Hard coating (3H)
PC Resolution (max)	2560x1440
Mac® Resolution (max)	2560x1440
USB Type A	3
USB Type B	1
USB Type C	60W x 1
HDMI 1.4 In	1
DisplayPort	1
Internal Speakers	2W (x2)
Eco Mode (Conserve)	18.7 W
Eco Mode (optimized)	22.6 W
Consumption (typical)	27.7 W
Consumption (max)	57.7 W
Voltage	AC 100-240V (universal), 50-60Hz
Stand-by	0.3 W
Power Supply	Internal

Cable Organization	No
Kensington Lock Slot	1
Physical Controls	1,2,3,4,5,6 (Power)
On Screen Display	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)
Temperature	32-104° F (0 - 40° C)
Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Frequency Horizontal	15 ~ 90 KHz
Frequency Vertical	49 ~ 75 Hz
Digital Sync	TMDS for HDMI (v1.4), PCI-E for DisplayPort (v1.2), Micro-Packet for USB Type C
Height Adjust	130 mm / 5.1 in
Swivel	120°
Pivot (Right/Left)	90° / 90°
Tilt (Forward/Back)	40° / 5°
Regulations	cTUVus, FCC-B, ICES003, VG2755, EPEAT Certified, MX-CoC, Mexico Energy
Net (lbs)	15.2
Net Without Stand (lbs)	9.9
Gross (lbs)	22.5
Net (kg)	6.9
Net Without Stand (kg)	4.5
Gross (kg)	10.2
Packaging (in.)	27.2 x 8.6 x 16.9
Physical (in.)	24.1 x 16.0 x 8.0
Physical Without Stand (in.)	24.1 x 14.3 x 2.0
Packaging (mm)	692.0 x 218.0 x 430.0
Physical (mm)	613.0 x 406.0 x 202.0
Physical Without Stand (mm)	613.0 x 363.0 x 52.0
Package Contents	VG2755-2K, Power Cable, USB Type-C Cable, HDMI Cable, USB Upstream Cable, Quick Start Guide
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Warranty	*Refurbished. 30-day DOA policy for full refund, with a 90-day repair warranty on parts and labor.

UPC: 766907002393



Contact Sales
ViewSonic.com
888.881.8781
email:
salesinfo@viewsonic.com