




VIEWSONIC 4K UHD 4,000 ANSI LUMENS DESIGNED FOR XBOX GAMING PROJECTOR WITH 240HZ, 4.2MS AND HDR | PX749-4K

Key Features


- 4K Home Theater Projector: UHD (3840x2160p) 4K resolution with a 1.1-1.5 throw ratio and 4,000 ANSI lumens perfect for gaming and home entertainment
- Designed for Xbox: Experience immersive gameplay with 1440p at 120Hz, up to 240Hz refresh rate, and 4.2ms input lag for smooth, high-action gaming
- Vibrant Colors & HDR Support: SuperColor technology and HDR/HLG compatibility deliver a wide color gamut with enhanced contrast and visual depth.
- Large Screen Projection: Projects screen sizes from 30" to 300" with a throw distance of 3.9 ft - 43 ft; displays a 100" image from 8.2 ft
- Easy Setup & Image Adjustment: Features 1.3x optical zoom, 0.8x-2.0x digital zoom, H/V keystone, curved screen projection, 4-corner adjustment, and auto keystone
- Installation Options: This projector is ceiling mountable; compatible with ViewSonic mount PJ-WMK-007



30 - 300 in. / 0.76 - 7.62 m
DISPLAY



PANEL



VGA (640 x 480) to 4K (3840 x 2160)
RESOLUTION



Product Description



The ViewSonic® PX749-4K is an Ultra HD high-brightness projector that delivers stunning entertainment to your home theater. Boasting true 4K UHD resolution and HDR/HLG support, it ensures vivid, lifelike visuals for movies, sports, and gaming. Plus, thanks to 4,000 ANSI lumens of brightness, this projector delivers bright images in nearly any environment. Designed in partnership with Microsoft, this "Designed for Xbox" projector offers Xbox gameplay with 1440p native resolution at a 120Hz refresh rate and ultra-fast 4.2ms input lag. For other high-action games and movies, this projector can deliver a 240Hz refresh rate! No matter what you watch or how you play, the PX749-4K provides awesome visuals on screens up to 300".

Specifications

	More Information
UPC	766907020076
Light Source	DLP Lamp
Display Resolution	4K (3840x2160)
Display Resolution	3840 x 2160
Brightness (Lumens)	4,000 ANSI
Screen Size	30 - 300 in. / 0.76 - 7.62 m
Throw Distance	0.75m-9.76m (100"@2.50m)
Throw Ratio	1.13-1.47
Keystone	Vertical (+/- 40°) / Horizontal (+/- 40°)
Lens	1.3x optical zoom
Light Source Life, Normal (hours)	4000
Light Source Life, Dynamic Eco-Mode (hours)	20000
Color Depth	1.07 Billion Colors
Dynamic Contrast Ratio	12,000:1
Aspect Ratio	16:9
Frequency Horizontal	15K-135KHz
Frequency Vertical	23-240Hz
PC Resolution (max)	VGA (640 x 480) to 4K (3840 x 2160)
Mac® Resolution (max)	480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 2160p
USB 2.0 Type A	1
USB Type C	1 (Video input, and Power 5V/2A)
Ethernet LAN (RJ45)	1
3.5mm 12V Trigger	1
3.5mm Audio Out	1
Control (RS232)	1
HDMI 2.0 In	2
Internal Speakers	10W Cube
Voltage	100-240V+/- 10%, 50/60Hz AC
Consumption (typical)	310W
Stand-by	<0.5W
Physical Controls	Keypad, Power key
On Screen Display	Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)

Temperature	32-104º F (0 - 40º C)
Kensington Lock Slot	1
Net (lbs)	6.6
Gross (lbs)	8.6
Net (kg)	3.0
Gross (kg)	3.9
Packaging (in.)	19.3 x 14.8 x 12.3
Physical (in.)	14.0 x 9.6 x 4.8
Packaging (mm)	415.0 x 168.0 x 297.0
Physical (mm)	312.0 x 222.0 x 108.0
Regulations	cTUVus
Package Contents	PX749-4K projector, power cable, remote control, Quick Start Guide
Warranty	Three-year limited warranty on parts and labor
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.

UPC: 766907020076



Contact Sales

[ViewSonic.com](https://www.viewsonic.com)

888.881.8781

email:

salesinfo@viewsonic.com