



## PG706WU - 4000 LUMENS WUXGA PROJECTOR WITH RJ45 LAN CONTROL, VERTICAL KEYSTONE AND OPTICAL ZOOM

### Key Features

---



30 - 300 in. / 0.76 - 7.62 m  
**DISPLAY**



**PANEL**



1920 x 1200  
**RESOLUTION**

Flexible connectivity for your favorite devices.



### Product Description

---


The ViewSonic® PG706WU WUXGA projector features 4,000 lumens, 1920x1200 native resolution, an intuitive, user-friendly design, and a sleek white chassis. Exclusive SuperColor™ technology offers a wide color gamut for beautiful image production in nearly any environment. Equipped with Crestron® LAN controller, this projector makes it easy for IT admin to remotely control and manage multiple projectors from their workstations. With 1.1x optical zoom, vertical keystone, and extensive connectivity, the PG706WU provides flexible and quick set-up. What's more, an energy-saving SuperEco™ feature reduces power consumption and extends the lamp life by up to 20,000 hours. The PG706WU is the ideal projector for both high-definition presentations and vibrant multimedia entertainment.

# Specifications

|                                             | More Information             |
|---------------------------------------------|------------------------------|
| UPC                                         | 766907005882                 |
| Light Source                                | DLP Lamp                     |
| Display Resolution                          | WUXGA (1920x1200)            |
| Display Resolution                          | 1920 x 1200                  |
| Brightness (Lumens)                         | 4,000 ANSI                   |
| Screen Size                                 | 30 - 300 in. / 0.76 - 7.62 m |
| Throw Distance                              | 3.3 - 36.0 ft / 1.0 - 11.0 m |
| Throw Ratio                                 | 1.5-1.65                     |
| Keystone                                    | Vertical (+/- 40°)           |
| Lens                                        | 1.1x optical zoom            |
| Light Source (watt)                         | 245                          |
| Light Source Life, Normal (hours)           | 4000                         |
| Light Source Life, Dynamic Eco-Mode (hours) | 20000                        |
| Color Depth                                 | 1.07B Color (R/G/B 10bit)    |
| Dynamic Contrast Ratio                      | 12,000:1                     |
| Aspect Ratio                                | 16:10                        |
| Input Lag                                   | 37ms                         |
| Frequency Horizontal                        | 15K~102KHz                   |
| Frequency Vertical                          | 23~120Hz                     |
| PC Resolution (max)                         | 1920 x 1200                  |
| Mac® Resolution (max)                       | 1920 x 1200                  |
| USB 2.0 Type A                              | 1                            |
| Ethernet LAN (RJ45)                         | 1                            |
| 3.5mm Audio Out                             | 1                            |
| 3.5mm Audio In                              | 1                            |
| Control (RS232)                             | 1                            |
| HDMI 1.4 In                                 | 1                            |
| HDMI 1.4 (with HDCP 1.4)                    | 1                            |
| VGA In                                      | 1                            |
| VGA Out                                     | 1                            |
| Composite RCA Video In                      | 1                            |
| S-Video In                                  | 1                            |
| Internal Speakers                           | 10W (x1)                     |

|                                  |                                                                                                                    |
|----------------------------------|--------------------------------------------------------------------------------------------------------------------|
| <b>Consumption (typical)</b>     | 355W                                                                                                               |
| <b>Stand-by</b>                  | <0.5W                                                                                                              |
| <b>Physical Controls</b>         | Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, mode/enter, auto, source                  |
| <b>On Screen Display</b>         | Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality) |
| <b>Temperature</b>               | 32-104° F (0 - 40° C)                                                                                              |
| <b>Humidity (non-condensing)</b> | 0-90%                                                                                                              |
| <b>Kensington Lock Slot</b>      | 1                                                                                                                  |
| <b>Net (lbs)</b>                 | 6.2                                                                                                                |
| <b>Gross (lbs)</b>               | 8.7                                                                                                                |
| <b>Net (kg)</b>                  | 2.8                                                                                                                |
| <b>Gross (kg)</b>                | 4.0                                                                                                                |
| <b>Packaging (in.)</b>           | 16.3 x 11.7 x 6.6                                                                                                  |
| <b>Physical (in.)</b>            | 12.3 x 4.3 x 8.7                                                                                                   |
| <b>Packaging (mm)</b>            | 415.0 x 297.0 x 168.0                                                                                              |
| <b>Physical (mm)</b>             | 312.0 x 108.0 x 222.0                                                                                              |
| <b>Regulations</b>               | FCC, cTUVus, ROHS                                                                                                  |
| <b>Package Contents</b>          | PG706WU projector, power cable, VGA cable, remote control, Quick Start Guide                                       |
| <b>Warranty</b>                  | *Refurbished. 30-day DOA policy for full refund, with a 90-day repair warranty on parts and labor.                 |

UPC: 766907005882



**Contact Sales**  
[ViewSonic.com](http://ViewSonic.com)  
 888.881.8781  
 email:  
[salesinfo@viewsonic.com](mailto:salesinfo@viewsonic.com)