





VG2456V - 24" 1080P VIDEO CONFERENCE MONITOR WITH WEBCAM, 90W USB C, DOCKING, BUILT-IN GIGABIT ETHERNET


Key Features



24"
DISPLAY



IPS
PANEL



1920x1080
RESOLUTION



Product Description

The ViewSonic® VG2456V is a 24" (23.8" viewable) docking monitor with premium video conferencing features such as a pop-up webcam, adjustable LED lighting and more to help you look your best when calling into a meeting. Enjoy reliable and flexible network connectivity with the integrated gigabit Ethernet port, while the latest USB-C connectivity makes dual-monitor setup a breeze and provides up to 90W power delivery to your laptop. A best-in-class ergonomic design features 40-degree tilt and bi-directional pivot so your screen and workspace are as comfortable as you need—whether you are working in the office, or from home.


Specifications

[More Information](#)

UPC	766907021752
Screen Size	24"
Viewable Area (in.)	23.8
Panel Type	IPS
Display Resolution	1920 x 1080
Display Resolution	Full HD (1920x1080)
Static Contrast Ratio	1,000:1
Dynamic Contrast Ratio	80M:1
Light Source	LED
Brightness	250 cd/m2
Colors	16.7M
Color Space Support	8 bit (6 bit + Hi-FRC)
Aspect Ratio	16:9
Response Time (Typical GTG)	5ms
Viewing Angles	178º horizontal, 178º vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-Glare type, Hard-coating (3H), Haze 25%
Flicker-Free	Yes
Blue Light Filter	Yes
PC Resolution (max)	1920x1080
Mac® Resolution (max)	1920x1080
USB Type A	2
USB Type B	1
USB Type C	90W x 1
3.5mm Audio Out	1
Ethernet LAN (RJ45)	1
HDMI 1.4 In	1
DisplayPort	1
Internal Speakers	5W (x2)
Eco Mode (Conserve)	136
Eco Mode (optimized)	137
Consumption (typical)	139
Consumption (max)	165
Voltage	AC 100-240V (universal), 50-60Hz
Stand-by	0.5
Power Supply	Internal

Cable Organization	Yes
Headphone Hook	No
Microphone	noise-cancelling microphone array
Kensington Lock Slot	1
Webcam	Yes
Physical Controls	Key 1 (audio focus), Key 2, Key 3, Key 4, Key 5, Key 6 (power)
On Screen Display	Input Select, Conference Mode, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu
Temperature	32-104º F (0 - 40º C)
Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Frequency Horizontal	15 ~ 85 KHz
Frequency Vertical	50 ~ 75 Hz
Height Adjust	110 mm / 4.3 in
Swivel	60º
Pivot (Right/Left)	90º / 90º
Tilt (Forward/Back)	5º / 40º
Regulations	cTUVus, FCC-B, ICES003, Energy Star 8.0, EPEAT Silver, CEC, MX-CoC, Mexico Energy
Net (lbs)	15
Net Without Stand (lbs)	10
Gross (lbs)	20.9
Net (kg)	6.8
Net Without Stand (kg)	4.5
Gross (kg)	9.5
Packaging (in.)	23.9 " (W) x 16.2 " (H) x 8.3 " (D)
Physical (in.)	21.2 " (W) x 15.82~20.15 " (H) x 8 " (D)
Physical Without Stand (in.)	21.2 " (W) x 13.7 " (H) x 2.2 " (D)
Packaging (mm)	606 mm (W) x 411 mm (H) x 210 mm (D)
Physical (mm)	539 mm (W) x 401.83~511.83 mm (H) x 202 mm (D)
Physical Without Stand (mm)	539 mm (W) x 349 mm (H) x 56 mm (D)
Package Contents	LCD Display, Power Cable, HDMI Cable, USB Type C cable, USB A/B Cable, Quick Start Guide
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Warranty	*Refurbished. 30-day DOA policy for full refund, with a 90-day repair warranty on parts and labor.

UPC: 766907021752



Contact Sales
ViewSonic.com
888.881.8781 📞
email:
salesinfo@viewsonic.com