



VIEWSONIC 24" COLORPRO™ 1080P IPS MONITOR WITH 65W USB-C, RJ45, SRGB, AND DAISY CHAIN | VP2468A

Key Features


- 24 Inch Full HD (1920x1080p) IPS monitor with thin bezels and 60Hz refresh rate
- Ethernet RJ45 and USB-C connectivity for fast data, audio and video transfer, 65W charging over one cable
- Advanced ergonomics (tilt, swivel, pivot and height) for all-day comfort
- Flicker-Free technology and Blue Light Filter for reduced eye fatigue
- 100% sRGB, EBU, SMPTE-C, Rec. 709, and DICOM-SIM color spaces and Delta E<2 accuracy
- This monitor has been certified as capable of reproducing Pantone Matching System colors
- Hardware calibration ensures that the color displayed perfectly matches the original file
- The VP2468a supports laptops, PCs, Macs and more with USB-C, RJ45, USB, HDMI, DP (DaisyChain enabled) inputs



24"
DISPLAY



IPS
PANEL



1920x1080
RESOLUTION



Product Description


The ViewSonic® VP2468a is a 24" (23.8" viewable) Full HD monitor that delivers color accuracy crucial for professional applications. With a sleek frameless design and edge-to-edge SuperClear® IPS panel, this monitor provides an incredible viewing experience ideal for content creation and enterprise workstations. USB-C connectivity helps to simplify your workspace by delivering audio, video, data and up to 65W of power delivery over a single universal cable. In addition, DisplayPort out enables seamless daisy chaining to a second monitor. To ensure precise, uniform color, each of our monitors is factory calibrated to deliver an amazing Delta E<2 value for incredible color accuracy. An integrated color uniformity function ensures consistent chromaticity across the screen, while a 14-bit 3D look-up table generates a stunningly smooth palette of 4.39 trillion colors. Add to that 6-axis color adjustment functionality, and this monitor provides the ultimate color processing capability for professional applications.

Specifications

	More Information
UPC	766907009477
Screen Size	24"
Viewable Area (in.)	23.8
Panel Type	IPS
Display Resolution	1920 x 1080
Display Resolution	Full HD (1920x1080)
Static Contrast Ratio	1,000:1
Light Source	LED
Brightness	250 cd/m2
Colors	16.7M
Color Space Support	8 bits
Aspect Ratio	16:9
Response Time (Typical GTG)	5ms
Viewing Angles	178º horizontal, 178º vertical
Panel Surface	Anti-glare, Hard coating (3H)
PC Resolution (max)	1920x1080
Mac® Resolution (max)	1920x1080
USB Type A	2
USB Type C	65W x 1
3.5mm Audio Out	1
Ethernet LAN (RJ45)	1
HDMI 1.4 In	1
DisplayPort	1
DisplayPort Out	1
Eco Mode (Conserve)	17W
Eco Mode (optimized)	19W
Consumption (typical)	22W
Consumption (max)	25W
Voltage	AC 100-240V (universal), 50-60Hz
Stand-by	0.3W
Power Supply	Internal
Cable Organization	No
Kensington Lock Slot	1

Physical Controls	1,2,3,4,5,6 (Power)
On Screen Display	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)
Temperature	32-104º F (0 - 40º C)
Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Frequency Horizontal	15 ~ 90 KHz
Frequency Vertical	24 ~ 75 Hz
Height Adjust	130 mm / 5.1 in
Swivel	60º
Tilt (Forward/Back)	6° / 21°
Regulations	cTUVus, FCC-B, ICES003, Energy Star, EPEAT, MX-CoC, Mexico Energy
Net (lbs)	12.5
Net Without Stand (lbs)	7.0
Gross (lbs)	17.1
Net (kg)	5.7
Net Without Stand (kg)	3.2
Gross (kg)	7.8
Packaging (in.)	25.6 x 16.2 x 10.6
Physical (in.)	21.2 x 16.6 x 8.5
Physical Without Stand (in.)	21.2 x 12.2 x 1.9
Packaging (mm)	650.0 x 412.0 x 270.0
Physical (mm)	539.0 x 422.0 x 215.0
Physical Without Stand (mm)	539.0 x 311.0 x 48.0
Package Contents	VP2468a Display, Power Cable, DP to DP Cable, USB Type C cable, Quick Start Guide
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Warranty	Three-year limited warranty on parts, labor and backlight

UPC: 766907009477



Contact Sales
[ViewSonic.com](https://www.viewsonic.com)
 888.881.8781
 email:
salesinfo@viewsonic.com