

VIEWSONIC 27" COLORPRO™ 4K UHD IPS MONITOR WITH 60W USB-C, SRGB AND PANTONE VALIDATED | VP2756-4K

Key Features


- 27 Inch 4K UHD (3840x2160p) IPS monitor with thin bezels and 60Hz refresh rate
- In addition to fast data, audio and video transfer, USB-C also provides quick 60W charging over a single cable
- Advanced ergonomics (tilt, swivel, pivot and height) for all-day comfort
- Flicker-Free technology and Blue Light Filter for reduced eye fatigue
- 100% sRGB, EBU, SMPTE-C, and Rec. 709 color spaces and Delta E<2 accuracy
- This monitor has been certified as capable of reproducing Pantone Matching System colors
- The VP2756-4K supports laptops, PCs, Macs and more with USB-C, HDMI, USB and DisplayPort inputs



27"
DISPLAY



IPS
PANEL



3840 x 2160
RESOLUTION



Product Description


Engineered to deliver unmatched color accuracy crucial for professional applications, the ViewSonic® VP2756-4K UHD monitor displays your work with the vivid and lifelike color it deserves. With a SuperClear® IPS panel and a sleek 3-sided frameless design, the VP2756-4K provides a near-seamless viewing experience ideal for multi-monitor setups. The VP2756-4K is equipped with USB-C for single cable connectivity to deliver video, audio, and 60W of power delivery. To ensure precise, uniform color, each of our monitors is factory calibrated to deliver an amazing Delta E <2, so you can be confident what you see on screen is what your clients and customers will see as well.

Specifications

UPC	766907012972
Screen Size	27"
Viewable Area (in.)	27
Panel Type	IPS
Display Resolution	3840 x 2160
Display Resolution	4K (3840x2160)
Static Contrast Ratio	1,000:1
Dynamic Contrast Ratio	20,000,000:1
Light Source	LED
Brightness	350 cd/m2
Colors	1.07B
Color Space Support	10 bit (8 bit + A-FRC)
Aspect Ratio	16:9
Response Time (Typical GTG)	5ms
Viewing Angles	178º horizontal, 178º vertical
Panel Surface	Anti-Glare type, Hard-coating (3H), Haze 25%
PC Resolution (max)	3840 x 2160
Mac® Resolution (max)	3840 x 2160
USB Type A	2
USB Type B	1
USB Type C	60W x 1
HDMI 2.0 In	2
DisplayPort	1
Internal Speakers	2W (x2)
Eco Mode (Conserve)	37.5W
Eco Mode (optimized)	39.5W
Consumption (typical)	42W
Consumption (max)	122W
Voltage	100-240 VAC
Stand-by	0.3W
Power Supply	Internal
Cable Organization	No
Kensington Lock Slot	1
Physical Controls	Key 1 (power), Key 2, Key 3, Key 4, Key 5 (favorite)
On Screen Display	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu
Temperature	32-104º F (0 - 40º C)

Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Frequency Horizontal	15 ~ 136 KHz
Frequency Vertical	24 ~ 75 Hz
Height Adjust	130 mm / 5.1 in
Swivel	60°
Pivot (Right/Left)	90° / 90°
Tilt (Forward/Back)	5° / 21°
Regulations	cTUVus, FCC-B, ICES003, CEC, MX-CoC, Mexico Energy, Energy Star, EPEAT
Net (lbs)	15.1
Net Without Stand (lbs)	9.8
Gross (lbs)	21.0
Net (kg)	6.9
Net Without Stand (kg)	4.4
Gross (kg)	9.5
Packaging (in.)	29.1 x 18.3 x 8.9
Physical (in.)	24.1 x 16.15~21.27 x 8.5
Physical Without Stand (in.)	24.1 x 14.3 x 2.1
Packaging (mm)	740.0 x 465.0 x 225.0
Physical (mm)	613.0 x 410.0~540.0 x 215.0
Physical Without Stand (mm)	613.0 x 363.0 x 53.0
Package Contents	VP2756-4K, Power Cable, USB-C Cable, HDMI cable, USB-A/B Cable
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Warranty	Three-year limited warranty on parts, labor and backlight

UPC: 766907012972



Contact Sales
ViewSonic.com
 888.881.8781
 email:
salesinfo@viewsonic.com