



LS710HD - 4,200 ANSI LUMENS 1080P LASER PROJECTOR

Key Features


- High brightness 4200 Lumens 1080p laser projector with 0.49 short throw lens and advanced visual features
- Latest laser technology provides an extended lifespan of up to 30,000 hours
- Easy setup with short throw, 4 corner adjustment, and a 15-degree H/V keystone, 360-degree projection and portrait mode
- Access to original 4K quality content with HDR/HGL support
- Supports most media players, PCs, Macs, and mobile devices with inputs such as HDMI, USB, Ethernet LAN



40 - 300 in. / 1.0 - 7.6 m
DISPLAY



PANEL



VGA(640 x 480) to 4K UHD (3840 x 2160)
RESOLUTION



Product Description

Experience multimedia presentations and content in a new light with the ViewSonic® LS710HD projector. Powered by state-of-the-art laser phosphor technology, this lamp-free, high-brightness 1080p projector delivers a stunning 4,200 ANSI lumens so clients and colleagues can view images with pristine clarity even in areas with high ambient light. This eco-friendly projector is designed for enhanced sustainability, so you never have to worry about dealing with toxic mercury or frequent lamp replacements ever again. Experience easy image adjustments and flexible installation options, including short throw ratio, edge blending, H/V keystoneing and four corner projection. An ultra-short throw ratio of .49 empowers you to create immersive 100" movies and shows from just 1.1 meter away. Think bigger and present better with the ViewSonic LS701HD projector.

Specifications

More Information	
UPC	766907019957
Light Source	Laser
Display Resolution	Full HD (1920x1080)
Display Resolution	1920 x 1080
Brightness (Lumens)	4,200 ANSI
Screen Size	40 - 300 in. / 1.0 - 7.6 m
Throw Distance	0.43-3.25m (100"@1.08m)
Throw Ratio	0.49
Keystone	Vertical (+/- 15°) / Horizontal (+/- 15°)

Lens	Fixed Zoom
Light Source Life, Normal (hours)	20000
Light Source Life, Dynamic Eco-Mode (hours)	30000
Color Depth	1.07 Billion Colors
Dynamic Contrast Ratio	3,000,000:1
Aspect Ratio	16:9
Input Lag	37ms
Frequency Horizontal	15K~102KHz
Frequency Vertical	23-120Hz
PC Resolution (max)	VGA(640 x 480) to 4K UHD (3840 x 2160)
Mac® Resolution (max)	480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 4K UHD
USB 2.0 Type A	1
Ethernet LAN (RJ45)	1
3.5mm Audio Out	1
Control (RS232)	1
HDMI 2.0 In	1
HDMI 2.0 (with HDCP 2.2)	1
Internal Speakers	15W (x2)
Voltage	100-240V+/- 10%, 50/60Hz AC
Consumption (typical)	245W
Stand-by	<0.5W
Physical Controls	Keypad, Power key
On Screen Display	Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)
Temperature	32-104° F (0 - 40° C)
Kensington Lock Slot	1
Net (lbs)	9.9
Gross (lbs)	14.6
Net (kg)	4.5
Gross (kg)	6.6
Packaging (in.)	19.5 x 7.7 x 15.2
Physical (in.)	13.3 x 10.4 x 5.2
Packaging (mm)	496 x 195 x 387
Physical (mm)	337 x 265 x 131.5
Regulations	cTUVus
Package Contents	Projector, power cable, remote control, Quick Start Guide

Warranty

Three-year limited warranty on parts and labor, 1-year limited warranty on the light source, 1st year free Express Exchange® service. (One year Express Exchange Service requires product registration).

UPC: 766907019957



Contact Sales

ViewSonic.com

888.881.8781

email: salesinfo@viewsonic.com