





## VIEWSONIC 4K UHD 4,000 ANSI LUMENS DESIGNED FOR XBOX GAMING PROJECTOR WITH 240HZ, 4.2MS AND HDR | PX749-4K-S

### Key Features


---



30 - 300 in. / 0.76 - 7.62 m  
**DISPLAY**



**PANEL**



VGA (640 x 480) to 4K (3840 x 2160)  
**RESOLUTION**



### Product Description

---



The ViewSonic® PX749-4K is an Ultra HD high-brightness projector that delivers stunning entertainment to your home theater. Boasting true 4K UHD resolution and HDR/HLG support, it ensures vivid, lifelike visuals for movies, sports, and gaming. Plus, thanks to 4,000 ANSI lumens of brightness, this projector delivers bright images in nearly any environment. Designed in partnership with Microsoft, this "Designed for Xbox" projector offers Xbox gameplay with 1440p native resolution at a 120Hz refresh rate and ultra-fast 4.2ms input lag. For other high-action games and movies, this projector can deliver a 240Hz refresh rate! No matter what you watch or how you play, the PX749-4K provides awesome visuals on screens up to 300".

# Specifications

|                                             | More Information                                                                                                   |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------|
| UPC                                         | 766907032109                                                                                                       |
| Light Source                                | DLP Lamp                                                                                                           |
| Display Resolution                          | 4K (3840x2160)                                                                                                     |
| Display Resolution                          | 3840 x 2160                                                                                                        |
| Brightness (Lumens)                         | 4,000 ANSI                                                                                                         |
| Screen Size                                 | 30 - 300 in. / 0.76 - 7.62 m                                                                                       |
| Throw Distance                              | 0.75m-9.76m (100"@2.50m)                                                                                           |
| Throw Ratio                                 | 1.13-1.47                                                                                                          |
| Keystone                                    | Vertical (+/- 40°) / Horizontal (+/- 40°)                                                                          |
| Lens                                        | 1.3x optical zoom                                                                                                  |
| Light Source Life, Normal (hours)           | 4000                                                                                                               |
| Light Source Life, Dynamic Eco-Mode (hours) | 20000                                                                                                              |
| Color Depth                                 | 1.07 Billion Colors                                                                                                |
| Dynamic Contrast Ratio                      | 12,000:1                                                                                                           |
| Aspect Ratio                                | 16:9                                                                                                               |
| Frequency Horizontal                        | 15K-135KHz                                                                                                         |
| Frequency Vertical                          | 23-240Hz                                                                                                           |
| PC Resolution (max)                         | VGA (640 x 480) to 4K (3840 x 2160)                                                                                |
| Mac® Resolution (max)                       | 480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 2160p                                                                  |
| USB 2.0 Type A                              | 1                                                                                                                  |
| USB Type C                                  | 1 (Video input, and Power 5V/2A)                                                                                   |
| Ethernet LAN (RJ45)                         | 1                                                                                                                  |
| 3.5mm 12V Trigger                           | 1                                                                                                                  |
| 3.5mm Audio Out                             | 1                                                                                                                  |
| Control (RS232)                             | 1                                                                                                                  |
| HDMI 2.0 In                                 | 2                                                                                                                  |
| Internal Speakers                           | 10W Cube                                                                                                           |
| Voltage                                     | 100-240V+/- 10%, 50/60Hz AC                                                                                        |
| Consumption (typical)                       | 310W                                                                                                               |
| Stand-by                                    | <0.5W                                                                                                              |
| Physical Controls                           | Keypad, Power key                                                                                                  |
| On Screen Display                           | Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality) |

|                             |                                                                                                    |
|-----------------------------|----------------------------------------------------------------------------------------------------|
| <b>Temperature</b>          | 32-104º F (0 - 40º C)                                                                              |
| <b>Kensington Lock Slot</b> | 1                                                                                                  |
| <b>Net (lbs)</b>            | 6.6                                                                                                |
| <b>Gross (lbs)</b>          | 8.6                                                                                                |
| <b>Net (kg)</b>             | 3.0                                                                                                |
| <b>Gross (kg)</b>           | 3.9                                                                                                |
| <b>Packaging (in.)</b>      | 19.3 x 14.8 x 12.3                                                                                 |
| <b>Physical (in.)</b>       | 14.0 x 9.6 x 4.8                                                                                   |
| <b>Packaging (mm)</b>       | 415.0 x 168.0 x 297.0                                                                              |
| <b>Physical (mm)</b>        | 312.0 x 222.0 x 108.0                                                                              |
| <b>Regulations</b>          | cTUVus                                                                                             |
| <b>Package Contents</b>     | PX749-4K projector, power cable, remote control, Quick Start Guide                                 |
| <b>Warranty</b>             | *Refurbished. 30-day DOA policy for full refund, with a 90-day repair warranty on parts and labor. |
| <b>Recycle/Disposal</b>     | Please dispose of in accordance with local, state or federal laws.                                 |

UPC: 766907032109



**Contact Sales**  
[ViewSonic.com](https://www.viewsonic.com)

888.881.8781  
email:  
[salesinfo@viewsonic.com](mailto:salesinfo@viewsonic.com)