


## IFP5541 - 55" 4K 16:9 ANDROID EDLA VIEWBOARD INTERACTIVE DISPLAY WITH INTEGRATED MICROPHONE AND USB-C

### Key Features

---


- Smooth Multitasking Without Lag or Delays
- Immersive Audio for Maximum Engagement
- One-cable USB-C Simplicity
- Responsive Writing Experience
- Engaging Lessons with ViewSonic® Education Software
- Robust Security and Centralized Management
- Native Access to the Google Education Ecosystem
- Eco-Friendly & Energy Efficient



55"  
DISPLAY



PANEL



RESOLUTION



### Product Description

---

"The ViewSonic® ViewBoard® IFP5541 interactive display delivers the right balance of features, performance, and value for today's classrooms and meeting spaces. This 55-inch touchscreen is designed to feel premium and intuitive, making it easy for educators and teams to get up and running with minimal setup. Powered by the latest Android™ platform with EDLA certification, it provides secure, built-in access to Google Workspace, Microsoft 365, and familiar apps. Everything works right away, so users can focus on sharing ideas instead of troubleshooting technology.

One-cable USB-C simplifies connectivity, while powerful built-in audio ensures everyone can hear and be heard. Energy-efficient features help reduce power consumption over time, making the IFP5541 a smart, future-ready choice that's easy to deploy, easy to use, and easy on budgets."

# Specifications

| More Information            |                                                                |
|-----------------------------|----------------------------------------------------------------|
| UPC                         | 766907038927                                                   |
| OS                          | ViewBoard OS EDLA                                              |
| CPU                         | Rockchip RK3576                                                |
| Memory                      | 8GB LPDDR                                                      |
| Storage                     | 128GB eMMC                                                     |
| Microphone                  | Beamforming array x 8, full duplex echo cancellation           |
| Internal Speakers           | 25W*2 + 20W = 70W                                              |
| HDMI 2.1 In                 | 3                                                              |
| HDMI Out                    | 1                                                              |
| VGA                         | 1                                                              |
| DisplayPort                 | 1                                                              |
| SPDIF                       | 1                                                              |
| USB Type A                  | 5                                                              |
| USB Type B                  | 3                                                              |
| USB Type C                  | 100W x 1, 15W x 1                                              |
| RS232                       | 1                                                              |
| Ethernet LAN (RJ45)         | 2                                                              |
| Intel® OPS Slot In (80-pin) | 1                                                              |
| Line In                     | 1                                                              |
| Voltage                     | 100-240 VAC                                                    |
| Consumption (typical)       | 115.5 W                                                        |
| Stand-by                    | <0.5W                                                          |
| Physical Controls           | 7 (Power, Home, Input source, Touch, Freeze, Volume+, Volume-) |
| Temperature                 | 32-104° F (0 - 40° C)                                          |
| Non-Operating Temperature   | -4°F to 140°F (-20C to 60C)                                    |
| Humidity (non-condensing)   | 20-80%                                                         |
| Touch Technology            | IR Recognition                                                 |
| Touch Points                | 64 points                                                      |
| Tip Detection               | Dual tips: 3mm and 10mm / Finger: 12-15mm / Palm: 30mm         |
| Other                       | Palm Rejection                                                 |
| Latency                     | ≤5ms                                                           |
| Net (lbs)                   | 54.45                                                          |
| Gross (lbs)                 | 72.53                                                          |

|                                    |                                                                                                                                                                                                                                                              |
|------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Net (kg)</b>                    | 24.7                                                                                                                                                                                                                                                         |
| <b>Gross (kg)</b>                  | 32.9                                                                                                                                                                                                                                                         |
| <b>Packaging (in.)</b>             | 54.92x34.45x8.46                                                                                                                                                                                                                                             |
| <b>Physical (in.)</b>              | 50x30.83x3.42                                                                                                                                                                                                                                                |
| <b>Packaging (mm)</b>              | 1395x875x215                                                                                                                                                                                                                                                 |
| <b>Physical (mm)</b>               | 1270.5x783.2x86.8                                                                                                                                                                                                                                            |
| <b>VESA Compatible</b>             | 400 x 200 mm                                                                                                                                                                                                                                                 |
| <b>Warranty</b>                    | 3-year limited warranty on parts, labor and backlight, onsite warranty                                                                                                                                                                                       |
| <b>Recycle/Disposal</b>            | Please dispose of in accordance with local, state or federal laws.                                                                                                                                                                                           |
| <b>Package Contents</b>            | IFP5541, Power Cord (3m), USB-C Cable (1.8m) Remote control with AAA battery, USB Touch Cable (3m), Stylus x 2 (a set), Quick Start Guide + Compliance statement, RS232 adapter, Clamp x 5, Camera Plate, Screw x 4, HDMI cable 3m, VB-WIFI-004 WiFi Adapter |
| <b>Regulations</b>                 | CTUVus, FCC, Energy 8.0, EPEAT, CEC                                                                                                                                                                                                                          |
| <b>Ethernet LAN</b>                | 2 (10/100/1000 Mbps BaseT for Android and OPS)                                                                                                                                                                                                               |
| <b>Wifi</b>                        | VB-WIFI-004 adapter, 802.11AX + Bluetooth 5.0                                                                                                                                                                                                                |
| <b>Bluetooth</b>                   | Bluetooth 5.0                                                                                                                                                                                                                                                |
| <b>Screen Size</b>                 | 55"                                                                                                                                                                                                                                                          |
| <b>Light Source</b>                | DLED                                                                                                                                                                                                                                                         |
| <b>Display Resolution</b>          | 3840 x 2160                                                                                                                                                                                                                                                  |
| <b>Refresh Rate</b>                | 60Hz                                                                                                                                                                                                                                                         |
| <b>Aspect Ratio</b>                | 16:9                                                                                                                                                                                                                                                         |
| <b>Static Contrast Ratio</b>       | 5,000:1                                                                                                                                                                                                                                                      |
| <b>Dynamic Contrast Ratio</b>      | 5,000:1                                                                                                                                                                                                                                                      |
| <b>Backlight Life (Hours)</b>      | 65,000                                                                                                                                                                                                                                                       |
| <b>Brightness</b>                  | 400 cd/m2                                                                                                                                                                                                                                                    |
| <b>Response Time (Typical GTG)</b> | 8ms                                                                                                                                                                                                                                                          |
| <b>Viewing Angles</b>              | 178° horizontal, 178° vertical                                                                                                                                                                                                                               |
| <b>Panel Surface</b>               | Anti-glare, 9H Pencil hardness / 3.2mm thickness                                                                                                                                                                                                             |
| UPC: 766907038927                  |                                                                                                                                                                                                                                                              |



## Contact Sales

[ViewSonic.com](https://www.viewsonic.com)

888.881.8781

email:

[salesinfo@viewsonic.com](mailto:salesinfo@viewsonic.com)