



## 24" 1080P 240HZ 1MS GAMING MONITOR WITH AMD FREESYNC AND NVIDIA G-SYNC COMPATIBILITY | VX2479

### Key Features

---

- **REACT FASTER AT 240HZ:** A blazing 240Hz refresh rate and 1ms (MPRT) response time keep gameplay fluid and your reactions instant.
- **TEAR-FREE GAMEPLAY:** AMD FreeSync™ and NVIDIA G-SYNC® Compatibility synchronize your GPU and display to eliminate screen tearing and stutter.
- **SHARP, DETAILED FULL HD VISUALS:** Full HD 1080p resolution delivers crisp, detailed visuals across every scene and frame.
- **CONNECT YOUR WHOLE SETUP:** Two HDMI ports, one DisplayPort and audio out give you flexible connectivity for every device in your rig.
- **PLAY FOR LONGER WITH LESS STRAIN:** Flicker-Free technology and a blue light filter reduce eye fatigue so you can stay in the game longer.



24"  
**DISPLAY**



IPS  
**PANEL**



1920 x 1080  
**RESOLUTION**



### Product Description

---

The 24" VX2479 gaming monitor gives gamers the speed they need to stay one step ahead of the competition. A 240Hz refresh rate and 1ms (MPRT) response time mean fast-action scenes stay sharp and responsive when the pressure is on. AMD FreeSync™ and NVIDIA G-SYNC® Compatibility build on that speed by wiping out tearing and stutter, keeping your focus exactly where it belongs. HDR10 takes it further still, pulling richer contrast and deeper color out of every scene. The frameless 3-sided design makes multi-monitor configurations look as sharp as they perform, with two HDMI ports and one DisplayPort ready for every device in your setup.

# Specifications

|                             | More Information                             |
|-----------------------------|----------------------------------------------|
| UPC                         | 766907041064                                 |
| Screen Size                 | 24"                                          |
| Viewable Area (in.)         | 23.8                                         |
| Panel Type                  | IPS                                          |
| Display Resolution          | 1920 x 1080                                  |
| Display Resolution          | Full HD (1920x1080)                          |
| Static Contrast Ratio       | 1,000:1                                      |
| Dynamic Contrast Ratio      | 80,000,000:1                                 |
| Light Source                | LED                                          |
| Brightness                  | 250 cd/m2                                    |
| Colors                      | 16.7M                                        |
| Color Space Support         | 6 bit + FRC                                  |
| Aspect Ratio                | 16:9                                         |
| Response Time (Typical GTG) | 2ms                                          |
| Response Time (MPRT)        | 1ms                                          |
| Viewing Angles              | 178º horizontal, 178º vertical               |
| Backlight Life (Hours)      | 30,000                                       |
| Panel Surface               | Anti-Glare type, Hard-coating (3H), Haze 25% |
| Refresh Rate                | 240Hz                                        |
| PC Resolution (max)         | 1920 x 1080                                  |
| Mac® Resolution (max)       | 1920 x 1080                                  |
| 3.5mm Audio Out             | 1                                            |
| HDMI 1.4 In                 | 2                                            |
| DisplayPort                 | 1                                            |
| Eco Mode (Conserve)         | 19W                                          |
| Eco Mode (optimized)        | 22W                                          |
| Consumption (typical)       | 26W                                          |
| Consumption (max)           | 28W                                          |
| Voltage                     | 12V                                          |
| Stand-by                    | 0.5W                                         |
| Power Supply                | External                                     |
| Cable Organization          | No                                           |
| Kensington Lock Slot        | 1                                            |

|                                     |                                                                                     |
|-------------------------------------|-------------------------------------------------------------------------------------|
| <b>Physical Controls</b>            | Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power)                                |
| <b>On Screen Display</b>            | Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu |
| <b>Temperature</b>                  | 32-104º F (0 - 40º C)                                                               |
| <b>Humidity (non-condensing)</b>    | 20-90%                                                                              |
| <b>VESA Compatible</b>              | 100 x 100 mm                                                                        |
| <b>Frequency Horizontal</b>         | HDMI/DisplayPort: 30 ~ 268 KHz                                                      |
| <b>Frequency Vertical</b>           | HDMI/DisplayPort: 48 ~ 240 Hz                                                       |
| <b>Tilt (Forward/Back)</b>          | 5º / 20º                                                                            |
| <b>Regulations</b>                  | cTUVus, FCC-B, ICES003, NRCAN, NOM, Mexico Energy                                   |
| <b>Net (lbs)</b>                    | 7.1                                                                                 |
| <b>Net Without Stand (lbs)</b>      | 6.1                                                                                 |
| <b>Gross (lbs)</b>                  | 9.3                                                                                 |
| <b>Net (kg)</b>                     | 3.2                                                                                 |
| <b>Net Without Stand (kg)</b>       | 2.8                                                                                 |
| <b>Gross (kg)</b>                   | 4.2                                                                                 |
| <b>Packaging (in.)</b>              | 23.8 x 15.7 x 4.7                                                                   |
| <b>Physical (in.)</b>               | 21.33 x 16.2 x 7.09                                                                 |
| <b>Physical Without Stand (in.)</b> | 21.33 x 12.72 x 1.71                                                                |
| <b>Packaging (mm)</b>               | 605.0 x 400.0 x 120.0                                                               |
| <b>Physical (mm)</b>                | 541.86 x 411.6 x 180.0                                                              |
| <b>Physical Without Stand (mm)</b>  | 541.86 x 323 x 43.5                                                                 |
| <b>Package Contents</b>             | LCD Display Power Cable AC/DC Adapter DisplayPort Cable Quick Start Guide           |
| <b>Recycle/Disposal</b>             | Please dispose of in accordance with local, state or federal laws.                  |
| <b>Warranty</b>                     | Three-year limited warranty on parts, labor and backlight                           |

UPC: 766907041064



## Contact Sales

[ViewSonic.com](http://ViewSonic.com)

888.881.8781

email:

[salesinfo@viewsonic.com](mailto:salesinfo@viewsonic.com)