




27" COLORPRO™ QHD IPS MONITOR WITH 100W THUNDERBOLT, RJ45, SRGB 100% AND HDR400 | VP2776T-2K


Key Features



27"
DISPLAY



IPS
PANEL



2560 x 1440
RESOLUTION

Product Description

The ViewSonic ColorPro® VP2776T-2K is the docking solution for modern corporate desktops, incorporating a Thunderbolt™ 4 dock directly into the monitor to simplify your workspace with single-cable connectivity that delivers 100W power delivery, 2.5GbE Ethernet, and an integrated hub featuring HDMI, DisplayPort, and USB ports. Designed as a docking standard for mixed fleets, it eliminates compatibility headaches for IT managers by supporting daisy chaining on both Windows and macOS, allowing users to duplicate their set-up effortlessly, supporting dual 2K displays for added screen real estate. Sharp visuals honed by factory-calibrated 100% sRGB color accuracy and a fully ergonomic stand, the VP2776T-2K consolidates enterprise-grade performance and connectivity into a single, seamless desktop solution.

Specifications

More Information	
UPC	766907041408
Screen Size	27"
Viewable Area (in.)	27
Panel Type	IPS
Display Resolution	2560 x 1440
Display Resolution	WQHD (2560x1440)
Static Contrast Ratio	1,500:1
Dynamic Contrast Ratio	20M:1
Light Source	LED
Brightness	400
Colors	16.7M
Color Space Support	8 bit true

Aspect Ratio	16:9
Response Time (Typical GTG)	5ms
Viewing Angles	178º horizontal, 178º vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-Glare type, Hard-coating (3H), Haze 25%
Refresh Rate	120Hz
PC Resolution (max)	2560 x 1440
Mac® Resolution (max)	2560 x 1440
USB Type A	3
USB Type C	2 [1 upstream (15W) / 1 downstream (15W)]
3.5mm Audio Out	1
Ethernet LAN (RJ45)	1
HDMI 2.1 In	1
DisplayPort	1
DisplayPort Out	1
Internal Speakers	3W (x2)
Eco Mode (Conserve)	231
Eco Mode (optimized)	238
Consumption (typical)	245
Consumption (max)	250
Voltage	DC 24V
Stand-by	0.5
Power Supply	External
Cable Organization	No
Kensington Lock Slot	1
Physical Controls	Joystick key: Up, Right, Down, Left, Center; Power
On Screen Display	Input Select, Color Mode, ViewMode, Audio Adjust, Setup Menu
Temperature	32-104º F (0 - 40º C)
Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Frequency Horizontal	HDMI 2.1/DisplayPort/Thunderbolt = 30 ~ 183 KHz
Frequency Vertical	HDMI 2.1/DisplayPort/Thunderbolt = 48 ~ 120 Hz
Height Adjust	120 mm / 4.7 in
Swivel	-30º / 30º
Pivot (Right/Left)	90º / 90º
Tilt (Forward/Back)	3º / 23º

Regulations	cTUVus, FCC-B ICES003, Energy Star 8.0, EPEAT Silver, CEC
Net (lbs)	17.6
Net Without Stand (lbs)	10.1
Gross (lbs)	28.9
Net (kg)	8
Net Without Stand (kg)	4.6
Gross (kg)	13.1
Packaging (in.)	28.3 x 17.8 x 9
Physical (in.)	24.16 x 17.73 ~ 22.46 x 9.13
Physical Without Stand (in.)	24.16 x 14.32 x 2.20
Packaging (mm)	720 x 452 x 228
Physical (mm)	613.7 x 450.36 ~ 570.36 x 231.9
Physical Without Stand (mm)	613.7 x 363.85 x 55.8
Package Contents	LCD Display, DisplayPort Cable (v1.4), HDMI Cable (v2.1), Thunderbolt 4 Cable, USB-C to USB-A Cable, Power Adaptor, Power Cable, Quick Start Guide
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Warranty	Three-year limited warranty on parts, labor and backlight
UPC: 766907041408	

Contact Sales

[ViewSonic.com](https://www.viewsonic.com)

888.881.8781 ☎

email: salesinfo@viewsonic.com ✉