





## VP2468A - 24" COLORPRO™ 1080P IPS MONITOR WITH 65W USB C, RJ45, SRGB, AND DAISY CHAIN

### Key Features


---



24"  
**DISPLAY**



IPS  
**PANEL**



1920x1080  
**RESOLUTION**



### Product Description

---


The ViewSonic® VP2468a is a 24" (23.8" viewable) Full HD monitor that delivers color accuracy crucial for professional applications. With a sleek frameless design and edge-to-edge SuperClear® IPS panel, this monitor provides an incredible viewing experience ideal for content creation and enterprise workstations. USB-C connectivity helps to simplify your workspace by delivering audio, video, data and up to 65W of power delivery over a single universal cable. In addition, DisplayPort out enables seamless daisy chaining to a second monitor. To ensure precise, uniform color, each of our monitors is factory calibrated to deliver an amazing Delta E<2 value for incredible color accuracy. An integrated color uniformity function ensures consistent chromaticity across the screen, while a 14-bit 3D look-up table generates a stunningly smooth palette of 4.39 trillion colors. Add to that 6-axis color adjustment functionality, and this monitor provides the ultimate color processing capability for professional applications.

# Specifications

|                             | More Information                 |
|-----------------------------|----------------------------------|
| UPC                         | 766907011661                     |
| Screen Size                 | 24"                              |
| Viewable Area (in.)         | 23.8                             |
| Panel Type                  | IPS                              |
| Display Resolution          | 1920 x 1080                      |
| Display Resolution          | Full HD (1920x1080)              |
| Static Contrast Ratio       | 1,000:1                          |
| Light Source                | LED                              |
| Brightness                  | 250 cd/m2                        |
| Colors                      | 16.7M                            |
| Color Space Support         | 8 bits                           |
| Aspect Ratio                | 16:9                             |
| Response Time (Typical GTG) | 5ms                              |
| Viewing Angles              | 178º horizontal, 178º vertical   |
| Panel Surface               | Anti-glare, Hard coating (3H)    |
| PC Resolution (max)         | 1920x1080                        |
| Mac® Resolution (max)       | 1920x1080                        |
| USB Type A                  | 2                                |
| USB Type C                  | 65W x 1                          |
| 3.5mm Audio Out             | 1                                |
| Ethernet LAN (RJ45)         | 1                                |
| HDMI 1.4 In                 | 1                                |
| DisplayPort                 | 1                                |
| DisplayPort Out             | 1                                |
| Eco Mode (Conserve)         | 17W                              |
| Eco Mode (optimized)        | 19W                              |
| Consumption (typical)       | 22W                              |
| Consumption (max)           | 25W                              |
| Voltage                     | AC 100-240V (universal), 50-60Hz |
| Stand-by                    | 0.3W                             |
| Power Supply                | Internal                         |
| Cable Organization          | No                               |
| Kensington Lock Slot        | 1                                |

|                                     |                                                                                                                                                                                                                      |
|-------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Physical Controls</b>            | 1,2,3,4,5,6 (Power)                                                                                                                                                                                                  |
| <b>On Screen Display</b>            | Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality) |
| <b>Temperature</b>                  | 32-104º F (0 - 40º C)                                                                                                                                                                                                |
| <b>Humidity (non-condensing)</b>    | 20-90%                                                                                                                                                                                                               |
| <b>VESA Compatible</b>              | 100 x 100 mm                                                                                                                                                                                                         |
| <b>Frequency Horizontal</b>         | 15 ~ 90 KHz                                                                                                                                                                                                          |
| <b>Frequency Vertical</b>           | 24 ~ 75 Hz                                                                                                                                                                                                           |
| <b>Height Adjust</b>                | 130 mm / 5.1 in                                                                                                                                                                                                      |
| <b>Swivel</b>                       | 60º                                                                                                                                                                                                                  |
| <b>Tilt (Forward/Back)</b>          | 6° / 21°                                                                                                                                                                                                             |
| <b>Regulations</b>                  | cTUVus, FCC-B, ICES003, Energy Star, EPEAT, MX-CoC, Mexico Energy                                                                                                                                                    |
| <b>Net (lbs)</b>                    | 12.5                                                                                                                                                                                                                 |
| <b>Net Without Stand (lbs)</b>      | 7.0                                                                                                                                                                                                                  |
| <b>Gross (lbs)</b>                  | 17.1                                                                                                                                                                                                                 |
| <b>Net (kg)</b>                     | 5.7                                                                                                                                                                                                                  |
| <b>Net Without Stand (kg)</b>       | 3.2                                                                                                                                                                                                                  |
| <b>Gross (kg)</b>                   | 7.8                                                                                                                                                                                                                  |
| <b>Packaging (in.)</b>              | 25.6 x 16.2 x 10.6                                                                                                                                                                                                   |
| <b>Physical (in.)</b>               | 21.2 x 16.6 x 8.5                                                                                                                                                                                                    |
| <b>Physical Without Stand (in.)</b> | 21.2 x 12.2 x 1.9                                                                                                                                                                                                    |
| <b>Packaging (mm)</b>               | 650.0 x 412.0 x 270.0                                                                                                                                                                                                |
| <b>Physical (mm)</b>                | 539.0 x 422.0 x 215.0                                                                                                                                                                                                |
| <b>Physical Without Stand (mm)</b>  | 539.0 x 311.0 x 48.0                                                                                                                                                                                                 |
| <b>Package Contents</b>             | VP2468a Display, Power Cable, DP to DP Cable, USB Type C cable, Quick Start Guide                                                                                                                                    |
| <b>Recycle/Disposal</b>             | Please dispose of in accordance with local, state or federal laws.                                                                                                                                                   |
| <b>Warranty</b>                     | *Refurbished. 30-day DOA policy for full refund, with a 90-day repair warranty on parts and labor.                                                                                                                   |

UPC: 766907011661



## Contact Sales

[ViewSonic.com](https://www.viewsonic.com)

888.881.8781

email:

[salesinfo@viewsonic.com](mailto:salesinfo@viewsonic.com)