





VP2756-2K - 27" COLORPRO™ 1440P IPS MONITOR WITH 60W USB C, SRGB AND PANTONE VALIDATED

## Key Features


---



27"  
DISPLAY



IPS  
PANEL



2560 x 1440  
RESOLUTION



## Product Description

---

Engineered to deliver unmatched color accuracy crucial for professional applications, the ViewSonic® VP2756-2K QHD monitor displays your work with the vivid and lifelike color it deserves. With a SuperClear® IPS panel and a sleek 3-sided frameless design, the VP2756-2K provides a near-seamless viewing experience ideal for multi-monitor setups. The VP2756-2K is equipped with USB-C for single cable connectivity to deliver video, audio, and 60W of power delivery. To ensure precise, uniform color, each of our monitors is factory calibrated to deliver an amazing Delta E <2, so you can be confident what you see on screen is what your clients and customers will see as well.

## Specifications

---


---

[More Information](#)

|                                    |                                                                                     |
|------------------------------------|-------------------------------------------------------------------------------------|
| <b>UPC</b>                         | 766907017601                                                                        |
| <b>Screen Size</b>                 | 27"                                                                                 |
| <b>Viewable Area (in.)</b>         | 27                                                                                  |
| <b>Panel Type</b>                  | IPS                                                                                 |
| <b>Display Resolution</b>          | 2560 x 1440                                                                         |
| <b>Display Resolution</b>          | WQHD (2560x1440)                                                                    |
| <b>Static Contrast Ratio</b>       | 1,000:1                                                                             |
| <b>Dynamic Contrast Ratio</b>      | 20,000,000:1                                                                        |
| <b>Light Source</b>                | LED                                                                                 |
| <b>Brightness</b>                  | 350 cd/m2                                                                           |
| <b>Colors</b>                      | 16.7M                                                                               |
| <b>Color Space Support</b>         | 8 bit                                                                               |
| <b>Aspect Ratio</b>                | 16:9                                                                                |
| <b>Response Time (Typical GTG)</b> | 5ms                                                                                 |
| <b>Viewing Angles</b>              | 178º horizontal, 178º vertical                                                      |
| <b>Backlight Life (Hours)</b>      | 30,000                                                                              |
| <b>Panel Surface</b>               | Anti-Glare type, Hard-coating (3H), Haze 25%                                        |
| <b>PC Resolution (max)</b>         | 2560 x 1440                                                                         |
| <b>Mac® Resolution (max)</b>       | 2560 x 1440                                                                         |
| <b>USB Type A</b>                  | 2                                                                                   |
| <b>USB Type B</b>                  | 1                                                                                   |
| <b>USB Type C</b>                  | 60W x 1                                                                             |
| <b>HDMI 1.4 In</b>                 | 1                                                                                   |
| <b>DisplayPort</b>                 | 1                                                                                   |
| <b>Eco Mode (Conserve)</b>         | 34.5W                                                                               |
| <b>Eco Mode (optimized)</b>        | 38.5W                                                                               |
| <b>Consumption (typical)</b>       | 40W                                                                                 |
| <b>Consumption (max)</b>           | 121W                                                                                |
| <b>Voltage</b>                     | 100-240 VAC                                                                         |
| <b>Stand-by</b>                    | 0.3W                                                                                |
| <b>Power Supply</b>                | Internal                                                                            |
| <b>Cable Organization</b>          | No                                                                                  |
| <b>Kensington Lock Slot</b>        | 1                                                                                   |
| <b>Physical Controls</b>           | Key 1 (power), Key 2, Key 3, Key 4, Key 5 (favorite)                                |
| <b>On Screen Display</b>           | Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu |
| <b>Temperature</b>                 | 32-104º F (0 - 40º C)                                                               |

|                                     |                                                                                                    |
|-------------------------------------|----------------------------------------------------------------------------------------------------|
| <b>Humidity (non-condensing)</b>    | 20-90%                                                                                             |
| <b>VESA Compatible</b>              | 100 x 100 mm                                                                                       |
| <b>Frequency Horizontal</b>         | 15 ~ 130 KHz                                                                                       |
| <b>Frequency Vertical</b>           | 24 ~ 75 Hz                                                                                         |
| <b>Height Adjust</b>                | 130 mm / 5.1 in                                                                                    |
| <b>Swivel</b>                       | 60°                                                                                                |
| <b>Pivot (Right/Left)</b>           | 90° / 90°                                                                                          |
| <b>Regulations</b>                  | cTUVus, FCC-B, ICES003, CEC, MX-CoC, Mexico Energy                                                 |
| <b>Net (lbs)</b>                    | 15.1                                                                                               |
| <b>Net Without Stand (lbs)</b>      | 9.8                                                                                                |
| <b>Gross (lbs)</b>                  | 21.0                                                                                               |
| <b>Net (kg)</b>                     | 6.9                                                                                                |
| <b>Net Without Stand (kg)</b>       | 4.4                                                                                                |
| <b>Gross (kg)</b>                   | 9.5                                                                                                |
| <b>Packaging (in.)</b>              | 29.1 x 18.3 x 8.9                                                                                  |
| <b>Physical (in.)</b>               | 24.1 x 16.15~21.27 x 8.5                                                                           |
| <b>Physical Without Stand (in.)</b> | 24.1 x 14.3 x 2.1                                                                                  |
| <b>Packaging (mm)</b>               | 740.0 x 465.0 x 225.0                                                                              |
| <b>Physical (mm)</b>                | 613.0 x 410.0~540.0 x 215.0                                                                        |
| <b>Physical Without Stand (mm)</b>  | 613.0 x 363.0 x 53.0                                                                               |
| <b>Package Contents</b>             | VP2756-2K, Power Cable, USB-C Cable, HDMI cable, UAB-A/B Cable                                     |
| <b>Recycle/Disposal</b>             | Please dispose of in accordance with local, state or federal laws.                                 |
| <b>Warranty</b>                     | *Refurbished. 30-day DOA policy for full refund, with a 90-day repair warranty on parts and labor. |

UPC: 766907017601



**Contact Sales**  
[ViewSonic.com](https://www.viewsonic.com)  
 888.881.8781  
 email:  
[salesinfo@viewsonic.com](mailto:salesinfo@viewsonic.com)