




VX2485-MHU - 24" 1080P THIN-BEZEL IPS MONITOR WITH 60W USB C AND HDMI

## Key Features

---



24"  
DISPLAY



IPS  
PANEL



1920 x 1080  
RESOLUTION

Future-Proof inputs for flexible connectivity options.



## Product Description

---

Designed for the modern-day home office, the ViewSonic® VX2485-mhu is a 24" Full HD IPS monitor that combines style with optimal versatility and functionality. Whether for gaming, streaming, or editing, these sleek and slim displays are engineered with the everyday user in mind. Equipped with AMD FreeSync™ technology\*, this monitor's variable refresh rate capabilities virtually eliminate screen tearing and stuttering for a smoother viewing experience. With a three-sided borderless design, thin profile, and thoughtful cable management features, this display transforms the desktop into a streamlined and clutter-free workspace. What's more, a unique ergonomic stand allows you to easily tilt and swivel the screen for maximum comfort. The latest USB 3.2 Type-C connectivity delivers charging power, video, and audio over a single cable, while HDMI and VGA inputs keep you connected to your favorite devices.


\*AMD FreeSync supported via HDMI only

# Specifications

|                             | More Information                             |
|-----------------------------|----------------------------------------------|
| UPC                         | 766907007503                                 |
| Screen Size                 | 24"                                          |
| Viewable Area (in.)         | 23.8                                         |
| Panel Type                  | IPS                                          |
| Display Resolution          | 1920 x 1080                                  |
| Display Resolution          | Full HD (1920x1080)                          |
| Static Contrast Ratio       | 1,000:1                                      |
| Dynamic Contrast Ratio      | 80,000,000:1                                 |
| Light Source                | LED                                          |
| Brightness                  | 250 cd/m2                                    |
| Colors                      | 16.7M                                        |
| Color Space Support         | 8 bit (6 bit + A-FRC)                        |
| Aspect Ratio                | 16:9                                         |
| Response Time (Typical GTG) | 14ms                                         |
| Response Time (GTG w/OD)    | 5ms                                          |
| Viewing Angles              | 178º horizontal, 178º vertical               |
| Backlight Life (Hours)      | 30,000                                       |
| Panel Surface               | Anti-Glare type, Hard-coating (3H), Haze 25% |
| Refresh Rate                | 75Hz                                         |
| PC Resolution (max)         | 1920 x 1080                                  |
| Mac® Resolution (max)       | 1920 x 1080                                  |
| USB Type C                  | 60W x 1                                      |
| 3.5mm Audio In              | 1                                            |
| 3.5mm Audio Out             | 1                                            |
| VGA                         | 1                                            |
| HDMI 1.4 In                 | 1                                            |
| Internal Speakers           | 3W (x2)                                      |
| Eco Mode (Conserve)         | 13W                                          |
| Eco Mode (optimized)        | 16W                                          |
| Consumption (typical)       | 18W                                          |
| Consumption (max)           | 94W                                          |
| Voltage                     | 100-240 VAC, 50-60Hz                         |
| Stand-by                    | 0.5W                                         |

|                                     |                                                                                                    |
|-------------------------------------|----------------------------------------------------------------------------------------------------|
| <b>Power Supply</b>                 | External                                                                                           |
| <b>Cable Organization</b>           | No                                                                                                 |
| <b>Kensington Lock Slot</b>         | 1                                                                                                  |
| <b>Physical Controls</b>            | Key 1 (favorite), Key 2, Key 3, Key 4, Key 5, Key 6 (power)                                        |
| <b>On Screen Display</b>            | Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu                |
| <b>Temperature</b>                  | 32-104° F (0 - 40° C)                                                                              |
| <b>Humidity (non-condensing)</b>    | 20-90%                                                                                             |
| <b>VESA Compatible</b>              | 100 x 100 mm                                                                                       |
| <b>Frequency Horizontal</b>         | HDMI (v1.4): 16 ~ 84 KHz, USB Type C: 84 ~ 84 KHz                                                  |
| <b>Frequency Vertical</b>           | HDMI (v1.4): 48 ~ 76 KHz, USB Type C: 48 ~ 76 KHz                                                  |
| <b>Digital Sync</b>                 | TMDS for HDMI (v1.4). Micro-Packet for USB Type C.                                                 |
| <b>Swivel</b>                       | 30°                                                                                                |
| <b>Tilt (Forward/Back)</b>          | 5° / 20°                                                                                           |
| <b>Regulations</b>                  | cTUVus, FCC-B, ICES003, Energy Star, EPEAT, CEC, NRCAN, MX-CoC, Mexico Energy                      |
| <b>Net (lbs)</b>                    | 9.3                                                                                                |
| <b>Net Without Stand (lbs)</b>      | 5.9                                                                                                |
| <b>Gross (lbs)</b>                  | 12.8                                                                                               |
| <b>Net (kg)</b>                     | 4.2                                                                                                |
| <b>Net Without Stand (kg)</b>       | 2.7                                                                                                |
| <b>Gross (kg)</b>                   | 5.8                                                                                                |
| <b>Packaging (in.)</b>              | 24.6 x 16.1 x 4.9                                                                                  |
| <b>Physical (in.)</b>               | 21.2 x 15.9 x 9.8                                                                                  |
| <b>Physical Without Stand (in.)</b> | 21.2 x 12.7 x 2.0                                                                                  |
| <b>Packaging (mm)</b>               | 624.0 x 410.0 x 125.0                                                                              |
| <b>Physical (mm)</b>                | 540.0 x 404.0 x 250.0                                                                              |
| <b>Physical Without Stand (mm)</b>  | 540.0 x 322.0 x 50.0                                                                               |
| <b>Package Contents</b>             | VX2485-mhu Monitor, AC/DC Power Adapter, USB-C Cable, HDMI Cable, Quick Start Guide                |
| <b>Recycle/Disposal</b>             | Please dispose of in accordance with local, state or federal laws.                                 |
| <b>Warranty</b>                     | *Refurbished. 30-day DOA policy for full refund, with a 90-day repair warranty on parts and labor. |

UPC: 766907007503



**Contact Sales**  
[ViewSonic.com](http://ViewSonic.com)  
888.881.8781  
email: [salesinfo@viewsonic.com](mailto:salesinfo@viewsonic.com)