



VX3211-4K-MHD - 32" 4K UHD MONITOR WITH FREESYNC, HDR10, HDMI, DISPLAYPORT, VGA, AND SRGB


Key Features



32"
DISPLAY



MVA
PANEL



3840 x 2160
RESOLUTION

Future Proof inputs for flexible connectivity options




Product Description

Whether for office use or for enjoying entertainment at home, the ViewSonic® VX3211-4K-mhd delivers amazing Ultra HD resolution for an incredible multimedia viewing experience. With 4-times more pixels than Full HD, this 32" monitor delivers more content for maximized detail and efficiency. 95% NTSC color gamut coverage, a MEGA dynamic contrast ratio of 80M:1, and HDR10 content support all combine to deliver vivid color and contrast for incredible screen performance. For a fluid gaming experience, AMD FreeSync technology virtually eliminates screen tearing and stuttering. Built in Picture-in-Picture (PIP) mode lets you see more and do more for work or play, while built-in HDMI and DisplayPort inputs offer flexibility for your connection needs.

Specifications

	More Information
UPC	766907994612
Screen Size	32"
Viewable Area (in.)	31.5
Panel Type	MVA
Display Resolution	3840 x 2160
Static Contrast Ratio	3,000:1
Dynamic Contrast Ratio	80,000,000:1
Light Source	WLED
Brightness	300 cd/m2
Colors	1.07B
Color Space Support	8-bit+Hi-FRC
Aspect Ratio	16:9
Response Time (Typical GTG)	9.5ms
Response Time (GTG w/OD)	3ms
Viewing Angles	178º horizontal, 178º vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-glare, Hard coating (3H)
PC Resolution (max)	3840 x 2160
Mac® Resolution (max)	3840 x 2160
3.5mm Audio Out	1
HDMI 2.0 In	2
DisplayPort	1
Internal Speakers	2.5W (x2)
Eco Mode (Conserve)	35W
Eco Mode (optimized)	42W
Consumption (typical)	50W
Consumption (max)	65W
Voltage	AC 100-240V (universal), 50-60Hz
Stand-by	0.5W
Cable Organization	No
Kensington Lock Slot	1
Physical Controls	1, 2, 3, 4, 5, Power

On Screen Display	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)
Temperature	32-104° F (0 - 40° C)
Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Frequency Horizontal	HDMI: 15~204KHz, DisplayPort: 135~135KHz
Frequency Vertical	HDMI: 40~60KHz, DisplayPort: 40~60KHz
Digital Sync	TMDS for HDMI, PCI-E for DisplayPort
Tilt (Forward/Back)	5° / 13°
Regulations	cULus, FCC-B, ICES003, MX-CoC, Mexico Energy
Net (lbs)	14.6
Net Without Stand (lbs)	12.7
Gross (lbs)	22.2
Net (kg)	6.6
Net Without Stand (kg)	5.8
Gross (kg)	10.1
Packaging (in.)	33.0 x 24.2 x 11.1
Physical (in.)	28.7 x 19.5 x 9.1
Physical Without Stand (in.)	28.7 x 17.0 x 2.5
Packaging (mm)	838.0 x 615.0 x 282.0
Physical (mm)	729.7 x 495.5 x 230.3
Physical Without Stand (mm)	729.7 x 432.8 x 64.3
Package Contents	VX3211-4K Display, Power Cable, HDMI Cable, Quick Start Guide
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Warranty	*Refurbished. 30-day DOA policy for full refund, with a 90-day repair warranty on parts and labor.
UPC: 766907994612	



Contact Sales
[ViewSonic.com](https://www.viewsonic.com)
888.881.8781
email: salesinfo@viewsonic.com