




VX3418-2KPC - 34" 21:9 CURVED 1440P 1MS 180HZ GAMING MONITOR WITH
FREESYNC PREMIUM


Key **Features**



34
DISPLAY



MVA
PANEL



3440 x 1440
RESOLUTION



Product **Description**

With an immersive 1500R curved screen and stunning WQHD 3440 x 1440 resolution, the ViewSonic® VX3418-2KPC monitor provides an incredible viewing experience for work or play. With features including a high 180Hz* refresh rate, 1ms (MPRT) response time and FreeSync Premium technology, this monitor virtually eliminates screen tearing and stuttering for a fluid gaming experience. The VX3418-2KPC also comes equipped with ViewSonic exclusive ViewMode™ presets, which offer optimized screen performance for different home entertainment applications such as watching movies, editing files, or playing video games. Two HDMI (v2.0) inputs, and one DisplayPort (v1.2) input offers flexible connectivity for both general use and entertainment.

*180Hz refresh rate with DisplayPort

Specifications

More Information	
UPC	766907015140
Monitor Series	OMNI Gaming
Screen Size	34
Viewable Area (in.)	34
Panel Type	MVA
Display Resolution	3440 x 1440
Display Resolution	WQHD (3440x1440)
Static Contrast Ratio	4,000:1
Dynamic Contrast Ratio	80,000,000:1
Light Source	LED
Brightness	300 cd/m2

Colors	16.7M
Color Space Support	6 bit+FRC
Aspect Ratio	21:9
Response Time (MPRT)	1ms
Viewing Angles	178º horizontal, 178º vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-Glare type, Hard-coating (3H), Haze 25%
Curvature	1500R
Refresh Rate	144Hz
PC Resolution (max)	3440 x 1440
Mac® Resolution (max)	3440 x 1440
3.5mm Audio In	1
HDMI 2.0 In	2
DisplayPort	2
Internal Speakers	5W (x2)
Eco Mode (Conserve)	23.8
Eco Mode (optimized)	29.6
Consumption (typical)	36W
Consumption (max)	48W
Voltage	100-240 VAC
Stand-by	0.5W
Power Supply	External
Cable Organization	No
Kensington Lock Slot	1
Physical Controls	Key 1 (power), Key 2, Key 3, Key 4, Key 5 (favorite)
On Screen Display	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu
Temperature	32-104º F (0 - 40º C)
Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Frequency Horizontal	HDMI (v2.0): 31.469 ~ 150.849, DisplayPort: 31.469 ~ 217.32 KHz
Frequency Vertical	HDMI (v2.0): 48 ~ 100 Hz, DisplayPort: 48 ~ 180 Hz
Height Adjust	80 mm / 3.1 in
Tilt (Forward/Back)	5º / 10º
Regulations	cTUVus, FCC-B, ICES003, CEC, MX-CoC, Mexico Energy
Net (lbs)	16.8
Gross (lbs)	22.5

Net (kg)	7.6
Gross (kg)	10.2
Packaging (in.)	35.0 x 20.8 x 7.5
Physical (in.)	31.8 x 18.2~21.3 x 13.0
Physical Without Stand (in.)	31.8 x 14.2 x 4.9
Packaging (mm)	888.0 x 528.0 x 190.0
Physical (mm)	806.0 x 462.3~542.3 x 331.0
Physical Without Stand (mm)	806.0 x 362.0 x 125.0
Package Contents	VX3418-2KPC Display, Power Cable, AC/DC Adapter, DP to DP Cable, Quick Start Guide
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Warranty	*Refurbished. 30-day DOA policy for full refund, with a 90-day repair warranty on parts and labor.

UPC: 766907015140



Contact Sales

ViewSonic.com

888.881.8781 

email: salesinfo@viewsonic.com 