




PA700X - 4500 LUMENS XGA HIGH BRIGHTNESS PROJECTOR WITH DUAL HDMI, USB, VGA, RS232

Key Features



30 - 300 in. / 0.76 - 7.62 m
DISPLAY **PANEL**



VGA(640 x 480) to FullHD(1920 x 1080)
RESOLUTION



Product Description


Put your presentations in the best light with the ViewSonic® PA700X XGA projector. This state-of-the-art high brightness projector combines a powerful 4,500 ANSI lumens and XGA resolution for stunning images on a 300" screen. Dual HDMI ports empower you to seamlessly switch between different devices while a USB Type-A port lets you connect wireless dongles directly into the projector. And with easy USB software updates, you can effortlessly keep your projector up-to-date with the latest features. Whether you consider the PA700X a business projector or an education projector, this powerful device is the perfect presentation tool for any environment.

Specifications

| | |
|--|--|
| UPC | 766907023367 |
| Light Source | DLP Lamp |
| Display Resolution | XGA (1024x768) |
| Display Resolution | 1024 x 768 |
| Brightness (Lumens) | 4,500 ANSI |
| Screen Size | 30 - 300 in. / 0.76 - 7.62 m |
| Throw Distance | 1.18m-13.17m (100"@3.94m) |
| Throw Ratio | 1.94-2.16 |
| Keystone | Vertical (+/- 40°) |
| Lens | 1.1x optical zoom |
| Light Source (watt) | 240 |
| Light Source Life, Normal (hours) | 4000 |
| Light Source Life, Dynamic Eco-Mode (hours) | 12000 |
| Color Depth | 1.07 Billion Colors |
| Dynamic Contrast Ratio | 22,000:1 |
| Aspect Ratio | 4:3 |
| Input Lag | 37ms |
| Frequency Horizontal | 15K~102KHz |
| Frequency Vertical | 23-120Hz |
| PC Resolution (max) | VGA(640 x 480) to FullHD(1920 x 1080) |
| Mac® Resolution (max) | 480i, 480p, 576i, 576p, 720p, 1080i, 1080p |
| USB 2.0 Type A | 1 |
| 3.5mm Audio Out | 1 |
| 3.5mm Audio In | 1 |
| Control (RS232) | 1 |
| HDMI 1.4 (with HDCP 1.4) | 2 |
| VGA In | 1 |
| VGA Out | 1 |
| Internal Speakers | 3W (x1) |
| Voltage | 100-240V+/- 10%, 50/60Hz AC |
| Consumption (typical) | 300W |
| Stand-by | <0.5W |
| Physical Controls | Keypad, Power key |
| On Screen Display | Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality) |
| Temperature | 32-104° F (0 - 40° C) |

| | |
|-----------------------------|--|
| Kensington Lock Slot | 1 |
| Net (lbs) | 6 |
| Gross (lbs) | 8.4 |
| Net (kg) | 2.7 |
| Gross (kg) | 3.8 |
| Packaging (in.) | 15.7 x 13.3 x 6.6 |
| Physical (in.) | 12.2 x 9.2 x 4.5 |
| Packaging (mm) | 400 x 337 x 168 |
| Physical (mm) | 309 x 234 x 115 |
| Regulations | cTUVus |
| Package Contents | Projector, power cable, remote control, Quick Start Guide |
| Warranty | *Refurbished. 30-day DOA policy for full refund, with a 90-day repair warranty on parts and labor. |
| Recycle/Disposal | Please dispose of in accordance with local, state or federal laws. |

UPC: 766907023367



Contact Sales
ViewSonic.com
 888.881.8781
 email:
salesinfo@viewsonic.com