


VP2785-4K - 27" 4K UHD ADOBERGB COLORPRO™ IPS MONITOR W/ USB C & HDR10

Key Features


- 4K UHD (3840x2160p) advanced ergonomic, 60Hz IPS monitor deliver lifelike colors
- A three-sided ultra-thin bezel shows off more of your masterpiece, and less of the monitor
- Connect video, audio, data and power with a single USB-C cable and plug in peripherals like USB drives and mice with the USB hub
- Screen wide 99% Adobe RGB, EBU, SMPTE-C, Rec. 709, and DICOM-SIM color spaces, Delta E<2 accuracy, and a smooth palette of 4.39 trillion colors deliver precise, lifelike images
- Quick and easy calibration ensures that the color displayed perfectly matches the original file
- Displays videos as they are intended to be seen with HDR10 content support – giving you a fuller, more immersive viewing experience
- The VP2785-4K supports laptops, PCs, and Apple/Mac operating systems with USB 3.1 Type C, HDMI 2.0 with HDCP 2.2, DisplayPort, and Mini DisplayPort inputs



27"
DISPLAY



IPS
PANEL



3840 x 2160
RESOLUTION



Product Description

Covering 99% of the Adobe RGB color space and 96% DCI-P3, the ViewSonic® VP2785-4K Ultra HD monitor meets the high color standards of photographers, graphic designers, video editors, print departments, and other design professionals. With a sleek and modern design, the VP2785-4K features future-proof DisplayPort technology, as well as HDMI and USB 3.1 type C ports. To ensure precise, uniform color, each of our monitors is factory calibrated to deliver an amazing Delta E<2 value for superior color accuracy. An integrated color uniformity function ensures consistent chromaticity across the screen, while a 14-bit 3D look-up table generates a stunningly smooth palette of 4.39 trillion colors. What's more, productivity-boosting features include an advanced ergonomic design, a built-in ambient light and presence sensor, and a KVM switch. Hardware calibration is also available with the optional ViewSonic Colorbration Kit, which allows you to quickly and easily calibrate the monitor for photography, graphic design, content creation, and other color-critical applications.

Specifications

	More Information
UPC	766907902112
Screen Size	27"
Viewable Area (in.)	27
Panel Type	IPS
Display Resolution	3840 x 2160
Static Contrast Ratio	1,000:1
Dynamic Contrast Ratio	20M:1
Light Source	LED
Brightness	350 cd/m2
Colors	1.07B
Color Space Support	10bit (8bit + A-FRC)
Aspect Ratio	16:9
Response Time (Typical GTG)	14ms
Response Time (GTG w/OD)	7ms
Viewing Angles	178º horizontal, 178º vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-glare, Hard coating (3H)
PC Resolution (max)	3840 x 2160
Mac® Resolution (max)	3840 x 2160
USB Type A	3
USB Type B	1
USB Type C	1
3.5mm Audio Out	1
HDMI 2.0 (with HDCP 2.2)	2
DisplayPort	1
Mini DisplayPort	1
Eco Mode (Conserve)	45
Eco Mode (optimized)	55
Consumption (typical)	67
Consumption (max)	70
Voltage	AC 100-240V (universal), 50-60Hz
Stand-by	0.5W
Cable Organization	No

Kensington Lock Slot	1
Physical Controls	1, 2, 3, 4, 5, Power
On Screen Display	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)
Temperature	32-104° F (0 - 40° C)
Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Frequency Horizontal	15 ~90KHz
Frequency Vertical	24 ~120Hz
Digital Sync	TMDS, PCI-E
Height Adjust	130 mm / 5.1 in
Swivel	120°
Pivot (Right/Left)	90° / 90°
Tilt (Forward/Back)	5° / 21°
Regulations	UL, cUL, FCC-B, Mexico CoC, CB , CE, WEEE, RoHS, ErP, REACH, TCO6.0, Ukraine, GS, Ergo
Net (lbs)	14.1
Net Without Stand (lbs)	8.7
Gross (lbs)	22.3
Net (kg)	6.4
Net Without Stand (kg)	3.9
Gross (kg)	10.1
Packaging (in.)	28.3 x 10.6 x 18.1
Physical (in.)	24.1 x 21.5 x 8.5
Physical Without Stand (in.)	24.1 x 14.3 x 2.3
Packaging (mm)	720 x 268 x 460
Physical (mm)	612.4 x 545.5 x 215.0
Physical Without Stand (mm)	612.4 x 362.7 x 57.6
Package Contents	VP2785-4K Display, AC/DC Adapter, Power Cable, Mini DP to DisplayPort Cable , USB 3.1 Gen 1 Type-C Cable, USB 3.0 Up Stream Cable, Quick Start Guide, ViewSonic Wizard CD-Rom
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.

UPC: 766907902112



Contact Sales
ViewSonic.com
888.881.8781
email: salesinfo@viewsonic.com