


EP2410T-B1 - 24" DISPLAY, 1920 X 1080 RESOLUTION, 250 CD/M2 BRIGHTNESS, 16/7

## Key Features


- 10-POINT MULTI-TOUCH
- POWERFUL QUAD CORE PROCESSOR
- OPTIONAL AUTOMATIC HAND SANITIZING DISPENSER
- OPTIONAL CONTENT MANAGEMENT SOFTWARE
- " EQUIPPED WITH WI-FI, BLUETOOTH, AND RJ45
- VERSATILE CONNECTIVITY



24  
DISPLAY



IPS  
PANEL



RESOLUTION

## Product Description

The ViewSonic® EP2410T-B1 is a Health Flex Hand Sanitizing Station bundled with a 24" touch display, media player, and hand sanitizer dispenser holder. With a sleek and slim design, and optional touchless dispenser for hands-free sanitizing, the EP2410T-B1 makes displaying health notices, business information, and promotions easier than ever. Featuring Full HD 1080p resolution, 178°/178° wide-angle viewing, 250-nit brightness, 1,000:1 contrast ratio, and dual stereo speakers, the EP2410T-B1 delivers customized multimedia messaging with vivid clarity. Photo and video files can be played back using the external Octa-core media player and 16GB of internal memory, or you can add your own media player using the convenient media player cradle inside the lockable security door. Highlight your commitment to your customers' health with the ViewSonic Health Flex Hand Sanitizing Station bundle.

## Specifications

### More Information

<b>Screen Size</b>	24
<b>Viewable Area (in.)</b>	23.6
<b>Display Resolution</b>	1920 x 1080
<b>Light Source</b>	LED
<b>Static Contrast Ratio</b>	3,000:1
<b>Brightness</b>	250 cd/m2
<b>Colors</b>	16.7M
<b>Viewing Angles</b>	178° horizontal, 178° vertical

<b>Backlight Life (Hours)</b>	30,000
<b>Response Time (Typical GTG)</b>	16ms
<b>Panel Surface</b>	Anti-glare, hard-coating (3H)
<b>Panel Type</b>	IPS
<b>Operation Rating</b>	16/7
<b>Internal Speakers</b>	2.5W (x2)
<b>3.5mm Audio Out</b>	1
<b>3.5mm Mic In</b>	1
<b>Ethernet LAN (RJ45)</b>	1
<b>HDMI 1.4 In</b>	1
<b>HDMI 1.4 Out</b>	1
<b>USB 2.0 Type A</b>	4
<b>USB 2.0 Type B</b>	1
<b>SD Card Slot</b>	1
<b>DC Jack (12V/4A)</b>	1
<b>Media Player Type</b>	Yes
<b>Voltage</b>	AC 100-240V (universal), 50-60Hz
<b>Consumption (max)</b>	40W
<b>Consumption (typical)</b>	16W
<b>Stand-by</b>	<2W
<b>Temperature</b>	32-95° F (0 - 35° C)
<b>Humidity (non-condensing)</b>	20-90%
<b>Frequency Horizontal</b>	15~90kHz
<b>Frequency Vertical</b>	24~75Hz
<b>Gross (lbs)</b>	66.7
<b>Net (lbs)</b>	54.4
<b>Gross (kg)</b>	30.3
<b>Net (kg)</b>	24.7
<b>Packaging (in.)</b>	65.0 x 20.0 x 20.0
<b>Physical (in.)</b>	60.0 x 16.0 x 16.0
<b>Packaging (mm)</b>	1651.0 x 508.0 x 508.0
<b>Physical (mm)</b>	1524.0 x 406.4 x 406.4
<b>Regulations</b>	cTUVus, FCC-B(including ICES003), FCC-ID, CA IC
<b>Package Contents</b>	STND-059 x 1, VSD243 x 1
<b>Recycle/Disposal</b>	Please dispose of in accordance with local, state or federal laws.
<b>Warranty</b>	One-year limited warranty on parts and labor

---

## Contact Sales

[ViewSonic.com](http://ViewSonic.com)

888.881.8781

email: [salesinfo@viewsonic.com](mailto:salesinfo@viewsonic.com)