



VIEWSONIC 27" 1440P LED MONITOR WITH HDMI, DISPLAYPORT AND ADAPTIVE SYNC | VA2715-2K-MHD

Key Features


- Versatile Monitor: 27 Inch 2K QHD (2560x1440p) LED monitor with thin bezels and 100Hz refresh rate
- Enhanced Viewing Comfort: Flicker-Free technology and Blue Light Filter for reduced eye fatigue
- No Image Tearing: VESA Adaptive Sync technology enables smooth frame rates to aid you in battle
- Optimized View Settings: Offers "Game," "Movie," "Web," "Text," and "Mono" presets
- Flexible Connectivity: The VA2715-2K-MHD supports laptops, PCs, Macs and more with HDMI and DisplayPort inputs




27"
DISPLAY



MVA
PANEL



2560x1440
RESOLUTION



WQHD (2560x1440p) RESOLUTION


Product Description

The ViewSonic® VA2715-2K-MHD is a 27" QHD monitor that delivers solid multimedia features at a great value with flexible connectivity, wide-angle viewing, and amazing screen performance. Featuring 2560 x 1440 resolution and a frameless design, this monitor provides a near-seamless viewing experience ideal for multi-monitor setups. Whether for working at the office, or enjoying entertainment at home, the VA2715-2K-MHD also features DisplayPort and HDMI ports for flexible connectivity to PCs, laptops, and other multimedia devices. In addition, a 3-year limited warranty, along with one of the industry's best pixel performance policies, makes the VA2715-2K-MHD a great overall value choice.

Specifications

UPC	766907014662
Screen Size	27"
Viewable Area (in.)	27
Panel Type	MVA
Display Resolution	2560 x 1440
Display Resolution	WQHD (2560x1440)
Static Contrast Ratio	4,000:1
Dynamic Contrast Ratio	50,000,000:1
Light Source	LED
Brightness	250 cd/m2
Colors	16.7M
Aspect Ratio	16:9
Response Time (GTG w/OD)	5ms
Viewing Angles	178º horizontal, 178º vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-glare, Hard coating (3H)
Refresh Rate	100Hz
PC Resolution (max)	2560x1440
Mac® Resolution (max)	2560x1440
3.5mm Audio Out	1
HDMI 1.4 In	2
DisplayPort	1
Internal Speakers	2W (x2)
Eco Mode (Conserve)	19W
Eco Mode (optimized)	24W
Consumption (typical)	29W
Consumption (max)	31W
Voltage	100-240 VAC, 50-60Hz
Stand-by	0.5W
Power Supply	External
Cable Organization	No
Kensington Lock Slot	1
Physical Controls	U, R, D, L, EN (power)
On Screen Display	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu
Temperature	32-104º F (0 - 40º C)
Humidity (non-condensing)	20-90%

VESA Compatible	100 x 100 mm
Frequency Horizontal	15 ~ 120KHz
Frequency Vertical	24 ~ 100Hz
Tilt (Forward/Back)	5° / 20°
Regulations	RoHS, WEEE, BSMI, RCM, VCCI, PSE
Net (lbs)	7.9
Net Without Stand (lbs)	6.8
Gross (lbs)	11.0
Net (kg)	3.6
Net Without Stand (kg)	3.1
Gross (kg)	5.0
Packaging (in.)	27.1 x 17.6 x 5.0
Physical (in.)	24.1 x 18.0 x 8.1
Physical Without Stand (in.)	24.1 x 14.2 x 1.6
Packaging (mm)	688.0 x 448.0 x 128.0
Physical (mm)	613.0 x 456.0 x 205.0
Physical Without Stand (mm)	613.0 x 361.0 x 40.0
Package Contents	VA2715-2K-MHD x1, HDMI Cable (v1.4; Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Warranty	Three-year limited warranty on parts, labor and backlight
UPC: 766907014662	



Contact Sales
ViewSonic.com
 888.881.8781
 email:
salesinfo@viewsonic.com