





# VIEWSONIC IFP6552-C1 - 65" VIEWBOARD® INTERACTIVE FLAT PANEL BUNDLE WITH CHROMEBOX

## Key Features


- 65" ViewBoard IFP6552 4K interactive flat panel
- VB-WIFI-001 WiFi and Bluetooth adapter
- NMP760 Chromebox
- WMK-047 wall mount



65"  
DISPLAY



PANEL



RESOLUTION

## Product Description

Ideal for education environments, this all-in-one ViewBoard Bundle includes a 65" ViewBoard IFP6552 4K interactive flat panel, a VB-WIFI-001 WiFi and Bluetooth adapter, a NMP760 Chromebox, and a WMK-047 wall mount.

## Specifications

| More Information    |                                   |
|---------------------|-----------------------------------|
| OS                  | ViewBoard OS based on Android 9.0 |
| GPU                 | ARM Mali-G52                      |
| CPU                 | ARM Quad Core Cortex A73          |
| CPU Processor Speed | 1.8GHz                            |

|                                              |                                                          |
|----------------------------------------------|----------------------------------------------------------|
| <b>Memory</b>                                | 4GB                                                      |
| <b>Storage</b>                               | 32GB                                                     |
| <b>Internal Speakers</b>                     | 15W (x2)                                                 |
| <b>Subwoofer</b>                             | 15W (x1)                                                 |
| <b>HDMI 2.0 In</b>                           | 3                                                        |
| <b>HDMI Out</b>                              | 1                                                        |
| <b>VGA</b>                                   | 1                                                        |
| <b>DisplayPort</b>                           | 1                                                        |
| <b>3.5mm Audio In</b>                        | 1                                                        |
| <b>3.5mm Audio Out</b>                       | 1                                                        |
| <b>SPDIF</b>                                 | 1                                                        |
| <b>USB 3.0</b>                               | 4                                                        |
| <b>USB 2.0</b>                               | 1                                                        |
| <b>USB 2.0 Type B</b>                        | 2                                                        |
| <b>USB 3.1 Type C</b>                        | 1                                                        |
| <b>OPS PC Slot</b>                           | 1                                                        |
| <b>RS232</b>                                 | 1                                                        |
| <b>Ethernet LAN (RJ45)</b>                   | 1                                                        |
| <b>WIFI Module Slot</b>                      | 1                                                        |
| <b>Voltage</b>                               | 100-240 VAC                                              |
| <b>Consumption With Slot-In PC (typical)</b> | 380W                                                     |
| <b>Stand-by</b>                              | <0.5W                                                    |
| <b>On Screen Display</b>                     | Input, Volume, Backlight, Audio, Screen, Display, Adjust |
| <b>Temperature</b>                           | 32-104º F (0 - 40º C)                                    |
| <b>Humidity (non-condensing)</b>             | 20-80%                                                   |
| <b>Touch Technology</b>                      | Infrared                                                 |
| <b>Touch Points</b>                          | Windows: 33, Android: 20                                 |
| <b>Tip Detection</b>                         | Dual tips, 2.5mm and 8mm                                 |
| <b>Net (lbs)</b>                             | 96.78                                                    |
| <b>Gross (lbs)</b>                           | 122.14                                                   |
| <b>Net (kg)</b>                              | 43.90                                                    |
| <b>Gross (kg)</b>                            | 55.40                                                    |
| <b>Packaging (in.)</b>                       | 65.35 x 41.14 x 9.65                                     |
| <b>Physical (in.)</b>                        | 59.41 x 37.61 x 4.69                                     |
| <b>Packaging (mm)</b>                        | 1660 x 1045 x 245                                        |
| <b>Physical (mm)</b>                         | 1509.1 x 955.4 x 119.1                                   |

|                                    |                                                                                                                                                                                                           |
|------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>VESA Compatible</b>             | 600 x 400 mm                                                                                                                                                                                              |
| <b>Warranty</b>                    | 3-year limited warranty on parts, labor and backlight, onsite warranty                                                                                                                                    |
| <b>Recycle/Disposal</b>            | Please dispose of in accordance with local, state or federal laws.                                                                                                                                        |
| <b>Package Contents</b>            | IFP6552 display, Power cable, Remote control, USB Type-C cable, USB Touch cable, Touch pen x 2, Quick Start Guide, RS232 adapter, Clamp x 5, Camera Plate, Screw x 8, HDMI cable, Eraser, AAA Battery x 2 |
| <b>Regulations</b>                 | cTUVus, FCC, ENERGY STAR 7.0, Mexico Energy, CE, CB, RoHS, ErP, WEEE                                                                                                                                      |
| <b>Battery Chemistry</b>           | Lithium                                                                                                                                                                                                   |
| <b>Ethernet LAN</b>                | (10/100/1000M) (USB Type-C 10/100, Android & PC 10/100/1000)                                                                                                                                              |
| <b>Wifi</b>                        | Wi-Fi 6 (802.11ax (a/b/g/n/ac/ax))                                                                                                                                                                        |
| <b>Bluetooth</b>                   | Bluetooth 5.0                                                                                                                                                                                             |
| <b>Display Type</b>                | LCD                                                                                                                                                                                                       |
| <b>Screen Size</b>                 | 65"                                                                                                                                                                                                       |
| <b>Viewable Area (in.)</b>         | 65                                                                                                                                                                                                        |
| <b>Orientation</b>                 | Landscape                                                                                                                                                                                                 |
| <b>Light Source</b>                | LED                                                                                                                                                                                                       |
| <b>Display Resolution</b>          | 3840 x 2160                                                                                                                                                                                               |
| <b>Refresh Rate</b>                | 60Hz                                                                                                                                                                                                      |
| <b>Aspect Ratio</b>                | 16:9                                                                                                                                                                                                      |
| <b>Static Contrast Ratio</b>       | 1,200:1                                                                                                                                                                                                   |
| <b>Backlight Life (Hours)</b>      | 50,000                                                                                                                                                                                                    |
| <b>Brightness</b>                  | 400 nits (without cover glass)                                                                                                                                                                            |
| <b>Response Time (Typical GTG)</b> | 8ms                                                                                                                                                                                                       |
| <b>Viewing Angles</b>              | 178° horizontal, 178° vertical                                                                                                                                                                            |
| <b>Panel Surface</b>               | Anti-glare 7H tempered glass                                                                                                                                                                              |

## Contact Sales

[ViewSonic.com](https://www.viewsonic.com)

888.881.8781 

email: [salesinfo@viewsonic.com](mailto:salesinfo@viewsonic.com) 