



VIEWSONIC 15.6" 1080P PORTABLE MONITOR WITH 60W USB-C AND MINI HDMI | VX1655

Key Features


- 15.6 Inch FHD (1920x1080p) LED portable monitor with 60Hz refresh rate and protective screen cover
- With a weight of 1.7 lbs and a thickness of 0.8 in, this portable monitor slips easily into backpacks and purses
- USB-C connectivity for fast data, audio and video transfer, and 2 way powered 60W USB C charging.
- Comes with a built-in stand with an integrated tripod mount
- The VX1655 supports laptops, PCs, and Apple/Mac operating systems and more with Mini-HDMI, and USB-C inputs



16"
DISPLAY



IPS
PANEL



1920 x 1080
RESOLUTION



Product Description

The ViewSonic® VX1655 is a 15.6" portable monitor with 1080p resolution for incredible visual performance on the go. An ultra-thin panel with the hardware integrated into the kickstand provides incredible stability, discreetly hides cable connectivity, and still allows for use in portrait and landscape modes. A convenient tripod mount is integrated into the stand for additional versatility. In addition, versatile connectivity options include two USB-C ports for 2-way charging, as well as mini-HDMI and a headphone jack. Measuring less than an inch thick and weighing under two pounds, the ultra-slim VX1655 perfectly fits into any bag, briefcase, or backpack so you can work wherever life takes you.

Specifications

UPC	766907022728
Screen Size	16"
Viewable Area (in.)	15.6
Panel Type	IPS
Display Resolution	1920 x 1080
Display Resolution	Full HD (1920x1080)
Static Contrast Ratio	800:1
Dynamic Contrast Ratio	80,000,000:1
Brightness	250 cd/m2
Colors	262K
Color Space Support	6 bit true
Aspect Ratio	16:9
Response Time (Typical GTG)	4ms
Viewing Angles	170º horizontal, 170º vertical
Backlight Life (Hours)	15,000
Panel Surface	Glossy
Refresh Rate	60Hz
PC Resolution (max)	1920 x 1080
Mac® Resolution (max)	1920 x 1080
USB Type C	60W x 2
3.5mm Audio Out	1
Mini HDMI 1.4	1
Internal Speakers	0.8W (x2)
Eco Mode (Conserve)	7w
Eco Mode (optimized)	8w
Consumption (typical)	11w
Consumption (max)	10w
Stand-by	0.5w
Power Supply	External
Cable Organization	No
Physical Controls	Up, Right, Down, Left, Power
On Screen Display	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu
Temperature	32-104º F (0 - 40º C)
Humidity (non-condensing)	20-90%
Frequency Horizontal	mini HDMI 1.4: 15 ~ 82 KHz USB Type C: 23 ~ 83 KHz
Frequency Vertical	mini HDMI 1.4: 48 ~ 60 Hz USB Type C: 48 ~ 60 Hz

Tilt (Forward/Back)

0° – 86°

Regulations

cTUVus, FCC-B, ICES003, Energy Star 8.0, EPEAT Silver, CEC, NOM, Mexico Energy

Net (lbs)

1.7

Gross (lbs)

4

Net (kg)

0.77

Gross (kg)

1.8

Packaging (in.)

16.5 x 15.5 x 3.0

Physical (in.)

14.0 x 8.8 x 0.8

Packaging (mm)

418.0 x 393.0 x 77.0

Physical (mm)

355.0 x 224.0 x 21.0

Package Contents

LCD Display, mini HDM Ito HDMI Cable, USB type-C to type-C cable, Cover, Quick Start Guide

Recycle/Disposal

Please dispose of in accordance with local, state or federal laws.

Warranty

Three-year limited warranty on parts, labor and backlight

UPC: 766907022728

**Contact Sales**[ViewSonic.com](https://www.viewsonic.com)

888.881.8781

email:

salesinfo@viewsonic.com