



VG2757V-2K - 27" 1440P VIDEO CONFERENCING MONITOR WITH WINDOWS HELLO COMPATIBLE IR WEBCAM, 90W USB-C, RJ45 ETHERNET

Key Features



27"
DISPLAY



IPS
PANEL



2560 X 1440
RESOLUTION



WINDOWS HELLO CERTIFIED
Facial Recognition for Safe Single User Sign-On

Product Description

ViewSonic VG2757V-2K-S video conferencing monitor is a docking monitor with premium features such as a pop-up webcam that will help maintain productive meetings whether in the office or working from home, with secure features like a Windows Hello compatible IR camera and Zoom certification for peace of mind on security and reliable conferencing. Premium webcam features to improve visual and audio aspects of video calls such as built in LED lighting, and powerful speakers, along with a QHD 2560 x 1440p resolution for stunning visuals. The IR camera allows for secure and easy sign-on with Windows Hello. Full docking functionality (daisy chain, USB-C single cable connectivity with 90W power delivery, reliable ethernet connectivity) simplifies accessories needed to deploy for IT infrastructure.


Specifications

[More Information](#)

UPC	766907027938
Screen Size	27"
Viewable Area (in.)	27
Panel Type	IPS
Display Resolution	2560 x 1440
Display Resolution	QHD (3440x1440)
Static Contrast Ratio	1,300:1
Dynamic Contrast Ratio	80M:1
Light Source	LED
Brightness	350 cd/m2
Colors	16.7M
Color Space Support	8 bit true
Aspect Ratio	16:9
Response Time (Typical GTG)	5ms
Viewing Angles	178° horizontal, 178° vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-Glare type, Hard-coating (3H), Haze 25%
Refresh Rate	100Hz
PC Resolution (max)	2560 X 1440
Mac® Resolution (max)	2560 X 1440
USB Type A	3
USB Type C	1 (Upstream 90W) 1 (Downstream, 15W)
3.5mm Audio Out	1
Ethernet LAN (RJ45)	1
HDMI 2.0 In	1
DisplayPort	1
DisplayPort Out	1
Internal Speakers	5W (x2)
Eco Mode (Conserve)	129.7
Eco Mode (optimized)	131.8
Consumption (typical)	134.4
Consumption (max)	182.5
Voltage	100-240 VAC, 50-60Hz
Stand-by	0.5
Power Supply	Internal
Cable Organization	No

Kensington Lock Slot	1
Webcam	Yes
Physical Controls	Key 1 (eye), Key 2, Key 3, Key 4, Key 5, Key 6 (power)
On Screen Display	Input Select, Conference Mode, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu
Temperature	32-104° F (0 - 40° C)
Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Frequency Horizontal	15 ~ 150 KHz
Frequency Vertical	50 ~ 100 Hz
Height Adjust	110 mm / 4.3 in
Swivel	60°
Pivot (Right/Left)	90° / 90°
Tilt (Forward/Back)	5° / 40°
Regulations	cTUVus, FCC-B ICES003, Energy Star, EPEAT, CEC, NOM, Mexico Energy
Net (lbs)	17.7
Net Without Stand (lbs)	12
Gross (lbs)	25.3
Net (kg)	8
Net Without Stand (kg)	5.5
Gross (kg)	11.5
Packaging (in.)	27.1 " (W) x 17.8 " (H) x 8.9 " (D)
Physical (in.)	24.12 " (W) x 16.67~21 " (H) x 8.55 " (D)
Physical Without Stand (in.)	24.12 " (W) x 15.36 " (H) x 2.24 " (D)
Packaging (mm)	689 mm (W) x 452 mm (H) x 225 mm (D)
Physical (mm)	612.7 mm (W) x 423.38~533.38 mm (H) x 217.24 mm (D)
Physical Without Stand (mm)	612.7 mm (W) x 390.15 mm (H) x 56.9 mm (D)
Package Contents	LCD Display, Power Cable, HDMI to HDMI Cable, USB Type-C Cable, USB Type-C to Type-A Cable, Quick Start Guide
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Warranty	*Refurbished. 30-day DOA policy for full refund, with a 90-day repair warranty on parts and labor.

UPC: 766907027938



Contact Sales
ViewSonic.com
 888.881.8781
 email: salesinfo@viewsonic.com