


Key Features

Easy Setup | Portable Design | Cinema SuperColor+ | Dual Bluetooth
Harman Kardon Speakers | Smart Connectivity



Product Description


Enjoy instant entertainment in any room with the ViewSonic® M2e portable smart LED projector. Simply power on the projector and its advanced instant auto focus and auto keystone features deliver a perfectly proportioned picture within seconds. Full HD resolution and 125% Rec.709 color accuracy deliver incredibly vivid and lifelike images, while Harman Kardon speakers provide immersive stereo sound. Smart connectivity options include WiFi for wireless screen mirroring from smart devices, Bluetooth for versatile audio, and USB-C for direct streaming from Switch gaming consoles. Compact and lightweight, the M2e delivers big-screen entertainment in the living room, kids' room or in the backyard, or it can be used as a business projector and carried from office-to-office, or slipped into a briefcase or backpack and taken on the road.



1920 x 1080
RESOLUTION



1,000 LED
LUMENS



1.21
THROW RATIO

Contact Sales

- call: 888.881.8781
- email: salesinfo@viewsonic.com
- visit: viewsonic.com

Display:

Type:	DLP LED
Resolution Type:	Full HD (1920x1080)
Resolution:	1920 x 1080
Brightness (Lumens):	1,000 LED
Display Size (in.):	100
Throw Distance:	0.65m-2.68m (80°@2.14m)
Throw Ratio:	1.21
Keystone:	Vertical (+/- 40°) / Horizontal (+/- 40°)
Lens:	Fixed Zoom
Light Source (watt):	RGGB LED
Light Source Life, Normal (hours):	30000
Color Depth:	1.07B Color (R/G/B 10bit)
Dynamic Contrast Ratio:	3,000,000:1
Aspect Ratio:	16:9

Video Signal:

Frequency Horizontal:	15K-102KHz
Frequency Vertical:	23-120Hz

Compatibility:

PC Resolution (max):	1920x1080
PC Resolution (min):	640 x 480
Mac® Resolution (max):	1920x1080
Mac® Resolution (min):	640 x 480

Connector:

USB 2.0 Type A(1), USB 3.1 Type C(1), Card Reader(Micro SD), 3.5mm Audio Out(1), HDMI 1.4 (with HDCP 1.4)(1), Wifi(5Gn), Bluetooth Audio-in(1 (BT4.2)), Bluetooth Audio-out(1 (BT4.2))

Audio:

Internal Speakers:	3W (x2)
--------------------	---------

Power:

Voltage:	Input: 100~240V Output: 19VDC / 4.74A
Consumption (typical):	75W
Stand-by:	0.5W

Controls:

Physical Controls:	Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, mode/enter, auto, source
On Screen Display:	Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)

Operating Conditions:

Temperature:	32-104° F (0 - 40° C)
Humidity (non-condensing):	0-90%

Additional Hardware:

Kensington Lock Slot:	1
-----------------------	---

Weight (imperial):

Net (lbs):	2.2
Gross (lbs):	6.4

Weight (metric):

Net (kg):	1.0
Gross (kg):	2.9

Dimensions (imperial) (WxHxD):

Packaging (in.):	10.1 x 10.0 x 6.6
Physical (in.):	7.2 x 7.2 x 2.1

Dimensions (metric) (WxHxD):

Packaging (mm):	258.0 x 255.0 x 167.0
Physical (mm):	184.0 x 184.0 x 54.0

General:

Regulations: FCC, cTUVus, ROHS

PACKAGE CONTENTS: M2e projector, carrying case, power cable, remote control, Quick Start Guide

Warranty: Three-year limited warranty on parts, labor and backlight

Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.

Portability: Portable

UPC: 766907008456

Accessories:

HB10B, PJ-SCW-1001W, PJ-WMK-006, VCB10, VSR100