

# IFP6563 - 65" PCAP 4K 16:9 ANDROID EDLA-CERTIFIED VIEWBOARD INTERACTIVE FLAT PANEL DISPLAY WITH INTEGRATED MICROPHONE AND USB-C

## Key Features

---


- Enterprise-Grade Security
- Optimized for IT Management
- Engaging Meetings with ViewSonic® Software
- Ultra-Responsive PCAP Touch for Seamless Collaboration
- Instantaneous Collaboration
- Easy Access with Quick User Authentication
- Flexible Camera Integration



65"  
DISPLAY



PANEL



RESOLUTION



## Product Description

---

Elevate every meeting with the ViewSonic® ViewBoard® IFP6563 - a 65" interactive flat panel display designed to power productivity in modern boardrooms, conference spaces, and hybrid workflows. Featuring ultra-responsive Projected Capacitive (PCAP) touch technology and a stunning bezel-less 4K display, it ensures smooth, precise interactions and crystal-clear visuals that keep teams engaged. Built on the latest Android™ EDLA platform, it delivers enhanced security, seamless app integration, and future-proof performance. From dynamic brainstorming to high-stakes presentations, the IFP6563 combines enterprise-grade tools with intuitive design to make every session more efficient and impactful. Backed by ViewSonic's robust software ecosystem and engineered for 24/7 reliability, this display is your scalable solution for driving collaboration, streamlining operations, and staying ahead in a fast-moving business world.

# Specifications

	More Information
<b>UPC</b>	766907034226
<b>OS</b>	ViewBoard OS EDLA
<b>GPU</b>	Rockchip RK3576
<b>Memory</b>	16GB LPDDR
<b>Storage</b>	128GB eMMC
<b>Microphone</b>	Beamforming array x 8, full duplex echo cancellation
<b>Internal Speakers</b>	20W (x2)
<b>Subwoofer</b>	20W (x1)
<b>HDMI 2.1 In</b>	4
<b>HDMI Out</b>	1
<b>DisplayPort</b>	1
<b>SPDIF</b>	1
<b>USB Type A</b>	5
<b>USB Type B</b>	3
<b>USB Type C</b>	4 (up to 100W Power Delivery)
<b>RS232</b>	1
<b>Ethernet LAN (RJ45)</b>	2
<b>Line In</b>	1
<b>Voltage</b>	100-240 VAC
<b>Stand-by</b>	<0.5W
<b>Temperature</b>	32-104° F (0 - 40° C)
<b>Non-Operating Temperature</b>	-4°F to 140°F (-20C to 60C)
<b>Humidity (non-condensing)</b>	20-80%
<b>Touch Technology</b>	Projective Capacitive
<b>Touch Points</b>	Windows: 50, Android: 20
<b>Latency</b>	≤10ms
<b>VESA Compatible</b>	600 x 400 mm
<b>NFC</b>	Yes
<b>Warranty</b>	3-year limited warranty on parts, labor and backlight, onsite warranty
<b>Recycle/Disposal</b>	Please dispose of in accordance with local, state or federal laws.
<b>Package Contents</b>	IFP6563, Power Cord (3m), USB-C Cable (1.8m), Remote control, USB Touch Cable (3m), Stylus x 2, Quick Start Guide + Compliance statement, RS232 adapter, Clamp x 5, Camera Plate, Screw x 8 (camera 2+2, wall mount 4), HDMI cable 3m, VB-WIFI-005 WiFi Adapter
<b>Regulations</b>	CTUVus, FCC, Energy 8.0, EPEAT, CEC

<b>Ethernet LAN</b>	(10/100/1000M) (USB Type-C 10/100, Android & PC 10/100/1000)
<b>Wifi</b>	VB-WIFI-005 adapter, 802.11AX + Bluetooth 5.2
<b>Screen Size</b>	65"
<b>Light Source</b>	DLED
<b>Display Resolution</b>	3840 x 2160
<b>Refresh Rate</b>	60Hz
<b>Aspect Ratio</b>	16:9
<b>Static Contrast Ratio</b>	5,000:1
<b>Dynamic Contrast Ratio</b>	5,000:1
<b>Brightness</b>	450 cd/m2
<b>Response Time (Typical GTG)</b>	6.5ms
<b>Viewing Angles</b>	178° horizontal, 178° vertical
<b>Panel Surface</b>	Anti Glare + Anti Flare + Anti-bacteria (9H pencil hardness, 3mm thickness)

UPC: 766907034226



**Contact Sales**

[ViewSonic.com](http://ViewSonic.com)

888.881.8781

email:

[salesinfo@viewsonic.com](mailto:salesinfo@viewsonic.com)