


TD2465 - 24" 1080P MVA 10-POINT TOUCH SCREEN MONITOR WITH ADVANCED ERGONOMICS


Key Features



24
DISPLAY



MVA
PANEL



1920 X 1080
RESOLUTION



Product Description

With responsive in-cell touch technology and an advanced ergonomic design, the ViewSonic® TD2465 touch display delivers hands-on control for industrial applications, office workspaces and classrooms. This 24" (23.8" viewable) Full HD display offers optimized screen performance and 10-point touch tracking that functions effectively whether you're wearing gloves or in a humid climate. From industrial solutions to classroom podiums, the TD2465 puts productivity and interactivity within reach.

Specifications

More Information

UPC	766907020670
Screen Size	24
Viewable Area (in.)	23.8
Panel Type	MVA
Display Resolution	1920 x 1080
Display Resolution	Full HD (1920x1080)
Static Contrast Ratio	3,000:1
Dynamic Contrast Ratio	20M:1
Light Source	LED
Brightness	250 cd/m2
Colors	16.7M
Color Space Support	8 bit (6 bit + Hi-FRC)
Aspect Ratio	16:9

Response Time (Typical GTG)	7ms
Viewing Angles	178° horizontal, 178° vertical
Backlight Life (Hours)	30,000
Panel Surface	Glossy, Hardness 7H
PC Resolution (max)	1920 X 1080
Mac® Resolution (max)	1920 X 1080
USB Type A	2
USB 2.0 Type B	1
3.5mm Audio In	1
3.5mm Audio Out	1
VGA	1
HDMI 1.4 In	1
DisplayPort	1
Touch Technology	Projective Capacitive
Touch Points	10-Point Touch
Internal Speakers	2W (x2)
Eco Mode (Conserve)	20
Eco Mode (optimized)	22
Consumption (typical)	24
Consumption (max)	26
Voltage	AC 100-240V (universal), 50-60Hz
Stand-by	0.5
Power Supply	Internal
Cable Organization	No
Headphone Hook	No
Physical Controls	1, 2, Up, Down, Power
On Screen Display	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Setup Menu, Memory Recall
Temperature	32-104° F (0 - 40° C)
Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Frequency Horizontal	24 ~ 82 KHz
Frequency Vertical	50 ~ 75 Hz
Tilt (Forward/Back)	5° / 20°
Regulations	cTUVus, FCC-B, ICES003, Energy Star, EPEAT, CEC, NOM, Mexico Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, UKCA, RCM
Net (lbs)	12.5

Net Without Stand (lbs)	10.4
Gross (lbs)	15.8
Net (kg)	5.7
Net Without Stand (kg)	4.7
Gross (kg)	7.2
Packaging (in.)	25.5 " (W) x 16.8 " (H) x 5.4 " (D)
Physical (in.)	21.6 " (W) x 15.82 " (H) x 7.8 " (D)
Physical Without Stand (in.)	21.6 " (W) x 12.8" (H) x 1.9 " (D)
Packaging (mm)	647 mm (W) x 426 mm (H) x 138 mm (D)
Physical (mm)	550 mm (W) x 401 mm (H) x 198 mm (D)
Physical Without Stand (mm)	550 mm (W) x 326 mm (H) x 49 mm (D)
Package Contents	TD2465 x1, 3-pin Plug x1, HDMI Cable (v1.4; Male-Male) x1, USB A/B Cable (v3.2; Male-Male) x1, Quick Start Guide x1
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Warranty	*Refurbished. 30-day DOA policy for full refund, with a 90-day repair warranty on parts and labor.

UPC: 766907020670



Contact Sales

ViewSonic.com

888.881.8781

email: salesinfo@viewsonic.com