


## 4,000 ANSI LUMENS WXGA LAMP-FREE LASER INSTALLATION PROJECTOR | LSD400W

### Key Features

---


- **RUNS FOR YEARS WITH MINIMAL MAINTAINENCE:** Runs for up to 30,000 hours with zero lamp replacements, keeping maintenance low and uptime high.
- **STAYS BRIGHT IN ANY ROOM:** At 4,000 ANSI lumens, images stay bright in well-lit classrooms and conference rooms without washing out color or detail.
- **SHARP, READABLE IMAGES AT ANY SCREEN SIZE:** A precise 0.65" DMD chip and WXGA resolution produce crisp text and vivid images at any screen size.
- **NO FILTER TO CLEAN OR REPLACE:** The IP6X-rated sealed engine blocks dust without a filter to clean or replace.
- **NO WARM-UP, NO WAIT:** Powers on to full brightness instantly with no warm-up and no cooldown required.
- **COMPACT ENOUGH TO FIT ANYWHERE:** 32% smaller than previous models, simplifying installation and reducing shipping and storage costs.



30 - 300 in. / 0.76 - 7.62 m  
**DISPLAY**



**PANEL**



WUXGA RB(1920 x 1200)  
**RESOLUTION**



### Product Description

---

The LSD400W WXGA laser projector brings reliable, lamp-free projection to classrooms and meeting rooms where budget matters as much as performance. This latest generation of laser phosphor technology delivers up to 30,000 hours of use with no lamp replacements, reducing maintenance and lowering the total cost of ownership. It also uses up to 49% less power than traditional lamp projectors, making long-term value easy to justify. A precise 0.65" DMD chip and WXGA resolution keep text crisp and images vivid at any screen size. And with 4,000 ANSI lumens, images stay bright even in well-lit classrooms and conference rooms without washing out color or detail. At 32% smaller than previous models, the LSD400W fits into tighter spaces and simplifies installation. Flexible features like full 360° projection and keystone correction make it easy to handle challenging setups. For rooms that need reliable projection day after day, the LSD400W keeps running without lamp replacements, filter maintenance or warm-up delays.

# Specifications

|                                             | More Information                                                |
|---------------------------------------------|-----------------------------------------------------------------|
| UPC                                         | 766907034325                                                    |
| Light Source                                | Laser                                                           |
| Display Resolution                          | WXGA (1280x800)                                                 |
| Display Resolution                          | 1280 x 800                                                      |
| Brightness (Lumens)                         | 4,000 ANSI                                                      |
| Screen Size                                 | 30 - 300 in. / 0.76 - 7.62 m                                    |
| Throw Distance                              | 1.00m - 11.11m / 3.28 ft - 36.45 ft (100"@3.33m)                |
| Throw Ratio                                 | 1.544 - 1.72                                                    |
| Offset                                      | 124%+/-10%                                                      |
| Keystone                                    | Vertical ( $\pm 30^{\circ}$ ) / Horizontal ( $\pm 30^{\circ}$ ) |
| Lens                                        | 1.1x optical zoom                                               |
| Light Source Life, Normal (hours)           | 20000                                                           |
| Light Source Life, Dynamic Eco-Mode (hours) | 30000                                                           |
| Color Depth                                 | 1.07 Billion Colors                                             |
| Dynamic Contrast Ratio                      | 3,000,000:1                                                     |
| Aspect Ratio                                | 16:10                                                           |
| Input Lag                                   | 25ms                                                            |
| Lens Shift                                  | N/A (Digital Zoom: 0.8x-2.0x)                                   |
| Frequency Horizontal                        | 15K-102KHz                                                      |
| Frequency Vertical                          | 24-120Hz                                                        |
| PC Resolution (max)                         | WUXGA RB(1920 x 1200)                                           |
| PC Resolution (min)                         | VGA(640 x 480)                                                  |
| Mac® Resolution (max)                       | WUXGA RB(1920 x 1200)                                           |
| Mac® Resolution (min)                       | VGA(640 x 480)                                                  |
| USB 2.0 Type A                              | 1 (5V/1.5A) Power, Service                                      |
| 3.5mm Audio Out                             | 1                                                               |
| Control (RS232)                             | 1                                                               |
| HDMI 1.4 (with HDCP 1.4)                    | 2                                                               |
| Internal Speakers                           | 3W (x1)                                                         |
| Voltage                                     | 100-240V+/- 10%, 50/60Hz AC                                     |
| Consumption (typical)                       | 114W                                                            |
| Stand-by                                    | <0.5W                                                           |
| Physical Controls                           | Keypad, Power key                                               |

**On Screen Display**

Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)

**Temperature**

32-104° F (0 - 40° C)

**Normal**

30dB

**Eco-Mode**

25dB

**Kensington Lock Slot**

1

**Net (lbs)**

6.83

**Gross (lbs)**

10.14

**Net (kg)**

3.1

**Packaging (in.)**

15.75" x 11.02" x 6.10"

**Physical (in.)**

11.26" x 8.5" x 5.08"

**Packaging (mm)**

400 x 280 x 155mm

**Physical (mm)**

286 x 216 x 129mm

**Regulations**

cTUVus, CE, FCC, RoHS, REACH, EEE

**Package Contents**

Projector, power cable, remote control, Quick Start Guide

**Warranty**

Three-year limited warranty on parts and labor, 1st year free Express Exchange® service. (One year Express Exchange Service requires product registration).

**Recycle/Disposal**

Please dispose of in accordance with local, state or federal laws.

UPC: 766907034325

**Contact Sales**

[ViewSonic.com](http://ViewSonic.com)

888.881.8781

email:

[salesinfo@viewsonic.com](mailto:salesinfo@viewsonic.com)