



## LSD600W - 6,000 ANSI LUMENS WXGA LASER INSTALLATION PROJECTOR

### Key Features

- 3rd Generation Laser Phosphor Technology: Up to 30,000-hour maintenance-free lifespan.
- 6,000 ANSI Lumens: High-brightness performance for expansive, well-lit venues.
- Eco-Friendly Design: Consumes up to 62% less power than comparable lamp-based projectors.
- DLP 0.65" DMD Chip: Superior native contrast for deeper blacks and enhanced visual depth.
- Ultimate Installation Flexibility: 1.3x optical zoom, H/V keystone, and 360° projection.

### Product Description

The ViewSonic® LSD600W is a powerhouse addition to the Luminous Superior Series, delivering high-brightness, lamp-free projection for corporate auditoriums, large boardrooms, and public venues. Adopting advanced 3rd generation laser phosphor technology, it provides 6,000 ANSI Lumens of consistent brightness for up to 30,000 hours, entirely eliminating the need for frequent bulb replacements and toxic mercury disposal. Designed for professional-grade reliability and sustainability, the LSD600W is 32% more compact than previous generations and features an IP5X sealed optical engine to ensure impeccable image quality in dust-prone environments. With a high-contrast 0.65" DMD chip, it delivers exceptional clarity and legibility for large-scale presentations. Its versatile setup options—including 360° orientation, 1.3x optical zoom, and comprehensive LAN control—make it a seamless, high-impact solution for modern installation projects.

### Specifications

	More Information
<b>UPC</b>	766907038194
<b>Light Source</b>	Laser Phosphor System
<b>Display Resolution</b>	WXGA (1280x800)
<b>Display Resolution</b>	1280 x 800
<b>Brightness (Lumens)</b>	6,000 ANSI
<b>Throw Distance</b>	0.76m - 9.95m / 2.49 ft - 32.64 ft (100" @ 2.54m)
<b>Throw Ratio</b>	1.18 - 1.54
<b>Keystone</b>	Vertical (± 30°) / Horizontal (± 30°)
<b>Lens</b>	1.3x optical zoom
<b>Light Source Life, Normal (hours)</b>	20000
<b>Light Source Life, Dynamic Eco-Mode (hours)</b>	30000
<b>Dynamic Contrast Ratio</b>	3,000,000:1
<b>Aspect Ratio</b>	16:10
<b>Input Lag</b>	25ms

<b>Frequency Horizontal</b>	15K-102KHz
<b>Frequency Vertical</b>	24-120Hz
<b>USB 2.0 Type A</b>	1 (5V/1.5A) Power, Service
<b>3.5mm Audio Out</b>	1
<b>Control (RS232)</b>	1
<b>HDMI 1.4 (with HDCP 1.4)</b>	2
<b>Internal Speakers</b>	15W (x1)
<b>Audible Noise (Normal)</b>	32dB
<b>Audible Noise (Eco)</b>	27dB
<b>Voltage</b>	100-240V+/- 10%, 50/60Hz AC
<b>Consumption (typical)</b>	165W
<b>Stand-by</b>	<0.5W
<b>Physical Controls</b>	Keypad, Power key
<b>On Screen Display</b>	Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)
<b>Temperature</b>	32-104° F (0 - 40° C)
<b>Kensington Lock Slot</b>	1
<b>Net (lbs)</b>	6.4
<b>Gross (lbs)</b>	10.14
<b>Net (kg)</b>	2.9
<b>Gross (kg)</b>	4.6
<b>Packaging (in.)</b>	15.75 x 11.02 x 6.10
<b>Physical (in.)</b>	11.26 x 8.50 x 5.08
<b>Packaging (mm)</b>	400 x 280 x 155
<b>Physical (mm)</b>	286 x 216 x 129
<b>Regulations</b>	cTUVus, CE, FCC, RoHS, REACH, EEE
<b>Package Contents</b>	Projector, power cable, remote control, Quick Start Guide
<b>Warranty</b>	Three-year limited warranty on parts and labor, 1st year free Express Exchange® service. (One year Express Exchange Service requires product registration).
<b>Recycle/Disposal</b>	Please dispose of in accordance with local, state or federal laws.

UPC: 766907038194



## Contact Sales

[ViewSonic.com](http://ViewSonic.com)

888.881.8781

email: [salesinfo@viewsonic.com](mailto:salesinfo@viewsonic.com)