



## VG2248 - 22" 1080P ERGONOMIC 40-DEGREE TILT IPS MONITOR WITH HDMI, DP, AND VGA

### Key Features

---




Future Proof inputs for flexible connectivity options



22"  
DISPLAY



IPS  
PANEL



1920 x 1080  
RESOLUTION



### Product Description

---

Designed for the modern day office, the ViewSonic® VG2248 monitor delivers an efficient end-to-end enterprise experience. Featuring SuperClear® IPS panel technology and 1080p resolution, this 22" (21.5" viewable) monitor delivers crisp and clear images from nearly any viewing angle. For enhanced productivity, an advanced ergonomic design offers a wide range of customizable adjustments for maximum comfort including pivot, swivel, height adjustment, and tilt. With the ability to tilt an impressive 40-degrees, the VG2248 is ideal for users who prefer to work while standing up, as well as for those who like to use their screen for group discussions. Versatile connectivity options include HDMI, DisplayPort, VGA, and USB. This monitor is also shipped in eco-friendly biodegradable packaging, along with an easy-to-install quick release stand that makes for simple out-of-the box setup. The quick release stand also includes an integrated client mount and cable management features, making this monitor perfect for deployment in cloud-based environments.

# Specifications

|                             | More Information                 |
|-----------------------------|----------------------------------|
| UPC                         | 766907988918                     |
| Screen Size                 | 22"                              |
| Viewable Area (in.)         | 21.5                             |
| Panel Type                  | IPS                              |
| Display Resolution          | 1920 x 1080                      |
| Static Contrast Ratio       | 1,000:1                          |
| Dynamic Contrast Ratio      | 50,000,000:1                     |
| Light Source                | WLED                             |
| Brightness                  | 250 cd/m2                        |
| Colors                      | 16.7M                            |
| Color Space Support         | 6 bits                           |
| Aspect Ratio                | 16:9                             |
| Response Time (Typical GTG) | 14ms                             |
| Response Time (GTG w/OD)    | 7ms                              |
| Viewing Angles              | 178º horizontal, 178º vertical   |
| Backlight Life (Hours)      | 30,000                           |
| Panel Surface               | Anti-glare, Hard coating (3H)    |
| PC Resolution (max)         | 1920 x 1080                      |
| Mac® Resolution (max)       | 1920 x 1080                      |
| USB Type A                  | 4                                |
| USB Type B                  | 1                                |
| VGA                         | 1                                |
| HDMI 1.4 In                 | 1                                |
| DisplayPort                 | 1                                |
| Internal Speakers           | 2W (x2)                          |
| Eco Mode (Conserve)         | 14.1W                            |
| Eco Mode (optimized)        | 16.3W                            |
| Consumption (typical)       | 19.6W                            |
| Consumption (max)           | 55.4W                            |
| Voltage                     | AC 100-240V (universal), 50-60Hz |
| Stand-by                    | 0.5W                             |
| Power Supply                | Internal                         |
| Cable Organization          | No                               |

|                                     |                                                                                                                                                                                                                      |
|-------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Kensington Lock Slot</b>         | 1                                                                                                                                                                                                                    |
| <b>Physical Controls</b>            | 1,2,3,4,5,Power                                                                                                                                                                                                      |
| <b>On Screen Display</b>            | Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality) |
| <b>Temperature</b>                  | 32-104° F (0 - 40° C)                                                                                                                                                                                                |
| <b>Humidity (non-condensing)</b>    | 20-90%                                                                                                                                                                                                               |
| <b>VESA Compatible</b>              | 100 x 100 mm                                                                                                                                                                                                         |
| <b>Frequency Horizontal</b>         | 24 ~ 82KHz                                                                                                                                                                                                           |
| <b>Frequency Vertical</b>           | 50 ~ 75Hz                                                                                                                                                                                                            |
| <b>Digital Sync</b>                 | TMDS for HDMI, PCI-E for DisplayPort                                                                                                                                                                                 |
| <b>Height Adjust</b>                | 130 mm / 5.1 in                                                                                                                                                                                                      |
| <b>Swivel</b>                       | 120°                                                                                                                                                                                                                 |
| <b>Pivot (Right/Left)</b>           | 90° / 90°                                                                                                                                                                                                            |
| <b>Tilt (Forward/Back)</b>          | 40° / 5°                                                                                                                                                                                                             |
| <b>Regulations</b>                  | cTUVus, FCC-B, ICES003, Energy Star Certified, EPEAT Certified, TUV Mexico CoC, Mexico Energy                                                                                                                        |
| <b>Net (lbs)</b>                    | 11.9                                                                                                                                                                                                                 |
| <b>Net Without Stand (lbs)</b>      | 6.5                                                                                                                                                                                                                  |
| <b>Gross (lbs)</b>                  | 17.4                                                                                                                                                                                                                 |
| <b>Net (kg)</b>                     | 5.4                                                                                                                                                                                                                  |
| <b>Net Without Stand (kg)</b>       | 2.9                                                                                                                                                                                                                  |
| <b>Gross (kg)</b>                   | 7.9                                                                                                                                                                                                                  |
| <b>Packaging (in.)</b>              | 22.4 x 8.3 x 15.0                                                                                                                                                                                                    |
| <b>Physical (in.)</b>               | 19.6 x 14.7 x 8.0                                                                                                                                                                                                    |
| <b>Physical Without Stand (in.)</b> | 19.6 x 11.7 x 2.0                                                                                                                                                                                                    |
| <b>Packaging (mm)</b>               | 570.0 x 210.0 x 380.0                                                                                                                                                                                                |
| <b>Physical (mm)</b>                | 498.5 x 372.7 x 202.2                                                                                                                                                                                                |
| <b>Physical Without Stand (mm)</b>  | 498.5 x 296.9 x 50.0                                                                                                                                                                                                 |
| <b>Package Contents</b>             | VG2248 Display, Power Cable, DP to DP Cable, USB 3.0 Upstream Cable, Quick Start Guide                                                                                                                               |
| <b>Recycle/Disposal</b>             | Please dispose of in accordance with local, state or federal laws.                                                                                                                                                   |
| <b>Warranty</b>                     | *Refurbished. 30-day DOA policy for full refund, with a 90-day repair warranty on parts and labor.                                                                                                                   |

UPC: 766907988918



**Contact Sales**  
[ViewSonic.com](http://ViewSonic.com)  
888.881.8781  
email: [salesinfo@viewsonic.com](mailto:salesinfo@viewsonic.com)