





VP2768A - 27" COLORPRO™ 1440P IPS MONITOR WITH 90W USB C, RJ45, SRGB, AND DAISY CHAIN


Key Features



27"
DISPLAY



IPS
PANEL



2560 x 1440
RESOLUTION



Product Description



The ViewSonic® VP2768a is a 27" Quad HD monitor that delivers color accuracy crucial for professional applications. With a sleek frameless design and edge-to-edge SuperClear® IPS panel, this monitor provides an incredible viewing experience ideal for content creation and enterprise workstations. USB-C connectivity helps to simply your workspace by delivering audio, video, data and up to 90W of power delivery over a single universal cable. In addition, DisplayPort out enables seamless daisy chaining to a second monitor. To ensure precise, uniform color, each of our monitors is factory calibrated to deliver an amazing Delta E<2 value for incredible color accuracy. An integrated color uniformity function ensures consistent chromaticity across the screen, while a 14-bit 3D look-up table generates a stunningly smooth palette of 4.39 trillion colors. Add to that 6-axis color adjustment functionality, and this monitor provides the ultimate color processing capability for professional applications.

Specifications

	More Information
UPC	766907012378
Screen Size	27"
Viewable Area (in.)	27
Panel Type	IPS
Display Resolution	2560 x 1440
Display Resolution	QHD (2560x1440)
Static Contrast Ratio	1,000:1
Light Source	LED
Brightness	350 cd/m2
Colors	16.7M
Color Space Support	8 bits
Aspect Ratio	16:9
Response Time (Typical GTG)	5ms
Viewing Angles	178º horizontal, 178º vertical
Panel Surface	Anti-glare, Hard coating (3H)
PC Resolution (max)	2560 x 1440
Mac® Resolution (max)	2560 x 1440
USB Type A	2
USB Type B	1
USB Type C	1
3.5mm Audio Out	1
Ethernet LAN (RJ45)	1
HDMI 1.4 In	2
DisplayPort	1
DisplayPort Out	1
Eco Mode (Conserve)	22.5W
Eco Mode (optimized)	26.5W
Consumption (typical)	32W
Consumption (max)	35W
Voltage	AC 100-240V (universal), 50-60Hz
Stand-by	0.3W
Power Supply	Internal
Cable Organization	No

Kensington Lock Slot	1
Physical Controls	1,2,3,4,5,6 (Power)
On Screen Display	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)
Temperature	32-104° F (0 - 40° C)
Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Frequency Horizontal	15 ~ 90 KHz
Frequency Vertical	24 ~ 75 Hz
Height Adjust	130 mm / 5.1 in
Swivel	60°
Tilt (Forward/Back)	6° / 21°
Regulations	cTUVus, FCC-B, ICES003, Energy Star, EPEAT, MX-CoC, Mexico Energy, CEC
Net (lbs)	15.2
Net Without Stand (lbs)	9.7
Gross (lbs)	21.2
Net (kg)	6.9
Net Without Stand (kg)	4.4
Gross (kg)	9.6
Packaging (in.)	28.3 x 18.1 x 10.6
Physical (in.)	24.1 x 16.1 x 8.5
Physical Without Stand (in.)	24.1 x 13.9 x 2.0
Packaging (mm)	720.0 x 460.0 x 268.0
Physical (mm)	613.0 x 410.0 x 215.0
Physical Without Stand (mm)	613.0 x 353.0 x 50.0
Package Contents	VP2768a Display, Power Cable, DP to DP Cable, USB Type C cable, USB Type B Uplink Cable, Quick Start Guide
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Warranty	*Refurbished. 30-day DOA policy for full refund, with a 90-day repair warranty on parts and labor.

UPC: 766907012378



Contact Sales
[ViewSonic.com](https://www.viewsonic.com)
888.881.8781
email: salesinfo@viewsonic.com