


TD2220-S

## Key Features


---



22"  
DISPLAY



TN  
PANEL



RESOLUTION



## Product Description

---

The 22" (21.5" viewable) ViewSonic TD2220 is a multi-touch Full HD LED backlit monitor with 1920x1080 resolution, integrated speakers, DVI & VGA inputs and VESA mountable design. It has 20,000,000:1 MEGA Dynamic Contrast Ratio for sharp crisp images, and Eco-mode come standard in the new 22" (21.5" viewable) offering. Perfect for both commercial and consumer applications, the TD2220 supports the USB HID Touch driver and is fully compatible with Windows 7. The TD2220 is a one-stop solution for your multi-touch monitor needs. You will also get the most out of your investment with ViewSonic's strongest pixel performance guarantee, 3-year limited warranty, as well as ENERGY STAR and EPEAT certifications. Touch the Difference with the ViewSonic TD2220 interactive multi-touch display.

## Specifications

---

---

### More Information

UPC

766907864113

Screen Size

22"

---

|                                    |                                                                                                                                                                                                                                                                 |
|------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Panel Type</b>                  | TN                                                                                                                                                                                                                                                              |
| <b>Display Resolution</b>          | 1920 x 1080                                                                                                                                                                                                                                                     |
| <b>Static Contrast Ratio</b>       | 1,000:1                                                                                                                                                                                                                                                         |
| <b>Dynamic Contrast Ratio</b>      | 20M:1                                                                                                                                                                                                                                                           |
| <b>Light Source</b>                | LED                                                                                                                                                                                                                                                             |
| <b>Brightness</b>                  | 200 cd/m2                                                                                                                                                                                                                                                       |
| <b>Response Time (Typical GTG)</b> | 5ms                                                                                                                                                                                                                                                             |
| <b>Viewing Angles</b>              | 170º horizontal, 160º vertical                                                                                                                                                                                                                                  |
| <b>Backlight Life (Hours)</b>      | 40,000                                                                                                                                                                                                                                                          |
| <b>Panel Surface</b>               | 8H Scratch Resistant Surface Hardness                                                                                                                                                                                                                           |
| <b>USB 2.0 Type A</b>              | 2                                                                                                                                                                                                                                                               |
| <b>USB 2.0 Type B</b>              | 1                                                                                                                                                                                                                                                               |
| <b>3.5mm Audio In</b>              | 1                                                                                                                                                                                                                                                               |
| <b>DVI-D</b>                       | 1                                                                                                                                                                                                                                                               |
| <b>Touch Technology</b>            | Optical                                                                                                                                                                                                                                                         |
| <b>Touch Points</b>                | 2-Point Touch                                                                                                                                                                                                                                                   |
| <b>Internal Speakers</b>           | 2-watt (x2)                                                                                                                                                                                                                                                     |
| <b>Eco Mode (Conserve)</b>         | 18W                                                                                                                                                                                                                                                             |
| <b>Eco Mode (optimized)</b>        | 21W                                                                                                                                                                                                                                                             |
| <b>Consumption (typical)</b>       | 26W                                                                                                                                                                                                                                                             |
| <b>Consumption (max)</b>           | 43W                                                                                                                                                                                                                                                             |
| <b>Voltage</b>                     | AC 100-240V (universal), 50-60Hz                                                                                                                                                                                                                                |
| <b>Cable Organization</b>          | No                                                                                                                                                                                                                                                              |
| <b>Kensington Lock Slot</b>        | 1                                                                                                                                                                                                                                                               |
| <b>Physical Controls</b>           | 1, 2, Down, Up, Power                                                                                                                                                                                                                                           |
| <b>On Screen Display</b>           | Auto Image Adjust, Contrast/Brightness, Input Select (D-SUB, DVI-D), Audio Adjust (Volume, Mute), Color Adjust (sRGB, Bluish, Cool, Native, Warm, User Color [R,G,B]), Information, Manual Image Adjust (H/V Position, Horizontal Size, Fine Tune, Sharpness, D |
| <b>Temperature</b>                 | 32-104º F (0 - 40º C)                                                                                                                                                                                                                                           |
| <b>Humidity (non-condensing)</b>   | 20-90%                                                                                                                                                                                                                                                          |
| <b>VESA Compatible</b>             | 100 x 100 mm                                                                                                                                                                                                                                                    |
| <b>Frequency Horizontal</b>        | 24~83kHz                                                                                                                                                                                                                                                        |
| <b>Frequency Vertical</b>          | 50~76Hz                                                                                                                                                                                                                                                         |
| <b>Analog Sync</b>                 | Separate Sync                                                                                                                                                                                                                                                   |
| <b>Regulations</b>                 | CE, REACH, WEEE, UkrSEPRO, EAC, cULus, FCC-B, ICES003, Energy Star, EPEAT, UL-MX-CoC, Mexico Energy                                                                                                                                                             |
| <b>Net (lbs)</b>                   | 1085                                                                                                                                                                                                                                                            |
| <b>Net Without Stand (lbs)</b>     | 8.73                                                                                                                                                                                                                                                            |

|                                     |                                                                                                                   |
|-------------------------------------|-------------------------------------------------------------------------------------------------------------------|
| <b>Gross (lbs)</b>                  | 14.22                                                                                                             |
| <b>Net (kg)</b>                     | 4.92                                                                                                              |
| <b>Net Without Stand (kg)</b>       | 3.96                                                                                                              |
| <b>Gross (kg)</b>                   | 6.45                                                                                                              |
| <b>Packaging (in.)</b>              | 22.44 x 16.81 x 8.43                                                                                              |
| <b>Physical (in.)</b>               | 20.1 x 14.4 x 9.5                                                                                                 |
| <b>Physical Without Stand (in.)</b> | 20.1 x 12.2 x 2.6                                                                                                 |
| <b>Packaging (mm)</b>               | 570 x 427 x 214                                                                                                   |
| <b>Physical (mm)</b>                | 511.5 x 364.6 x 240.0                                                                                             |
| <b>Physical Without Stand (mm)</b>  | 511.5 x 310.4 x 66.5                                                                                              |
| <b>Package Contents</b>             | TD2220 display, power cable, audio cable, VGA cable, DVI cable, USB Cable, Quick Start Guide, ViewSonic Wizard CD |
| <b>Power Management</b>             | ENERGY STAR® standards                                                                                            |
| <b>Recycle/Disposal</b>             | Please dispose of in accordance with local, state or federal laws.                                                |
| <b>Warranty</b>                     | *Refurbished. 30-day DOA policy for full refund, with a 90-day repair warranty on parts and labor.                |
| <b>Classification</b>               | Discontinued, Refurbished                                                                                         |

UPC: 766907864113



### Contact Sales

[ViewSonic.com](http://ViewSonic.com)

888.881.8781

email:

[salesinfo@viewsonic.com](mailto:salesinfo@viewsonic.com)