

VIEWSONIC 34" UWQHD CURVED VIDEO CONFERENCING MONITOR WITH WINDOWS HELLO COMPATIBLE IR WEBCAM, 100W USB-C, RJ45 | VG3457CV

Key Features

- Versatile Monitor: 34 Inch 21:9 UWQHD (3440x1440p) curved monitor with thin bezels and 100Hz refresh rate
- Feature-Packed Camera: Ergonomic 5MP pop-up camera that is Zoom and Windows Hello certified
- Video Conferencing Monitor: Built-in microphone, front-firing 5W speakers, and a 1080p camera
- Ditch The Dock: Ethernet RJ45 and USB-C connectivity for fast data, audio and video transfer, 100W charging over one cable
- Ergonomic Stand: Advanced ergonomics (40-degree tilt, swivel, and height) for all-day comfort
- Flexible Connectivity: The VG3457CV supports PC, Mac and more with USB-C, RJ45, HDMI 20, DisplayPort In, and USB



34"
DISPLAY



MVA
PANEL



3440 X 1440
RESOLUTION



WINDOWS HELLO CERTIFIED
Facial Recognition for Safe Single User Sign-On

Product Description


ViewSonic VG3457CV video conferencing monitor is an ultrawide docking monitor with premium features such as a Zoom certified pop-up webcam that will help maintain productive meetings whether in the office or working from home. Premium webcam features to improve visual and audio aspects of video calls such as built in LED lighting, and powerful speakers. The IR camera allows for secure and easy sign-on with Windows Hello. The 21:9 aspect ratio provides extra screen space, while the 1500R curved screen offers an immersive viewing experience. Reliable network connectivity is ensured with an integrated Ethernet port, and the latest USB Type-C connectivity provides up to 100W power delivery to your laptop. Additionally, the integrated USB hub allows for easy connecting and charging of peripherals and accessories.

Specifications

UPC	766907026078
Screen Size	34"
Viewable Area (in.)	34
Panel Type	MVA
Display Resolution	3440 x 1440
Display Resolution	UWQHD (3440x1440)
Static Contrast Ratio	3,000:1
Dynamic Contrast Ratio	80,000,000:1
Brightness	350 cd/m2
Colors	1.07B
Color Space Support	10 bit (8 bit + FRC)
Aspect Ratio	21:9
Response Time (Typical GTG)	5ms
Viewing Angles	178° horizontal, 178° vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-Glare type, Hard-coating (3H), Haze 25%
Curvature	1500R
Refresh Rate	100Hz
PC Resolution (max)	3440 X 1440
Mac® Resolution (max)	3440 X 1440
USB Type A	4
USB Type C	100W x 1, 15W x 1
3.5mm Audio Out	1
Ethernet LAN (RJ45)	1
HDMI 2.0 In	2
DisplayPort	1
Internal Speakers	5W (x2)
Eco Mode (Conserve)	35W
Eco Mode (optimized)	40W
Consumption (typical)	45W
Consumption (max)	210W
Voltage	AC 100-240V (universal), 50-60Hz
Stand-by	0.5W
Power Supply	Internal
Cable Organization	No
Kensington Lock Slot	1

Temperature	32-104° F (0 - 40° C)
Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Frequency Horizontal	HDMI 2.0, DisplayPort, USB Type C: 30 ~ 150 KHz
Frequency Vertical	HDMI 2.0, DisplayPort, USB Type C: 48 ~ 100 Hz
Height Adjust	110 mm / 4.3 in
Swivel	120°
Tilt (Forward/Back)	5° / 40°
Regulations	cTUVus, FCC-B ICES003, Energy Star, EPEAT, CEC, NOM, Mexico Energy
Net (lbs)	20.9
Net Without Stand (lbs)	15.4
Gross (lbs)	34.2
Net (kg)	9.5
Net Without Stand (kg)	7.0
Gross (kg)	15.5
Packaging (in.)	39 x 19.5 x 9.4
Physical (in.)	31.81 x 16.68~21.01 x 9.3
Physical Without Stand (in.)	31.81 x 15.4 x 4.53
Packaging (mm)	990.0 x 495.0 x 238.0
Physical (mm)	808.0 x 423.7~533.7 x 236.2
Physical Without Stand (mm)	808.0 x 31.3 x 4.53
Package Contents	VG3457CV Display, Power Cable, HDMI to HDMI Cable, USB Type-C Cable (with USB Type A adaptor), Quick Start Guide
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Warranty	Three-year limited warranty on parts, labor and backlight

UPC: 766907026078



Contact Sales

[ViewSonic.com](https://www.viewsonic.com)

888.881.8781

email: salesinfo@viewsonic.com