

SC-T46-L-S

# Key Features

---



# Product Description

---

The ViewSonic SC-T46 discrete thin client uses the powerful Intel Bay Trail N2930 with Linux OS. The SC-T46 is optimized for all the major remote networking protocols including Microsoft RDP with RemoteFX, Citrix HDX, and PCoIP for VMware View—making it a versatile virtualization solution with endless possibilities. The SC-T46 has the horsepower needed to handle a large portion of local processing and graphics rendering, and the flexibility to operate as a stateless device in a VDI-based infrastructure. The SC-T46 is also an energy and space saver, consuming only 16W of power and easily attaching to your VESA-ready monitor with the included bracket. The SC-T46 discrete thin client is the perfect solution for companies seeking the benefits of true PC-like performance, along with simplified management and lower TCO. ViewSonic's thin clients are the smart choice for optimizing your virtual desktop deployment.

# Specifications

---

| More Information    |                                 |
|---------------------|---------------------------------|
| UPC                 | 766907774412                    |
| CPU Processor Type  | Intel Bay Trail Quad-core N2930 |
| CPU Processor Speed | 1.83 GHz                        |
| Graphic Chipset     | Integrated                      |
| Resolution (max)    | 1920 x 1200                     |
| RAM                 | 2GB                             |
| Memory Type         | DDR3 (1333 MHz)                 |

|                                  |                                                                                                                                           |
|----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Operating System</b>          | Linux (Ubuntu 14.04 LTS)                                                                                                                  |
| <b>Supported OS</b>              | N/A                                                                                                                                       |
| <b>Protocols</b>                 | Microsoft RDP (8.0), Citrix ICA/HDX, VMware with PCoIP                                                                                    |
| <b>USB 2.0 Type A</b>            | 3                                                                                                                                         |
| <b>USB 3.0 Type A</b>            | 1                                                                                                                                         |
| <b>DVI-I</b>                     | 1                                                                                                                                         |
| <b>DVI-D</b>                     | 1                                                                                                                                         |
| <b>Ethernet LAN (RJ45)</b>       | 1                                                                                                                                         |
| <b>3.5mm Mic In</b>              | 1                                                                                                                                         |
| <b>3.5mm Audio Out</b>           | 1                                                                                                                                         |
| <b>Ethernet LAN</b>              | 10/100/1000 MB                                                                                                                            |
| <b>Voltage</b>                   | 12V DC; 3A                                                                                                                                |
| <b>Consumption (typical)</b>     | 16W                                                                                                                                       |
| <b>Temperature</b>               | 32-104º F (0 - 40º C)                                                                                                                     |
| <b>Humidity (non-condensing)</b> | 10-90%                                                                                                                                    |
| <b>Storage Capacity</b>          | 8GB                                                                                                                                       |
| <b>Storage Type</b>              | Flash                                                                                                                                     |
| <b>VESA Compatible</b>           | 100 x 100 mm                                                                                                                              |
| <b>Regulations</b>               | FCC(ICES003)/CB/CE EMC/CE R&TTE, WEEE, RoHS Compliant, REACH Compliant                                                                    |
| <b>Package Contents</b>          | SC-T46 thin client, power cord, power adapter, DVI-I to VGA adapter, stand / VESA mounting bracket,Quick Start Guide, ViewSonic Wizard CD |
| <b>Recycle/Disposal</b>          | Please dispose of in accordance with local, state or federal laws.                                                                        |
| <b>Part #</b>                    | SC-T46_L_BK_US0-S                                                                                                                         |
| <b>Warranty</b>                  | *Refurbished. 30-day DOA policy for full refund, with a 90-day repair warranty on parts and labor.                                        |
| <b>Country Of Origin</b>         | Taiwan                                                                                                                                    |
| <b>Classification</b>            | Discontinued, Refurbished                                                                                                                 |
| <b>Packaging (in.)</b>           | 7.9 x 5.0 x 6.2                                                                                                                           |
| <b>Physical (in.)</b>            | 1.6 x 5.6 x 4.1                                                                                                                           |
| <b>Packaging (mm)</b>            | 620 x 455 x 157                                                                                                                           |
| <b>Physical (mm)</b>             | 39.5 x 143 x 103                                                                                                                          |
| <b>Net (lbs)</b>                 | 1,2                                                                                                                                       |
| <b>Gross (lbs)</b>               | 2,7                                                                                                                                       |
| <b>Net (kg)</b>                  | 0,54                                                                                                                                      |
| <b>Gross (kg)</b>                | 1,23                                                                                                                                      |
| UPC: 766907774412                |                                                                                                                                           |



**Contact Sales**  
[ViewSonic.com](https://www.viewsonic.com)

888.881.8781

email:

[salesinfo@viewsonic.com](mailto:salesinfo@viewsonic.com)