

PRO9800WUL - 1920 X 1200 RESOLUTION, 5,500 ANSI LUMENS, 1.25 - 2.13:1 THROW RATIO

Key Features


- 5,500 Lumen Brightness
- Vertical/Horizontal Lens Shift with Centered Lens
- Stackable Design
- 360-degree Installation
- SuperColor: Amazing Color Accuracy



26.2 - 371.4 in. / 0.67 - 9.43m
DISPLAY



PANEL



Up to 1920x1200
RESOLUTION



Product Description

Bright and versatile for any professional installation, the ViewSonic® Pro9800WUL WUXGA projector delivers everything you need for big screens in big venues. Delivering 5,500 lumens of advanced high brightness, this projector is ideal for auditoriums, large boardrooms, houses of worship, and more. Thanks to SuperColor™ technology, content is brought to life with captivating color, crisp graphics, and stunning videos no matter the environment. Designed for installers, this top-notch performer is also easy to deploy and manage with its wide 1.7x optical zoom adjustment, a centered lens design, and a vertical/horizontal lens shift feature that provides extreme flexibility in even the most challenging installations. Thanks to the stackable design of these projectors, light output can be doubled by simply placing one projector on top of the other - perfect for large venues with high ambient light.

Specifications

More Information

UPC	766907848212
Light Source	DLP Lamp
Display Resolution	WUXGA (1920x1200)
Display Resolution	1920 x 1200
Brightness (Lumens)	5,500 ANSI
Screen Size	26.2 - 371.4 in. / 0.67 - 9.43m
Throw Distance	4 - 55.8 ft / 1.2 - 17m
Throw Ratio	1.25 - 2.13:1

Keystone	Vertical ($\pm 30^\circ$) / Horizontal ($\pm 25^\circ$)
Lens	1.7x Manual optical zoom / manual optical focus
Light Source (watt)	370
Light Source Life, Normal (hours)	1500
Light Source Life, Dynamic Eco-Mode (hours)	3500
Color Depth	30 bits, 1.07B Color (10+10+10)
Dynamic Contrast Ratio	15,000:1
Aspect Ratio	16:10
Input Lag	37ms
Lens Shift	Vertical (-12.1%/+20.8%) / Horizontal (+/- 10.3%)
Frequency Horizontal	15-100kHz
Frequency Vertical	24-120Hz
PC Resolution (max)	Up to 1920x1200
Mac® Resolution (max)	Up to 1920x1200
USB 2.0 Type A	1
USB 2.0 Type B	1
Ethernet LAN (RJ45)	1
3.5mm 12V Trigger	1
3.5mm Audio Out	1
3.5mm Audio In	3
Control (RS232)	1
HDMI 1.4 In	1
HDMI MHL	1
DVI-D	1
VGA In	2
VGA Out	1
Composite RCA Video In	1
S-Video In	1
RCA Audio In (L/R)	1
RCA Audio Out	1
3D VESA	1
Wired Remote In	1
Wired Remote Out	1
5-BNC	1
Internal Speakers	7W (x2)
Voltage	100~240VAC (Auto Switching), 50-60Hz (universal)

Consumption (max)	480W
Stand-by	<0.5W
Physical Controls	Power, H/V lens shift, focus, zoom, keystone/arrow keys, left/blank, right/panel key lock, menu/exit, mode/enter, source
On Screen Display	Display, Image, Video, Audio, Basic, Advanced
Temperature	41-104° F (5 - 40° C)
Humidity (non-condensing)	10-85%
Kensington Lock Slot	1
Net (lbs)	18.26
Gross (lbs)	27.31
Net (kg)	8.29
Gross (kg)	12.4
Packaging (in.)	22.68 x 17.17 x 11.46
Physical (in.)	17.51 x 12.81 x 5.82
Packaging (mm)	576 x 436 x 291
Physical (mm)	445 x 325.5 x 147.8
AV Control	AMX Certified, Crestron Certified
Regulations	UL, cUL, FCC, CE, EMC, CB, ROHS, REACH, SVCH, WEEE, ErP, Mexico NOM/ENERGY, PSB, RCM, CCC
Package Contents	Pro9800WUL projector, power cable, VGA cable, laser remote control with batteries, Quick Start Guide, ViewSonic Wizard CD (with User Guide)
Warranty	Three-year limited warranty on parts and labor, 1-year limited warranty on lamp, 1st year free Express Exchange® service. (One year Express Exchange Service requires product registration).
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Classification	Discontinued

UPC: 766907848212



Contact Sales

ViewSonic.com

888.881.8781

email: salesinfo@viewsonic.com