





PRO8800WUL - 1920 X 1200 RESOLUTION, 5,200 ANSI LUMENS, 1.07~1.71:1 THROW RATIO

Key Features


- 5,200 Lumen Brightness
- Vertical Lens Shift with Centered Lens
- PortAll®: Discreet Wireless Streaming
- 4 HDMI Inputs



30 - 300 in. / 0.76 - 7.62 m
DISPLAY



PANEL



1920x1200
RESOLUTION



Product Description

Delivering stunning WUXGA 1920x1200 resolution and 5200 lumens of brightness, the ViewSonic® LightStream® Pro8800WUL is the ideal projector for professional installations, large venues, and business and education environments. With its 1.6x optical zoom, centered lens, vertical lens shift, and HV keystoneing, the Pro8800WUL provides extreme flexibility even in the most challenging installations. Pro8800WUL includes a sleek top cover design for quick lamp and accessory access, while an intuitive PortAll® compartment accommodates additional accessories such as an HDBT receiver, wireless streaming device, or PC stick. The cable management hood hides unsightly cables, and a 4-in-1 power button serves as a central point for LED notifications. Moreover, four HDMI ports and additional audio and video ports allow for extensive connectivity to handle multiple devices without the need to switch cables. Powered by SuperColor™ technology for amazing images, and SonicExpert® technology for incredibly clear sound, the Pro8800HDL delivers professional audiovisual performance.

Specifications

More Information	
UPC	766907830118
Light Source	DLP Lamp
Display Resolution	WUXGA (1920x1200)
Display Resolution	1920 x 1200
Brightness (Lumens)	5,200 ANSI
Screen Size	30 - 300 in. / 0.76 - 7.62 m
Throw Distance	2.26~36.25 ft / 0.69~11.05 m
Throw Ratio	1.07~1.71:1

Keystone	Vertical ($\pm 30^\circ$) / Horizontal ($\pm 30^\circ$)
Lens	1.6x Manual optical zoom / manual optical focus
Light Source (watt)	370
Light Source Life, Normal (hours)	2000
Light Source Life, Dynamic Eco-Mode (hours)	2500
Color Depth	30 bits, 1.07B Color (10+10+10)
Aspect Ratio	16:10
Input Lag	37ms
Lens Shift	Vertical (+/-2.5 - 5%)
Frequency Horizontal	15-100kHz
Frequency Vertical	24-120Hz
PC Resolution (max)	1920x1200
Mac® Resolution (max)	1920x1200
Ethernet LAN (RJ45)	1
3.5mm 12V Trigger	1
3.5mm Audio Out	1
3.5mm Audio In	3
Control (RS232)	1
HDMI 1.4 In	3
HDMI MHL	1
VGA In	2
VGA Out	1
Composite RCA Video In	1
S-Video In	1
Micro USB	1
RCA Audio In (L/R)	1
3D VESA	1
Wired Remote Out	1
5-BNC	1
Internal Speakers	10W (x2)
Voltage	100~240VAC (Auto Switching), 50-60Hz (universal)
Consumption (max)	574W
Stand-by	<0.5W
Physical Controls	Display, Image, Power Management, Basic, Advanced, System, Information
On Screen Display	Power, lens shift, focus, zoom, keystone/arrow keys, left/blank, right/panel key lock, menu/exit, mode/enter, source

Temperature	41-104º F (5 - 40º C)
Humidity (non-condensing)	10-85%
Kensington Lock Slot	1
Net (lbs)	13.89
Gross (lbs)	23.81
Net (kg)	6.3
Gross (kg)	10.8
Packaging (in.)	22.72 (W) x 21.14 (D) x 10.24 (H)
Physical (in.)	19.55 (W) x 12.45 (D) x 5.50 (H)
Packaging (mm)	577 (W) x 537 (D) x 260 (H)
Physical (mm)	496.5 (W) x 316.24 (D) x 139.8 (H)
AV Control	AMX Certified, ATEN Certified, Crestron Certified, Extron Certified, PJ Link Certified
Regulations	EAC, TUV-S Mark(Argentina), India BIS, FCC,CE EMC, CB,CCC, ROHS, REACH, SVHC, WEEE, ErP, Mexico NOM, cTUVus, RCM, CECP
Package Contents	Pro8800WUL projector, power cable, VGA cable, laser remote control with batteries, Quick Start Guide, ViewSonic Wizard CD (with User Guide)
Warranty	Three-year limited warranty on parts and labor, 1-year limited warranty on lamp, 1st year free Express Exchange® service. (One year Express Exchange Service requires product registration).
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Classification	Discontinued

UPC: 766907830118



Contact Sales

ViewSonic.com

888.881.8781

email: salesinfo@viewsonic.com