


## VP2785-4K - 27" 4K UHD ADOBERGB COLORPRO™ IPS MONITOR W/ USB C & HDR10


### Key Features

---


- 4K UHD (3840x2160p) advanced ergonomic, 60Hz IPS monitor deliver lifelike colors
- A three-sided ultra-thin bezel shows off more of your masterpiece, and less of the monitor
- Connect video, audio, data and power with a single USB-C cable and plug in peripherals like USB drives and mice with the USB hub
- Screen wide 99% Adobe RGB, EBU, SMPTE-C, Rec. 709, and DICOM-SIM color spaces, Delta E<2 accuracy, and a smooth palette of 4.39 trillion colors deliver precise, lifelike images
- Quick and easy calibration ensures that the color displayed perfectly matches the original file
- Displays videos as they are intended to be seen with HDR10 content support - giving you a fuller, more immersive viewing experience
- The VP2785-4K supports laptops, PCs, and Apple/Mac operating systems with USB 3.1 Type C, HDMI 2.0 with HDCP 2.2, DisplayPort, and Mini DisplayPort inputs



27"  
**DISPLAY**



IPS  
**PANEL**



3840 x 2160  
**RESOLUTION**



### Product Description

---

Covering 99% of the Adobe RGB color space and 96% DCI-P3, the ViewSonic® VP2785-4K Ultra HD monitor meets the high color standards of photographers, graphic designers, video editors, print departments, and other design professionals. With a sleek and modern design, the VP2785-4K features future-proof DisplayPort technology, as well as HDMI and USB 3.1 type C ports. To ensure precise, uniform color, each of our monitors is factory calibrated to deliver an amazing Delta E<2 value for superior color accuracy. An integrated color uniformity function ensures consistent chromaticity across the screen, while a 14-bit 3D look-up table generates a stunningly smooth palette of 4.39 trillion colors. What's more, productivity-boosting features include an advanced ergonomic design, a built-in ambient light and presence sensor, and a KVM switch. Hardware calibration is also available with the optional ViewSonic Colorbration Kit, which allows you to quickly and easily calibrate the monitor for photography, graphic design, content creation, and other color-critical applications.

# Specifications

	More Information
<b>UPC</b>	766907902112
<b>Screen Size</b>	27"
<b>Viewable Area (in.)</b>	27
<b>Panel Type</b>	IPS
<b>Display Resolution</b>	3840 x 2160
<b>Static Contrast Ratio</b>	1,000:1
<b>Dynamic Contrast Ratio</b>	20M:1
<b>Light Source</b>	LED
<b>Brightness</b>	350 cd/m2
<b>Colors</b>	1.07B
<b>Color Space Support</b>	10bit (8bit + A-FRC)
<b>Aspect Ratio</b>	16:9
<b>Response Time (Typical GTG)</b>	14ms
<b>Response Time (GTG w/OD)</b>	7ms
<b>Viewing Angles</b>	178° horizontal, 178° vertical
<b>Backlight Life (Hours)</b>	30,000
<b>Panel Surface</b>	Anti-glare, Hard coating (3H)
<b>PC Resolution (max)</b>	3840 x 2160
<b>Mac® Resolution (max)</b>	3840 x 2160
<b>USB Type A</b>	3
<b>USB Type B</b>	1
<b>USB Type C</b>	1
<b>3.5mm Audio Out</b>	1
<b>HDMI 2.0 (with HDCP 2.2)</b>	2
<b>DisplayPort</b>	1
<b>Mini DisplayPort</b>	1
<b>Eco Mode (Conserve)</b>	45
<b>Eco Mode (optimized)</b>	55
<b>Consumption (typical)</b>	67
<b>Consumption (max)</b>	70
<b>Voltage</b>	AC 100-240V (universal), 50-60Hz
<b>Stand-by</b>	0.5W
<b>Cable Organization</b>	No

<b>Kensington Lock Slot</b>	1
<b>Physical Controls</b>	1, 2, 3, 4, 5, Power
<b>On Screen Display</b>	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)
<b>Temperature</b>	32-104° F (0 - 40° C)
<b>Humidity (non-condensing)</b>	20-90%
<b>VESA Compatible</b>	100 x 100 mm
<b>Frequency Horizontal</b>	15 ~90KHz
<b>Frequency Vertical</b>	24 ~120Hz
<b>Digital Sync</b>	TMDS, PCI-E
<b>Height Adjust</b>	130 mm / 5.1 in
<b>Swivel</b>	120°
<b>Pivot (Right/Left)</b>	90° / 90°
<b>Tilt (Forward/Back)</b>	5° / 21°
<b>Regulations</b>	UL, cUL, FCC-B, Mexico CoC, CB , CE, WEEE, RoHS, ErP, REACH, TCO6.0, Ukraine, GS, Ergo
<b>Net (lbs)</b>	14.1
<b>Net Without Stand (lbs)</b>	8.7
<b>Gross (lbs)</b>	22.3
<b>Net (kg)</b>	6.4
<b>Net Without Stand (kg)</b>	3.9
<b>Gross (kg)</b>	10.1
<b>Packaging (in.)</b>	28.3 x 10.6 x 18.1
<b>Physical (in.)</b>	24.1 x 21.5 x 8.5
<b>Physical Without Stand (in.)</b>	24.1 x 14.3 x 2.3
<b>Packaging (mm)</b>	720 x 268 x 460
<b>Physical (mm)</b>	612.4 x 545.5 x 215.0
<b>Physical Without Stand (mm)</b>	612.4 x 362.7 x 57.6
<b>Package Contents</b>	VP2785-4K Display, AC/DC Adapter, Power Cable, Mini DP to DisplayPort Cable , USB 3.1 Gen 1 Type-C Cable, USB 3.0 Up Stream Cable, Quick Start Guide, ViewSonic Wizard CD-Rom
<b>Recycle/Disposal</b>	Please dispose of in accordance with local, state or federal laws.

UPC: 766907902112



**Contact Sales**  
[ViewSonic.com](http://ViewSonic.com)  
 888.881.8781  
 email: [salesinfo@viewsonic.com](mailto:salesinfo@viewsonic.com)