


CDE4803-R


## Key Features

---

- Integrated USB multimedia player
  - Free-bundled vController™ software
  - Hospitality mode for automated multi-screen control
  - Control multiple devices with HDMI® CEC and IR pass-through
  - Enhanced viewing comfort
- 



48  
DISPLAY



PANEL



RESOLUTION



## Product Description

---

\*Final Sale. Sold AS-IS with no warranty on parts or labor. 30-day DOA policy for full refund. The ViewSonic® CDE4803 is a great value, high performance 48" Full HD LED commercial display for hotel, restaurant and hospitality environments. In addition to versatile connectivity options, including HDMI, VGA, and SPDIF, the display comes with a simple and convenient USB multimedia playback functionality. With 1920x1080 resolution, 350-nit brightness, wide viewing angles and dual 10W stereo speakers, the slim-bezel CDE4803 delivers vivid images and remarkable sound for superior multimedia performance. The HDMI CEC pass-through support provides one-touch-play, with additional features for multiple connected devices such as HD set-top-boxes, media players, and Blu-ray™ players. An RS232 port with IR pass-through provides automated control for hospitality installation. Creating a more comfortable viewing experience, the display is equipped with Flicker-Free and Blue Light Filter technologies. In addition, free-bundled vController software offers easy maintenance and intuitive interfaces for remote management via a PC server or laptop.

## Specifications

---

### More Information

|                          |              |
|--------------------------|--------------|
| <b>UPC</b>               | 766907825817 |
| <b>OS</b>                | 1.2          |
| <b>Internal Speakers</b> | 10W (x2)     |
| <b>HDMI In</b>           | 2            |
| <b>VGA</b>               | 1            |
| <b>RCA Audio In</b>      | 1            |
| <b>RCA Audio Out</b>     | 1            |
| <b>USB 2.0</b>           | 1            |

|                                     |                                                                                                                                                 |
|-------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Voltage</b>                      | AC 100-240V (universal), 50-60Hz                                                                                                                |
| <b>Consumption (typical)</b>        | 115W (typ)                                                                                                                                      |
| <b>Temperature</b>                  | 41-104° F (5 - 40° C)                                                                                                                           |
| <b>Humidity (non-condensing)</b>    | 20-80%                                                                                                                                          |
| <b>Physical Without Stand (in.)</b> | 42.6 x 24.5 x 2.4                                                                                                                               |
| <b>Physical Without Stand (mm)</b>  | 1081.8 x 623.4 x 59.9                                                                                                                           |
| <b>VESA Compatible</b>              | 400 x 400 / 200 x 200 mm                                                                                                                        |
| <b>Recycle/Disposal</b>             | Please dispose of in accordance with local, state or federal laws.                                                                              |
| <b>Package Contents</b>             | CDE4803 display, power cable, VGA cable, RS232 cable, remote control with batteries, ViewSonic Wizard CD (User Guide and vController™ software) |
| <b>Regulations</b>                  | CE, CB, ErP, WEEE, C-tick, cTUVus, FCC, ENERGY STAR, Mexico Energy                                                                              |
| <b>Classification</b>               | Discontinued                                                                                                                                    |
| <b>Screen Size</b>                  | 48                                                                                                                                              |
| <b>Orientation</b>                  | Landscape                                                                                                                                       |
| <b>Light Source</b>                 | LED                                                                                                                                             |
| <b>Display Resolution</b>           | 1920 x 1080                                                                                                                                     |
| <b>Aspect Ratio</b>                 | 16:9                                                                                                                                            |
| <b>Static Contrast Ratio</b>        | 4,000:1                                                                                                                                         |
| <b>Backlight Life (Hours)</b>       | 30,000                                                                                                                                          |
| <b>Brightness</b>                   | 350 cd/m2                                                                                                                                       |
| <b>Response Time (Typical GTG)</b>  | 8ms                                                                                                                                             |
| <b>Bezel Width (in.)</b>            | Top 0.47 in / Left 0.47 in / Bottom 0.58 in / Right 0.47 in                                                                                     |
| <b>Bezel Width (mm)</b>             | Top 11.9 mm / Left 11.9 mm / Bottom 14.7 mm / Right 11.9 mm                                                                                     |
| <b>Viewing Angles</b>               | 178° horizontal, 178° vertical                                                                                                                  |
| <b>Panel Surface</b>                | Anti-glare, Hard coating 3H                                                                                                                     |
| <b>Operation Rating</b>             | 16/7                                                                                                                                            |

UPC: 766907825817



## Contact Sales

[ViewSonic.com](http://ViewSonic.com)

888.881.8781

email: [salesinfo@viewsonic.com](mailto:salesinfo@viewsonic.com)