




PG706HD - 4000 LUMENS 1080P PROJECTOR WITH RJ45 LAN CONTROL, VERTICAL KEYSTONE AND OPTICAL ZOOM

Key Features


- High brightness 4000 Lumens 1080p projector with advanced visual features
- 1.1x optical zoom, 40 degree vertical keystone for flexible setup
- SuperEco Mode allows the lamp to shine bright for up to 20,000 hours
- A low 16ms input latency provides faster frame-by-frame action for smooth images without delay
- Supports most media players, PCs, Macs, and mobile devices with inputs such as dual HDMI, USB, VGA, Ethernet LAN



30 - 300 in. / 0.76 - 7.62 m
DISPLAY



PANEL



1920 x 1080
RESOLUTION



Product Description

The ViewSonic® PG706HD 1080p projector features 4,000 lumens, Full HD 1920x1080 native resolution, an intuitive, user-friendly design, and a sleek white chassis. Exclusive SuperColor™ technology offers a wide color gamut for beautiful image production in nearly any environment. Equipped with Crestron® LAN controller, this projector makes it easy for IT admin to remotely control and manage multiple projectors from their workstations. With vertical keystone, and extensive connectivity, the PG706HD provides flexible and quick set-up. What's more, an energy-saving SuperEco™ feature reduces power consumption and extends the lamp life by up to 20,000 hours. The PG706HD is the ideal projector for both high-definition presentations and vibrant multimedia entertainment.

Specifications

More Information	
UPC	766907001792
Light Source	DLP Lamp
Display Resolution	Full HD (1920x1080)
Display Resolution	1920 x 1080
Brightness (Lumens)	4,000 ANSI
Screen Size	30 - 300 in. / 0.76 - 7.62 m
Throw Distance	3.3 - 36.0 ft / 1.0 - 11.0 m
Throw Ratio	1.5-1.65
Keystone	Vertical (+/- 40°)

Lens	1.1x optical zoom
Light Source (watt)	245
Light Source Life, Normal (hours)	4000
Light Source Life, Dynamic Eco-Mode (hours)	20000
Color Depth	1.07B Color (R/G/B 10bit)
Aspect Ratio	16:9
Input Lag	37ms
Frequency Horizontal	15K~102KHz
Frequency Vertical	23~120Hz
PC Resolution (max)	1920 x 1080
PC Resolution (min)	640 x 480
Mac® Resolution (max)	1920 x 1080
Mac® Resolution (min)	640 x 480
USB 2.0 Type A	1
Ethernet LAN (RJ45)	1
3.5mm Audio Out	1
3.5mm Audio In	1
Control (RS-232)	1
HDMI 1.4 In	1
HDMI 1.4 (with HDCP 1.4)	1
VGA In	1
VGA Out	1
Composite RCA Video In	1
S-Video In	1
Internal Speakers	10W (x1)
Consumption (typical)	355W
Stand-by	<0.5W
Physical Controls	Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, mode/enter, auto, source
On Screen Display	Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)
Temperature	32-104º F (0 - 40º C)
Humidity (non-condensing)	0-90%
Kensington Lock Slot	1
Net (lbs)	6.2
Gross (lbs)	8.7
Net (kg)	2.8

Gross (kg)	3.9
Packaging (in.)	16.3 x 6.6 x 11.7
Physical (in.)	12.3 x 8.7 x 4.3
Packaging (mm)	415.0 x 168.0 x 297.0
Physical (mm)	312.0 x 222.0 x 108.0
Regulations	FCC, cTUVus, ROHS
Package Contents	PG706HD projector, power cable, VGA cable, remote control, Quick Start Guide
Warranty	Three-year limited warranty on parts and labor, 1-year limited warranty on lamp, 1st year free Express Exchange® service. (One year Express Exchange Service requires product registration).
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.

UPC: 766907001792



Contact Sales
ViewSonic.com
888.881.8781 
email: salesinfo@viewsonic.com 